

INSTALLATION INSTRUCTIONS

DRAG SPECIALTIES SEATS FOR FXD, FXDWG 1991 AND LATER

ATTENTION INSTALLER (if other than owner): Please forward this instruction sheet to the purchaser of this product. These instructions contain valuable information necessary to the end user.

INTRODUCTION: These instructions describe the procedure for properly installing Drag Specialties Seats onto Harley-Davidson® FXD and FXDWG models.

Review instructions carefully before beginning, as they contain important information. Please retain for future reference.

Particularly important information is distinguished in these instructions by the following notations:

NOTE: A NOTE provides key information to make procedures easier or clearer.

CAUTION: A CAUTION indicates special procedures that must be followed to avoid damage to the motorcycle and/or accessories.

WARNING!: A WARNING indicates special procedures that must be followed to avoid injury to a motorcycle operator or person inspecting or repairing the motorcycle.

TOOLS REQUIRED:

#3 Phillips screwdriver

HARDWARE:

Hardware comes installed on your seat for standard model applications.

- 1 – **438881 STEPWASHER**,
use on 1995 and earlier applications
(fenders with welded-in seat mount nuts).
- 1 – **490015A BRACKET**,
use on 1991 through 1995 and 2006-Up FXD
and 1993 through 1995 FXWG.
- 1 – **490014A BRACKET**,
use on 1996 to 2005 Dyna Glides.
- 1 – **438883 SPACER**,
use on 1996 to 2003 Wide Glide only.



PROCEDURE:

1. Begin by placing the bike on the side stand.
2. Remove the stock seat from the bike. Save the rear Phillips-head screw, it will be reused.

NOTE: On all models with factory rubber pads mounted on the fender, the pads must be removed prior to seat installation.

NOTE: On seats for 1996-2005 models, there are three mount holes for the rear bracket. For standard models, the bracket will be mounted in the two forward holes. For Wide Glide models, move the bracket to the two holes farthest to the rear. The brackets are positioned for standard models from the factory.

NOTE: On 1996-2003 Wide Glide models, mount the bracket in the two rear holes. Place the spacer between the bracket and the seat base at the center hole (rear hole on the bracket) for Wide Glide applications.

NOTE: Use the stepwasher on 1995 and earlier models.

3. Slip your new seat over the tab at the front of the frame near the gas tank position on the rear fender.
4. Center the rear of the seat in relation to the sissy bar and fender.
5. With the seat centered, position the rear bracket to line up with the hole in the fender. Remove the seat and tighten the fasteners holding the bracket.
6. Slip the seat onto the front frame tab and attach the rear bracket to the fender, reusing the stock mounting screws and plastic washer.

NOTE: Drag Specialties seats are designed for use with Drag Specialties sissy bars and most H-D® sissy bars.



3501 Kennedy Rd, PO Box 5222, Janesville, WI 53547-5222
P/N 010017