

INSTALLATION INSTRUCTIONS

DRAG SPECIALTIES SEATS FOR 1989-1996 FL, FLHR, FLT, FLHT FLHS

ATTENTION INSTALLER (if other than owner): Please forward this instruction sheet to the purchaser of this product. These instructions contain valuable information necessary to the end user.

INTRODUCTION: These instructions describe the procedure for properly installing Drag Specialties Seats onto FL, FLHR, FLT, FLHT and FLHS models. Review instructions carefully before beginning, as they contain important information. Please retain for future reference.

Particularly important information is distinguished in these instructions by the following notations.

NOTE: A NOTE provides key information to make procedures easier or clearer.

CAUTION: A CAUTION indicates special procedures that must be followed to avoid damage to the motorcycle and/or accessories.

WARNING!: A WARNING indicates special procedures that must be followed to avoid injury to a motorcycle operator or person inspecting or repairing the motorcycle.

ABOUT THE SOLAR REFLECTIVE TECHNOLOGY

Solar reflective technology keeps the seating area cool even in direct sunlight. The process has been shown to reduce surface temperatures by as much as 25°F.

NOTE: The Solar Reflective Technology is only available on select models. See catalog for specific applications.

CAUTION: Use of leather conditioner or chemicals will void warranty. Warm water, mild soap and a soft cloth should be used for cleanup.

TOOLS REQUIRED

#2 Phillips screwdriver
5/8" open-end wrench
7/16" wrench

NOTE: The saddlebags may need to be removed to access and remove the seat hand strap.

NOTE: This seat will fit 1989-1990 models if hand rails are removed or updated to 1991 style. On FLT, FLHT models the rear rack (if equipped) may require removal so seat will bolt directly to fender. These models will require dash extension Drag Specialties PART # 2202-0070.

PROCEDURE

1. Begin by placing bike in side stand.

FLT, FLHT, FLHS MODELS

2. Remove the stock seat from bike. Save the rear Phillips head screw; it will be reused. Proceed to step 5.

ROAD KING MODELS

3. Remove the rear seat from bike. Save the rear Phillips head screw; it will be reused.

4. With a 5/8" wrench, remove the two bolts on the rear of the solo front. These bolts will not be reused. Remove seat.

INSTALLATION

NOTE: The step washer in the rear mount will be required on all applications with a weld-in style fender nut.

5. On your new seat, loosen the two screws securing the rear bracket so the bracket can be adjusted. Install seat, securing the front into the mount tab. Adjust rear bracket to line up with hole in fender. Remove seat and tighten the screws securing the bracket.
6. Reinstall seat, using the screw previously removed.



3501 Kennedy Rd, PO Box 5222, Janesville, WI 53547-5222
010403