

# INSTALLATION INSTRUCTIONS

## DRAG SPECIALTIES SEATS FOR 2000-UP SOFTAIL MODELS

**ATTENTION INSTALLER** (if other than owner): Please forward this instruction sheet to the purchaser of this product. These instructions contain valuable information necessary to the end user.

**INTRODUCTION:** These instructions describe the procedure for properly installing Drag Specialties seats onto Softail models.

Review these instructions carefully before beginning, as they contain important information. Please retain for future reference.

Particularly important information is distinguished in these instructions by the following notations:

**NOTE: A NOTE** provides key information to make procedures easier or clearer.

**CAUTION: A CAUTION** indicates special procedures that must be followed to avoid damage to the motorcycle and/or accessories.

**WARNING: A WARNING** indicates special procedures that must be followed to avoid injury to a motorcycle operator or person inspecting or repairing the motorcycle.



### ABOUT THE SOLAR REFLECTIVE TECHNOLOGY

Solar reflective leather keeps the seating area cool even in direct sunlight. The process has been shown to reduce surface temperatures by as much as 25°F.

**NOTE:** The Solar Reflective Technology is only available on select models. See catalog for specific applications.

**CAUTION:** The use of leather conditioners or chemicals will void warranty.

**Cleanup:** Warm water, mild soap and a soft cloth should be used for cleanup.

**NOTE: ON SKINNY TIRE MODELS, EXCEPT FLS (SLIM) AND FXS BLACKLINE,** the bottom rear of the seat has four mounting holes for the rear bracket. **THE BRACKET IS INSTALLED IN THE TWO REAR HOLES AND CAN BE ADJUSTED OR RELOCATED FOR YOUR PARTICULAR APPLICATIONS.** The bracket must be mounted to the rear holes for the Heritage and Fat Boy applications.

**NOTE: ON FLS MODELS,** remove the plastic cap in the rear fender mount hole and save. Remove E-clip and nut from the current solo seat mount location and reinstall into the rear mount hole. Install plastic cap in forward mount location.

**NOTE: ON FXSB (BREAKOUT)** models, unscrew chrome button on rear fender. Use mounting screw and washer provided for installation.

### MOUNTING HARDWARE

\*490015A Bracket 1

\*424130 Screw 2

\*=Mounted on seat

### PROCEDURES:

1. Begin by placing the bike on the side stand.
2. Remove the stock seat from the bike.
3. The rear bracket comes installed on the seat.
4. Slip your new seat over the tab at the front of the frame near the gas tank and position it on the rear fender.
5. Center the rear of the seat in relation to the sissy bar and the fender.
6. With the seat centered, position the rear bracket to line up with the hole in the fender. Remove the seat and tighten the fasteners holding the bracket.
7. Slip the seat onto the front frame tab and attach the rear bracket to the fender, reusing the stock mounting screw. On FXSB, use mounting screw and washer provided.

Softail™ is a registered trademark of Harley-Davidson® Motor Company, Inc., Milwaukee, WI, U.S.A.

