

INSTALLATION INSTRUCTIONS

DRAG SPECIALTIES ONE-PIECE SEATS FOR ALL FXR MODELS

ATTENTION INSTALLER (if other than owner): Please forward this instruction sheet to the purchaser of this product. These instructions contain valuable information necessary to the end user.

INTRODUCTION: These instructions describe the procedure for properly installing Drag Specialties seats on all FXR models.

Review instructions carefully before beginning as they contain important information. Please retain for future reference.

Particularly important information is distinguished in these instructions by the following notations.

NOTE: A NOTE provides key information to make procedures easier or clearer.

CAUTION: A CAUTION indicates special procedures that must be followed to avoid damage to the motorcycle and/or accessories.

WARNING!: A WARNING indicates special procedures that must be followed to avoid injury to a motorcycle operator or person inspecting or repairing the motorcycle.

NOTE: Your new seat includes a rear mount bracket installed on the seat and a front tank mount bracket taped to the front of your new seat.

TOOLS REQUIRED:

- 1 - 1/2" combination wrench
- 1 - 7/16" combination wrench
- 1 - #3 Phillips screwdriver

SEAT REMOVAL, ONE-PIECE, TWO-PASSENGER SEAT

1. Begin by placing the motorcycle on the side stand.
2. Remove the stock seat from the bike. Save the rear Phillips-head screw and plastic washer. They will be reused. Proceed to step 4.

SEAT REMOVAL, FRONT AND REAR SOLO SEATS

1. Begin by placing the motorcycle on the side stand.
2. Remove the original two-piece seat and save the rear screw and washer. They will be reused. The hand strap and hardware will not be reused.
3. On the seat hinge, tap out the hinge pins and remove the upper half.

FRONT TANK MOUNT, ALL APPLICATIONS

4. The front seat mount that bolts to the rear of the gas tank is provided with all Drag Specialties FXR seats. If your bike currently has this mount installed, you will not need the one provided. To install the mount, remove the two bolts at rear of the gas tank. Install bracket and torque the bolts to factory specifications.



INSTALLING YOUR NEW PREDATOR SEAT

5. If your bike had a solo front that used the factory hinge assembly, you will need to install the front mount as described in Step 4.
6. Loosen the two 1/4" x 20" Phillips-head screws on the rear of your seat so that the rear bracket can be adjusted. Slip your new seat over the bracket at the rear of the gas tank and slide the seat all the way forward. Adjust rear bracket to align with the mount hole in the fender. Remove the seat and tighten rear mount screws. Reinstall seat using the screw and washer that was removed in step 2.

NOTE: Drag Specialties Seats are designed for use with Drag Specialties Sissy Bars.



3501 Kennedy Rd, PO Box 5222, Janesville, WI 53547-5222
010500