

# INSTALLATION INSTRUCTIONS

## DRAG SPECIALTIES SEATS FOR VICTORY KINGPIN, VEGAS, HIGHBALL AND VEGAS 8-BALL MODELS

**ATTENTION INSTALLER** (if other than owner): Please forward this instruction sheet to the purchaser of this product. These instructions contain valuable information necessary to the end user.

**INTRODUCTION:** These instructions describe the procedure for properly installing Drag Specialties seats on select Victory models. Review these instructions carefully before beginning, as they contain important information. Please retain for future reference.

Particularly important information is distinguished in these instructions by the following notations:

**NOTE: A NOTE** provides key information to make procedures easier or clearer.

**CAUTION: A CAUTION** indicates special procedures that must be followed to avoid damage to the motorcycle and/or accessories.

**WARNING!: A WARNING** indicates special procedures that must be followed to avoid injury to a motorcycle operator or person inspecting or repairing the motorcycle.

### SOLAR REFLECTIVE TECHNOLOGY:

Solar Reflective Leather keeps the seating area cool even in direct sunlight. The process has been shown to reduce surface temperatures by as much as 25°F.

**NOTE:** The Solar Reflective Technology is only available on select models. See catalog for specific applications.

**CAUTION:** The use of leather conditioners or chemicals will void the warranty. Cleanup: Warm water, mild soap and soft cloth should be used for cleanup.

### TOOLS REQUIRED:

6mm Allen wrench, 6mm socket, ratchet wrench and extension  
5mm Allen wrench  
Torque wrench


1. Begin by placing the bike on a side stand.

**WARNING!:** Make sure the motorcycle is secure and will not fall while on the side stand.

2. Remove the two side covers.

**CAUTION: USE EXTREME CARE NOT TO CONTACT THE POSITIVE BATTERY TERMINAL WHILE REMOVING AND INSTALLING THE SEAT AND OLD BRACKET SCREW.**

3. Remove the two seat screws (6mm Allen) one on each side and save, they will be reused.



### SEAT REMOVAL

4. If your model has a solo seat only, remove the seat at this time. Proceed to **"INSTALLING YOUR NEW SEAT."** If your model has a two-piece seat (driver and passenger) proceed to **STEP 5.**



5. Using the 6mm Allen

wrench, remove the left and right frame rail covers.

6. Remove the four passenger seat screws and remove the seat. Screws will not be reused.

### INSTALLING YOUR NEW SEAT

**NOTE:** If your model had a solo seat only and you are installing a full-length seat, remove the left and right frame rail covers at this time. **(SEE STEP 5.)**

7. **SOLO SEAT INSTALLATION:** Locate the front tongue and the two side brackets on the bottom of your new seat. Install the seat by raising the rear slightly while engaging the front tongue into the seat bracket at the rear of the fuel tank while aligning the side mounts along the frame. Proceed to **STEP 9.**

8. **FULL-LENGTH SEAT INSTALLATION:** Locate the front tongue and the two side brackets on the bottom of your new seat. Install the seat by raising the rear slightly while engaging the front tongue into the small bracket at the rear of the fuel tank while aligning the front and rear side mounts along the frame. Start all screws. Two screws are included for mounting the rear bracket.

**NOTE:** Review the seat nose to fit the tank. The side and rear brackets can be adjusted on the seat to the rear to ensure a snug fit.

9. Torque all screws to 18 ft.-lb.

10. Reinstall frame rail covers and torque to 18 ft.-lb.

11. Replace side covers.

**WARNING!:** Periodically check and re-torque all fasteners.



3501 Kennedy Rd, PO Box 5222, Janesville, WI 53547-5222  
010916