

# INSTALLATION INSTRUCTIONS

## DRAG SPECIALTIES SEATS FOR CUSTOM STRETCH TANKS

**ATTENTION INSTALLER** (if other than owner): Please forward this Instruction Sheet to the purchaser of this product. These instructions contain valuable information necessary to the end user.

**INTRODUCTION:** These instructions describe the procedure for properly installing Drag Specialties Seats for custom stretch tanks. Review these instructions carefully before beginning, as they contain important information. Please retain for future reference.

Particularly important information is distinguished in these instructions by the following notations:

**NOTE:** A **NOTE** provides key information to make procedures easier or clearer.

**CAUTION:** A **CAUTION** indicates special procedures that must be followed to avoid damage to the motorcycle and/or accessories.

**WARNING!:** A **WARNING!:** indicates special procedures that must be followed to avoid injury to a motorcycle operator or person inspecting or repairing the motorcycle.

### ABOUT THE SOLAR REFLECTIVE TECHNOLOGY:

Solar Reflective Technology keeps the seating area cool even in direct sunlight. The process has been shown to reduce surface temperatures by as much as 25° F.

**NOTE:** The Solar Reflective Technology is only available on select models. See catalog for specific applications.

**CAUTION:** The use of leather conditioner or chemicals will void the warranty. Warm water, mild soap and a soft cloth should be used for cleanup.

### INSTALLATION

**NOTE:** The step washer in the rear mount will be required on all applications with a weld-in fender nut. If your application uses a clip nut, remove the step washer from the rear bracket.

1. On your new seat, loosen the two screws securing the rear bracket so the bracket will move with some resistance.
2. Install the seat securing the front into the tab on the rear of the fuel tank. Bump the seat forward, closing the gap between the seat and the fuel tank.
3. Adjust the rear bracket to line up with the hole in the fender. Remove the seat, tighten the rear bracket and reinstall the seat.

