

INSTALLATION INSTRUCTIONS

DRAG SPECIALTIES LICENSE PLATE FRAME W/ DUAL FUNCTION LED P/N 2040-0045

ATTENTION INSTALLER (if other than owner): Please forward this Instruction Sheet to the purchaser of this product. These instructions contain valuable information necessary to the end user.

INTRODUCTION: These instructions describe the procedure for properly installing this license plate frame on any motorcycle. Review instructions carefully before beginning, as they contain important information. Please retain for future reference.

Particularly important information is distinguished in these instructions by the following notations.

NOTE: A **NOTE** provides key information to make procedures easier or clearer.

CAUTION: A **CAUTION** indicates special procedures that must be followed to avoid damage to the motorcycle and/or accessories.

WARNING! A **WARNING** indicates special procedures that must be followed to avoid injury to a motorcycle operator or person inspecting or repairing the motorcycle.



PROCEDURE:

1. Disconnect the battery at the negative terminal.
2. Remove seat.
3. Remove the taillight lens.
4. Install License Plate Frame with Dual Function LED lights on the license plate, making sure the wires are routed in the recessed channel on the back side of the frame.

NOTE: When installing the four studs included, make sure you use a thread locking adhesive on the studs where they screw into the Chrome frame. Tighten snugly with a 3/32" hex key.

5. Unplug the taillight lead from the receptacle in the taillight housing. Find the following three wires going to the taillight housing: blue, red with yellow tracer, and black. These wires all go to the taillight bulb.
6. Connect the wires from the license plate frame to the taillight wiring as follows:

| Taillight | to | License Plate Frame |
|-------------------------------|----|---------------------|
| Black, ground | to | Green, ground |
| Blue, taillight | to | Yellow, taillight |
| Red with yellow tracer, brake | to | Blue, brake |

NOTE: Make all wire connections in a professional manner. We recommend that you solder all connections and cover them with heat shrink tubing.

7. Install the taillight lens and check the wire routing to make sure that all wires are routed away from any moving components.
8. Reconnect the battery and check operation of the taillight and license plate frame light. Make sure that they both correspond to the input given to the motorcycle.

WARNING! Before operating motorcycle, be sure all hardware is tight.

