

P/N 0365-0079-80

NO MAR TIRECHANGERS

PAGE 01/02

V. 1840

January 1, 2007

MATERIAL SAFETY DATA SHEET

SECTION I-NAME

Product name as shown on label: Tire Slick Tire Mounting Lubricant
Manufactures Name: Tire Slick, Inc.
Address: 4811 East Fork Ln.
Monroe, NC 28110
Emergency Phone: 704-291-7171
Contact Person: Mike Blessing

SECTION II-INGREDIENTS

This product contains no hazardous components as defined by the Occupational Safety and Health Administration Regular. (29CFR Section 1910.1200)

SECTION III PHYSICAL DATA

Boiling Point: 212 F 100 C	Specific Gravity: (20-15) 1
Vapor Pressure: @ 68°F 20°C 0mmHG	Percent Solid by Weight: <5
Percent Volatile By Volume (%): <95	Evaporation Rate (20-15) 1
0mm Hg _ psi	Density: 1.0030@25C
Vapor Density (Air=1) NA	
Solubility in Water: Yes	
*PH: 10.-11.5	
Odor: None	
Appearance:	
Blue Viscous Liquid, no odor	SSE Viscosity: 960
*PH will drop as product cures.	

SECTION IV-HAZARDS

Hazardous material description; proper shipping, hazard class, Hazard ID NONE
NO (49CFR172.101)

Additional Hazards Classes: NONE

SECTION V-FIRST AID

Effects of overexposure:	None Known
Conditions to avoid:	None Known
EXPOSURE	
FIRST AID	PREVENTION

Inhalation

Skin

Eye

Ingestion

Flush with clean water, if irritation persists see doctor

SAFETY GOGGLES

See Doctor

SECTION VI-FIRE FIGHTING

Flash Point: Method used:

Non-combustible

 F C

Flammable limit:

 LEL OEL

Extinguishing media: N/A

Unusual fire & explosion hazards: N/A

SECTION VII-HANDLING & STORAGE

Steps to be taken when spilled:

Waste disposal method: Floors will be slippery, use care to avoid falling

Dispose of according to local regulations. Environmental friendly; Flush and rinse with water

Storage: No special requirements, avoid freezing as container may split

Precautions to be taken in handling & storage: None