

PORTER MFG. & SUPPLY CORP. -- GASGACINCH GASKET SEALER -- 8040-01-125-4673

===== Product Identification =====

Product ID:GASGACINCH GASKET SEALER

MSDS Date:10/02/1989

FSC:8040

NIIN:01-125-4673

Kit Part:Y

MSDS Number: BMQMX

=== Responsible Party ===

Company Name:PORTER MFG. & SUPPLY CORP.

Address:2215 NO CHICO AVENUE

City:SOUTH EL MONTE

State:CA

ZIP:91733

Country:US

Info Phone Num:213-283-4968 /818-448-3243

Emergency Phone Num:800-424-9300 (CHEMTREC)

Preparer's Name:LYNN D. GRANT

CAGE:PORTE

=== Contractor Identification ===

Company Name:PORTER MFG. & SUPPLY CORP

Address:2215 NO CHICO AVENUE

Box:City:SOUTH EL MONTE

State:CA

ZIP:91733

Phone:213-283-4968 /818-448-3243

CAGE:PORTE

===== Composition/Information on Ingredients =====

Ingred Name:TOLUENE (SARA III)

CAS:108-88-3

RTECS #:XS5250000

Fraction by Wt: 45-55%

Other REC Limits:NONE SPECIFIED

OSHA PEL:200 PPM/150 STEL

ACGIH TLV:50 PPM; 9293

EPA Rpt Qty:1000 LBS

DOT Rpt Qty:1000 LBS

Ingred Name:PETROLEUM NAPHTHA (SOLVENT IS A COMPLEX MIXTURE OF
PREDOMINATELY C6 TO C9 HYDROCARBONS. THE EXACT COMPOSITION WILL
VARY)

CAS:8030-30-6

RTECS #:DE3030000

Fraction by Wt: 22-27%

Other REC Limits:*VENT AS GUIDELINE)

ACGIH TLV:400PPM (RUBBER SOL-*

DS 173402

===== Hazards Identification =====

Routes of Entry: Inhalation:YES Skin:YES Ingestion:YES
Health Hazards Acute and Chronic:ACUTE TOXICITY: OVEREXPOSURE CAN LEAD TO CENTRAL NERVOUS SYSTEM DEPRESSION (HEADACHE, DIZZINESS, NAUSEA & UNCONSCIOUSNESS). EYE: SHORT TERM LIQUID OR VAPOR CONTACT MAY RESULT IN SLIGHT IRRITATION. PRO LONG/REPEAT MAY BE MORE IRRITATING. SKIN: PROLONG/REPEAT CONTACT CAN CAUSE DEFATTING & DRYING WHICH MAY RESULT IN *
Effects of Overexposure:*SKIN IRRIT & DERMATITIS. INHALE: HIGH CONC & PROLONGED EXPOSURE TO LOWER CONC MAY BE SLIGHTLY IRRITATING TO MUCOUS MEMBRANES. INGEST: LIQUID INGESTION MAY RESULT IN VOMITING-ASPIRATION OF LIQUID INTO THE LUNGS. THIS MUST BE AVOIDED AS LIQUID CONTACT W/LUNGS CAN RESULTING CHEMICAL PNEUMONITIS/EDEMA/HEMORRHAGE.

===== First Aid Measures =====

First Aid:EYE: FLUSH W/WATER FOR 15 MIN. GET MED AID. SKIN: FLUSH W/WATER FOLLOWED BY WASHING W/SOAP & WATER. REMOVE CONTAM CLOTHES & LAUNDER BEFORE REUSE. FOR PERSISTANT IRRIT GET MED AID. INHALE: REMOVE TO FRESH AIR & PROVIDE OXYGEN IF BREATHING IS DIFFICULT. GIVE CPR IF NOT BREATHING. GET MED AID. INGEST: DO NOT INDUCE VOMITING. IF SPONTANEOUS VOMITING OCCURS KEEP HEAD BELOW HIPS. GET MEDICAL AID.

===== Fire Fighting Measures =====

Flash Point Method:TCC
Flash Point:20.0F,-6.7C
Lower Limits:1
Upper Limits:8
Extinguishing Media:REGULAR FOAM, CO2 AND DRY CHEMICAL
Fire Fighting Procedures:USE SPECIAL SELF-CONTAINED BREATHING APPARATUS.
Unusual Fire/Explosion Hazard:ELIMINATE ALL IGNITION SOURCES, VAPORS ARE HEAVIER THAN AIR AND MAY TRAVEL ALONG THE GROUND OR MAY BE MOVED BY VENTILATION.

===== Accidental Release Measures =====

Spill Release Procedures:ELIMINATE ALL SOURCES OF IGNITION. DIKE AREA TO PREVENT RUN-OFF. PUMP LIQUID INTO METAL CONTAINER. COVER ANY REMAINING MATERIAL WITH SAND, DIRT, CLAY OR VERMICULITE AND PUT INTO METAL CONTAINER.

===== Handling and Storage =====

Handling and Storage Precautions:STORE AT ROOM TEMPERATURES BETWEEN 40F AND 100F. KEEP CONTAINER TIGHTLY CLOSED WHEN NOT IN USE. STORE UPRIGHT. KEEP FROM HEAT AND ALL IGNITION SOURCES.
Other Precautions:AVOID BREATHING OF VAPORS, EYE AND SKIN CONTACT.

===== Exposure Controls/Personal Protection =====

Respiratory Protection:USE APPROVED RESPIRATOR OR GAS MASK.
Ventilation:SUFFICIENT TO KEEP TLV BELOW 100 PPM.
Protective Gloves:SOLVENT RESISTANT TYPE
Eye Protection:USE SPLASH GOGGLES
Other Protective Equipment:WEAR CLOTHING AS REQUIRED TO MINIMIZE CONTACT.
Work Hygienic Practices:ALWAYS WASH THOROUGHLY WITH SOAP AND WATER AFTER EXPOSURE TO THE SKIN.
Supplemental Safety and Health

===== Physical/Chemical Properties =====

Boiling Pt:B.P. Text:206F,97C
Vapor Pres:17 @ 60F
Vapor Density:> AIR
Spec Gravity:0.88
Evaporation Rate & Reference:2.1 (BU AC=1)
Solubility in Water:NEGLIGIBLE
Appearance and Odor:NEUTRAL OR AMBER COLOR LIQUID, STRONG SOLVENT ODOR
Percent Volatiles by Volume:79.6

===== Stability and Reactivity Data =====

Stability Indicator/Materials to Avoid:YES
STRONG ACIDS, OXIDIZERS AND ALKALIES.
Stability Condition to Avoid:EXCESS HEAT, SPARKS, OPEN FLAME OR ANY SOURCES OF IGNITION.
Hazardous Decomposition Products:BURNING MAY PRODUCE CO2, CO AND VARIOUS HYDROCARBONS.

===== Disposal Considerations =====

Waste Disposal Methods:DISPOSE OF IN ACCORDANCE TO ALL FEDERAL, STATE & LOCAL REGULATIONS.

Disclaimer (provided with this information by the compiling agencies):
This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.