MOTOREX*
Oil of Switzerland
Reviewed on 12/16/2022

Printing date 02/24/2023

1 Identification

- · Product identifier
- · Trade name: CROSS POWER 2T
- · Application of the substance / the mixture

Only for proper handling.

Engine oil

- · Details of the supplier of the safety data sheet
- · Manufacturer/Supplier:

MOTOREX AG

Bern-Zürich-Strasse 31, Postfach

CH-4901 Langenthal

Tel. +41 (0)62 919 75 75

www.motorex.com

- · Information department: msds@motorex.com
- Emergency telephone number:

USA + Kanada: 1 800 424 9300 (Chemtrec Chemical Manufacturers Association, Arlington, VA 22209)

2 Hazard(s) identification

· Classification of the substance or mixture

Sensitization - Skin 1 H317 May cause an allergic skin reaction.

- · Label elements
- · GHS label elements

The product is classified and labeled according to the Globally Harmonized System (GHS).

· Hazard pictograms



GHS07

- · Signal word Warning
- · Hazard-determining components of labeling:

Benzenesulfonic acid, methyl-, mono-C20-24-branched alkyl derivs., calcium salts

· Hazard statements

H317 May cause an allergic skin reaction.

· Precautionary statements

P261 Avoid breathing dust/fume/gas/mist/vapors/spray

P272 Contaminated work clothing must not be allowed out of the workplace.

P280 Wear protective gloves.

P302+P352 If on skin: Wash with plenty of water.

P333+P313 If skin irritation or rash occurs: Get medical advice/attention.

P321 Specific treatment (see on this label).
P363 Wash contaminated clothing before reuse.

P501 Dispose of contents/container in accordance with local/regional/national/international

regulations.

- · Classification system:
- · NFPA ratings (scale 0 4)



Health = 0 Fire = 1 Reactivity = 0

(Contd. on page 2)

MOTOREX*
Oil of Switzerland

(Contd. of page 1)

Printing date 02/24/2023

Reviewed on 12/16/2022

Trade name: CROSS POWER 2T

· HMIS-ratings (scale 0 - 4)

HEALTH 0
FIRE 1
REACTIVITY 0

Health = 0 Fire = 1 Reactivity = 0

- · Other hazards
- · Results of PBT and vPvB assessment
- · **PBT:** Not applicable. · **vPvB:** Not applicable.

3 Composition/information on ingredients

- · Chemical characterization: Mixtures
- · **Description:** Mixture of the substances listed below with nonhazardous additions.

· Dangerous componer	nts:	
CAS: 1000172-11-1 Pentadecane, 7-methylene mixed with 1-tetradecene, dimers EC number: 700-184-9 and trimers, hydrogenated		10-25%
	Aspiration Hazard 1, H304	
EC number: 926-141-6	Hydrocarbons, C11-C14, n-alkanes, isoalkanes, cycloalkanes, <2% aromatics	10-25%
	Aspiration Hazard 1, H304; Flammable Liquids 4, H227	
CAS: 722503-68-6 EC number: 682-816-2	Benzenesulfonic acid, methyl-, mono-C20-24-branched alkyl derivs., calcium salts Sensitization - Skin 1, H317	≥0.25-<1%

4 First-aid measures

- · Description of first aid measures
- · After inhalation:

Supply fresh air and to be sure call for a doctor.

In case of unconsciousness place patient stably in side position for transportation.

· After skin contact:

Remove residues with soap and water.

Remove contaminated clothing immediately.

Immediately wash with water and soap and rinse thoroughly.

· After eye contact:

Rinse opened eye for several minutes under running water.

Consult a physician if irritation develops.

After swallowing:

Do not induce vomitting. Do not take in resorption stimulating agents.

Consult a physician who will decide on need and method of emptying the stomach.

- · Most important symptoms and effects, both acute and delayed
- No further relevant information available.
- · Indication of any immediate medical attention and special treatment needed

No further relevant information available.

5 Fire-fighting measures

- · Extinguishing media
- · Suitable extinguishing agents: Use fire fighting measures that suit the environment.
- Special hazards arising from the substance or mixture

In case of fire carbon, sulphur and nitrogen oxides can be formed.

(Contd. on page 3)

Printing date 02/24/2023

Reviewed on 12/16/2022

Trade name: CROSS POWER 2T

(Contd. of page 2)

- Advice for firefighters
- · Protective equipment: No special measures required.

6 Accidental release measures

- · Personal precautions, protective equipment and emergency procedures Not required.
- · Environmental precautions: Do not allow to enter sewers/ surface or ground water.
- · Methods and material for containment and cleaning up:

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).

Dispose contaminated material as waste according to item 13.

Ensure adequate ventilation.

Protective Action Criteria for Chemicals

PAC-1:			
1330-20-7		130 ppm	
100-41-4	ethylbenzene	33 ppm	
· PAC-2:	· PAC-2:		
1330-20-7		920* ppm	
100-41-4	ethylbenzene	1100* ppm	
· PAC-3:			
1330-20-7		2500* ppm	
100-41-4	ethylbenzene	1800* ppm	

Reference to other sections

No dangerous substances are released.

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

7 Handling and storage

· Precautions for safe handling

Vapours of this product are heavier than air and will collect in low areas such as pits, storage tanks, and other confined areas.

Ensure good ventilation/exhaustion at the workplace.

Prevent formation of aerosols.

- · Information about protection against explosions and fires: No special measures required.
- · Conditions for safe storage, including any incompatibilities
- Storage:
- · Requirements to be met by storerooms and receptacles: No special requirements.
- Information about storage in one common storage facility: Not required.
- · Further information about storage conditions:

The recommended storage temperature is (deg.C): ≤50°C

Store containers closed and protect against rain, dust, heat and other atmospheric influences.

Store in cool, dry well ventilated area away from sources of ignition and heat.

- Storage class: 10
- · Specific end use(s) No further relevant information available.

8 Exposure controls/personal protection

- · Control parameters
- · Components with limit values that require monitoring at the workplace:

The product does not contain any relevant quantities of materials with critical values that have to be monitored at the workplace.

(Contd. on page 4)

MOTOREX*
Oil of Switzerland
Reviewed on 12/16/2022

Printing date 02/24/2023

Trade name: CROSS POWER 2T

(Contd. of page 3)

- · Additional information: The lists that were valid during the creation were used as basis.
- · Exposure controls
- · Additional information about design of technical systems: No further data; see section 7.
- Personal protective equipment:
- General protective and hygienic measures:

Keep away from foodstuffs, beverages and feed.

Immediately remove all soiled and contaminated clothing.

Wash hands before breaks and at the end of work.

Do not inhale gases / fumes / aerosols.

Breathing equipment:

In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use respiratory protective device that is independent of circulating air.

Not necessary if room is well-ventilated.

Respiratory protection if formation of aerosol or mist: use mask with filter type A2, A2/P2 or ABEK.

Protection of hands:



Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

· Material of gloves

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

· Penetration time of glove material

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

- · Eve protection: Goggles recommended during refilling.
- · Body protection: Protective work clothing

9 Physical and chemical properties

Information on basic physical and chemical properties

· General Information

· Color: Red

Odor:
 Odor threshold:
 Melting point/Melting range:
 Boiling point/Boiling range:
 Flammability (solid, gaseous):

Characteristic

 Not determined.
 Undetermined.
 Not applicable.

· Explosion limits:

Lower: 0.6 Vol.%
Upper: 6.5 Vol.%
Flash point: 110 °C (230 °F)
Ignition temperature: >200 °C (DIN 51794)
Decomposition temperature: Not determined.
pH-value: Not determined.

· Viscosity:

• Kinematic: 56 mm²/s @ 40 °C (132.8 mm²/s @ 104 °F)

· Consistency

· **Dynamic:** Not determined.

(Contd. on page 5)

Printing date 02/24/2023

Reviewed on 12/16/2022

Trade name: CROSS POWER 2T

(Contd. of page 4)

· Solubility in / Miscibility with

Water: Not miscible or difficult to mix.

· Partition coefficient (n-octanol/water): Not determined. · Vapor pressure: Not determined.

0.874 g/cm³ (7.294 lbs/gal) (ASTM D 4052) · Density at 20 °C (68 °F):

Not determined. · Relative density · Vapor density Not determined.

· Other information

· Appearance:

· Form: Fluid

· Important information on protection of health

and environment, and on safety.

· Danger of explosion: Product does not present an explosion hazard.

Solvent separation test

· VOC content: 15.00 %

· Change in condition

-33 °C (-27.4 °F) Solidification point: Not determined. Evaporation rate

10 Stability and reactivity

- · Reactivity No further relevant information available.
- · Chemical stability
- Thermal decomposition / conditions to be avoided:

No decomposition if used according to specifications.

- · Possibility of hazardous reactions No dangerous reactions known.
- · Conditions to avoid No further relevant information available.
- · Incompatible materials: No further relevant information available.
- · Hazardous decomposition products: No dangerous decomposition products known.

11 Toxicological information

- · Information on toxicological effects
- · Acute toxicity: Based on available data, the classification criteria are not met.

· LD/LC50 values that are relevant for classification:			
Hydrocar	Hydrocarbons, C11-C14, n-alkanes, isoalkanes, cycloalkanes, <2% aromatics		
Oral	LD50	5,000 mg/kg (rat)	
	NOAEL	1,000-5,000 mg/kg/24h (rat)	
Dermal	LD50	2,000 mg/kg (rabbit)	
Inhalative	LC50 / 4h	5.28 mg/l (rat)	
	NOAEL	200 ppm (rat)	
	NOAEC	275-10,400 mg/m3 (rat)	

- · Sensitization: May cause an allergic skin reaction.
- Additional toxicological information:
- Carcinogenic categories

· IARC (Inte	rnational Agency for Research on Cancer)	
1330-20-7	xylene	3
100-41-4	ethylbenzene	2B
· NTP (Natio	onal Toxicology Program)	
None of the	e ingredients is listed.	

(Contd. on page 6)

MOTOREX*
Oil of Switzerland
Reviewed on 12/16/2022

Printing date 02/24/2023

Trade name: CROSS POWER 2T

(Contd. of page 5)

· OSHA-Ca (Occupational Safety & Health Administration)

None of the ingredients is listed.

12 Ecological information

· Toxicity

	· Aquatic	ntic toxicity: ocarbons, C11-C14, n-alkanes, isoalkanes, cycloalkanes, <2% aromatics	
İ	Hydroca		
İ	LL50	2-5 mg/l/96h (fish)	
	LL50	2-5 mg/l/48h (fish)	
	LL50	5-17 mg/l/24h (fish)	
	EL50	1.4 mg/l/48h (aquatic invertebrates)	
	EL50	4.6 mg/l/24h (aquatic invertebrates)	
		1-3 mg/l/24h (algae / cyanobacteria)	
	EL50	1-3 mg/l/72h (algae / cyanobacteria)	
	EL50	0.81-0.89 mg/l/21d (aquatic invertebrates)	
	NOELR	1.22 mg/l/21d (aquatic invertebrates)	
	NOELR	1,000 mg/l/72h (algae / cyanobacteria)	

- Persistence and degradability No further relevant information available.
- · Bioaccumulative potential No further relevant information available.
- · Mobility in soil No further relevant information available.
- Results of PBT and vPvB assessment
- · PBT: Not applicable.
- · vPvB: Not applicable.
- Other adverse effects
- · Additional ecological information:
- · General notes:

Water hazard class 1 (according to Appendix 1 AwSV): slightly hazardous for water Do not allow undiluted product or large quantities of it to reach ground water, water course or sewage system.

13 Disposal considerations

- · Waste treatment methods
- · Recommendation:

Must not be disposed of together with household garbage. Do not allow product to reach sewage system.

Contact waste processors for recycling information.

Return product and/or partially emptied container in original packaging to the point of sale or hand it over to a collection point for special waste.

- Uncleaned packagings:
- Recommendation: Disposal must be made according to official regulations.

14 Transport information

- · UN-Number
- · DOT, ADR/RID/ADN, ADN, IMDG, IATA Void
- · UN proper shipping name
- · DOT, ADR/RID/ADN, ADN, IMDG, IATA Void

(Contd. on page 7)

MOTOREX*
Oil of Switzerland
Reviewed on 12/16/2022

Printing date 02/24/2023

Trade name: CROSS POWER 2T

		(Contd. of page 6
· Transport hazard class(es)		
· DOT, ADR/RID/ADN, ADN, IMDG, IATA · Class	1 Void	
· Packing group · DOT, ADR/RID/ADN, IMDG, IATA	Void	
· Environmental hazards: · Marine pollutant:	No	
· Special precautions for user	Not applicable.	
· Transport in bulk according to Annex MARPOL73/78 and the IBC Code	(II of Not applicable.	
UN "Model Regulation":	Void	

15 Regulatory information

· Safety, health and environmental regulations/legislation specific for the substance or mixture

· Sara · Section 355 (extremely hazardous substances):	
None of the in	gredients is listed.	
· Section 313 (Specific toxic chemical listings):	
1330-20-7 xylene		
100-41-4 ethylbenzene		
TSCA (Toxic	Substances Control Act):	
68334-05-4	Fatty acids, C18-unsatd., dimers, 2-ethylhexyl esters	ACTIVE
9003-29-6	Polybuten (Isobutylen-/Buten-Copolymer)	ACTIVE
1000172-11-1	Pentadecane, 7-methylene mixed with 1-tetradecene, dimers and trimers, hydrogenated	ACTIVE
722503-68-6	Benzenesulfonic acid, methyl-, mono-C20-24-branched alkyl derivs., calcium salts	ACTIVE
68855-45-8	Phenol, dodecyl-, sulfurized, calcium salts	ACTIVE
92257-31-3	2-Naphthalenol, 1-((4-(phenylazo)phenyl)azo)-,ar- heptylar,ar,Methylderivate	ACTIVE
1330-20-7	xylene	ACTIVE
100-41-4	ethylbenzene	ACTIVE
· Hazardous A	ir Pollutants	
1330-20-7 xy	lene	
100-41-4 eth	nylbenzene	
Proposition 6	55	

	· Cnemicals known to cause cancer:
	100-41-4 ethylbenzene
i	Chamicala Impum to acuse venue ductive to visitu for famelae.

None of the ingredients is listed.

· Chemicals known to cause reproductive toxicity for males:

None of the ingredients is listed.

(Contd. on page 8)

MOTOREX*
Oil of Switzerland

Printing date 02/24/2023

Reviewed on 12/16/2022

Trade name: CROSS POWER 2T

		(Contd. of page
· Chemical	s known to cause developmental toxicity:	
None of th	ne ingredients is listed.	
· Carcinog	enic categories	
· EPA (Env	ironmental Protection Agency)	
1330-20-7	' xylene	1
100-41-4	ethylbenzene	L
· TLV (Thre	eshold Limit Value)	
1330-20-7	' xylene	A
100-41-4	ethylbenzene	A
· NIOSH-Ca	a (National Institute for Occupational Safety and Health)	<u>.</u>
None of th	e ingredients is listed.	

· Chemical safety assessment: A Chemical Safety Assessment has been carried out.

16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship. The classification of the mixture was carried out by calculation in accordance with the rules laid down in Annex I of Regulation (EC) No 1272/2008.

No special training instructions to ensure protection of human health and environment are required.

- · Department issuing SDS: Abteilung Produktsicherheit
- · Date of preparation / last revision 02/24/2023
- Abbreviations and acronyms:

ADR: Accord relatif au transport international des marchandises dangereuses par route (European Agreement Concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

DOT: US Department of Transportation

IATA: International Air Transport Association

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

NFPA: National Fire Protection Association (USA)

HMIS: Hazardous Materials Identification System (USA)

VOC: Volatile Organic Compounds (USA, EU)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

PBT: Persistent, Bioaccumulative and Toxic

vPvB: very Persistent and very Bioaccumulative

NIOSH: National Institute for Occupational Safety

OSHA: Occupational Safety & Health

TLV: Threshold Limit Value

PEL: Permissible Exposure Limit

REL: Recommended Exposure Limit

Flammable Liquids 4: Flammable liquids – Category 4 Sensitization - Skin 1: Skin sensitisation – Category 1

Aspiration Hazard 1: Aspiration hazard – Category 1

* Data compared to the previous version altered.

US