

Released: 2016-05-03

Version: 1.1 Revision Date: 2016-05-03

### 1. IDENTIFICATION OF THE SUBSTANCE / APPLICATION AND THE COMPANY

Supplier:	Product Name: Bike Chain Wax
Maxima Racing Oils	Article Number: 95-02904
9266 Abraham Way	
Santee, CA 92071	Applications: Lubricant/Protectant
USA	
+1 619 449 5000	Emergency Telephone: CHEMTREC +1 703 527 3887 (24 hours)

### 2. HAZARDS IDENTIFICATION

#### **GHS Classification**

Flammable Liquid	Category 2
Aspiration Hazard	Category 1
Skin Irritant	Category 2
Skin Sensitizer	Category 1A
Specific Target Organ Toxicity – Single	Category 3
Exposure	σ,
Toxic to Reproduction	Category 2

**GHS** Pictogram

Signal Word Hazard Statements



	Danger!
	H225 Highly flammable liquid and vapor.
	H304 May be fatal if swallowed and enters airways.
	H315 Causes skin irritation.
	H317 May cause an allergic skin reaction.
	H336 May cause drowsiness or dizziness.
	H361 Suspected of damaging fertility or the unborn
	child.
•	

#### **Precautionary Statements**

**Prevention** P201 Obtain special instructions before use.

P202 Do not handle until all safety precautions have been read and understood. P210 Keep away from heat, sparks, open flames, and hot surfaces. No smoking. P233 Keep container tightly closed.

- P240 Ground and bond container and receiving equipment
- P241 Use explosion-proof electrical, ventilating and lighting equipment.



Released: 2016-05-03

Version: 1.1 Revision Date: 2016-05-03

Response	<ul> <li>P242 Use only non-sparking tools.</li> <li>P243 Take precautionary measures against static discharge.</li> <li>P261 Avoid breathing dust, fume, gas, mist, vapors or spray.</li> <li>P264 Wash thoroughly after handling</li> <li>P271 Use only outdoors or in a well-ventilated area.</li> <li>P272 Contaminated work clothing should not be allowed out of the workplace.</li> <li>P280 Wear protective gloves.</li> <li>P301 + P310 IF SWALLOWED: Immediately call a POISON CENTER or doctor.</li> <li>P331 Do NOT induce vomiting.</li> <li>P303 + P361 + P353 IF ON SKIN (or hair): Take off immediately all contaminated</li> </ul>
	clothing. Rinse skin with water. P333 + P313 If skin irritation or rash occurs: Get medical attention. P362 + P364 Take off contaminated clothing and wash it before reuse.
	<ul> <li>P304 + P340 IF INHALED: Remove person to fresh air and keep comfortable for breathing.</li> <li>P308 + P313 IF exposed or concerned: Get medical attention.</li> <li>P370 + P378 In case of fire: Use carbon dioxide, foam or dry chemical to extinguish.</li> </ul>
Storage Disposal	P405 Store locked up. Dispose of contents and container in accordance with local, regional and national regulations.

## **Other Hazards**

None

## 3. COMPOSITION / INFORMATION ON INGREDIENTS

<b>Components</b> Petroleum Distillates	<b>Content %</b> 40-60	<b>CAS Number</b> 64742-89-8
Heptane	25-45	142-82-5
Cyclohexane	4-8	110-82-7
Hydrotreated light distillate (Petroleum)	1-5	64742-47-8
Stoddard Solvent	1-5	8052-41-3
Acetone	1-3	67-64-1
Hexane	0.1-<1	110-54-3
Cinnamal	<0.5	104-55-2



		Vers	ion: 1.1
Released: 2016-05-03		Revision Date: 201	6-05-03
Benzyl benzoate	<0.5	120-51-4	
Butanedioic acid ((4,5-dihydro-5-thioxo- 1,3,4-thiadiazol-2-yl) thio-bis (2 ethylhexyl) ester	<0.5	126104-53-8	

The specific identity and/or exact percentage has been withheld as a trade secret.

4. FIRST-AID MEASURES		
Inhalation	Immediately remove to fresh air. If breathing is difficult have qualified	
	personnel administer oxygen. If breathing has stopped, administer artificial	
	respiration. Get medical attention.	
Skin Contact	Remove contaminated clothing. Wash skin thoroughly with soap and water. If	
	irritation or rash develops, get medical attention. Launder clothing before re-	
	use.	
Eye Contact	Flush eyes with large quantities of water, holding the eyelids apart. Get	
•	medical attention if irritation develops or persists.	
Ingestion	Aspiration Hazard. Do not induce vomiting. If conscious, rinse mouth with	
C	water. Never give anything by mouth to an unconscious or convulsing person.	
	If vomiting occurs spontaneously, keep head below hips to prevent aspiration	
	into the lungs. Get immediate medical attention.	
Most Important	May cause eye irritation. Causes skin irritation. May cause an allergic skin	
Symptoms	reaction. Inhalation of vapors or mist may cause respiratory irritation and	
	central nervous system effects such as headache, dizziness, drowsiness,	
	nausea and unconsciousness. Aspiration hazard: Harmful or fatal if swallowed.	
	Suspected of causing reproductive or developmental effects based on animal	
	data.	
Indication of	Immediate medical attention is required for ingestion.	
Immediate Medical		
Attention Needed		
Notes to Physician	Treat appropriately.	
5. FIRE FIGHTING MEASU	5. FIRE FIGHTING MEASURES	
Suitable Extinguishing	Use carbon dioxide, alcohol foam or dry chemical. Water may be ineffective	

	0	
Media		but can be used to cool exposed containers and structures and disperse
		flammable vapors.
Specific Haza	ards	This product is highly flammable and forms explosive mixtures with air.
<b>Arising From</b>	n The	This product is highly flammable and forms explosive mixtures with air.
Chemical		Vapors are heavier than air and will travel along surfaces to remote ignition
		sources and flash back. Closed containers may explode if exposed to



Version: 1.1 Revision Date: 2016-05-03

Released: 2016-05-03	Revision Date: 2016-05-03	
Special Protective Equipment And Precautions For Fire- Fighters	extreme heat. Combustion may produce carbon oxides. Firefighters should wear full emergency equipment and an approved positive pressure self-contained breathing apparatus. Cool exposed intact containers with water.	
6. ACCIDENTAL RELEASE MEASURES		

Personal Precautions	Evacuate spill area and keep unprotected personnel away. Remove all sources of ignition. Ventilate area with explosion proof equipment. Wear
	appropriate protective ciotning. See also: Personal Protection Section 8.
Environmental Hazards	Avoid release into the environment. Report spill as required by local and
	federal regulations.
Methods/Materials for	Contain and collect using inert absorbent materials and place in
Cleaning up	appropriate containers for disposal. Use non-sparking tools and equipment.
	If spill has not ignited, use water spray to disperse the vapors and protect
	personnel attempting to stop leak. Ensure collected material is handled in
	accordance with section 13 "Disposal Considerations".

## 7. HANDLING AND STORAGE

Precautions for Safe Handling	Avoid contact with the eyes, skin and clothing. Do not breathe vapors or mists. Wear protective clothing and equipment. Use only with adequate ventilation. Wash thoroughly with soap and water after handling. Keep	
Conditions for Safe	all other sources of ignition. Do not permit smoking in use or storage areas. Store in a cool, dry, well-ventilated area away from heat, direct sunlight and	
Storage	all sources of ignition. Store in accordance with regulations for the storage of flammable liquids. Store away from oxidizers and other incompatible materials. Protect from physical damage.	

## 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Chemical Name	Exposure Limits
Datroloum Dictillator	5 mg/m3 TWA ACGIH TLV (inhalable) (as mineral oil)
Petroleum Distillates	5 mg/m3 TWA OSHA PEL (as oil mist, mineral)
Hentane	400 ppm TWA, 500 ppm STEL ACGIH TLV
rieptane	500 ppm TWA OSHA PEL



Released: 2016-05-03

Version: 1.1 Revision Date: 2016-05-03

	Cyclohexane		100 ppm TWA ACGIH TLV		
	Cyclotter		300 ppm TWA OSHA PEL		
	Hydrotreated light distillate		5 mg/m3 TWA ACGIH TLV (inhalable) (as mineral oil)		
	(Petroleu	um)	5 mg/m3 TWA OSHA PEL (as oil mist, mineral)		
	Stoddard Solvent		100 ppm TWA ACGIH TLV		
			500 ppm TWA OSHA PEL		
	Acetone Hexane Cinnamal Benzyl benzoate		250 ppm TWA, 500 ppm STEL ACGIH TLV		
			1000 ppm TWA OSHA PEL		
			50 ppm TWA skin ACGIH TLV		
			500 ppm TWA OSHA PEL		
			None Established		
			None Established		
	Butanedioic acid ((4	4,5-dihydro-5-			
	thioxo-1.3.4-thiadia	azol-2-vl) thio-			
	bis (2-ethylhexyl) ester		None Established		
Ар	propriate	Use with adequ	ate local exhaust ventilation to maintain exposures below		
Engineering Controls the occupat required.		the occupation required.	al exposure limits. Use explosion proof equipment where		
Personal Protection					
Respiratory Protection		If the exposure limits are exceeded, an approved organic vapor respirator			
appropriate for used. Selection with local regu <b>Eye Protection</b> Wear chemical <b>Skin/Body Protection</b> Wear protectiv of personal clo Contaminated <b>Hand Protection</b> Wear impervio		appropriate for the form and concentration of the contaminants should be used. Selection and use of respiratory equipment must be in accordance			
					with local regulations and good industrial hygiene practice.
		Wear protectiv	Vear chemical safety glasses or goggles to prevent eye contact. Vear protective clothing if needed to avoid skin contact and contamination of personal clothing. Suitable washing should be available in the work area. Contaminated clothing should be removed and laundered before re-use.		
		of personal clot			
		Contaminated			
		Wear impervio	us gloves to avoid prolonged skin contact.		



Released: 2016-05-03

Version: 1.1 Revision Date: 2016-05-03

## 9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance	Liquid	
Color	Clear	
Odor	Characteristic odor	
Odor Threshold	No data available	
рН	No data available	
Freezing Point	No data available	
Boiling Point	98.2 - 98.4 °C (208.76 – 209.12) (Heptane)	
Flash Point	-4 °C (24.8 °F) (Heptane)	
Evaporation Rate	No data available	
Flammability (solid, gas)	Not applicable	
Upper Explosion Limit	6.7% (heptane)	
Lower Explosion Limit	1.05% (t heptane)	
Vapor Pressure	6.09 kPa @ 25°C (77°F) (Heptane)	
Vapor Density (Air=1)	No data available	
Relative Density	0.69 @ 15°C (59°F) (Heptane)	
Solubility	In water: 2.4 mg/L @ 25°C (77°F) (Heptane)	
Partition Coefficient: n-	No data available	
octanol/water		
Auto Ignition	204°C (399.2°F) (Heptane)	
Temperature		
Decomposition	No data available	
Temperature		
Volatile Organic	No data available	
Compounds (VOC)		
Viscosity	0.641 mm2/s @ 20º (68ºF)	

## **10. STABILITY AND REACTIVITY**

Reactivity	Not expected to be reactive.	
Chemical Stability	Stable.	
Possibility of Hazardous Reactions	None known.	
Conditions to Avoid	Keep away from heat, sparks, flames and all other sources of ignition.	



Version: 1.1

## **BIKE CHAIN WAX**

Released: 2016-05-03	Revision Date: 2016-05-03
Incompatible Materials	Avoid contact with strong oxidizing agents, halogens, peroxides and strong reducing agents.
Hazardous Decomposition Product	Thermal decomposition may produce carbon oxides.

### **11. TOXICOLOGICAL INFORMATION**

### Potential Health Hazards

Eye Contact: May cause irritation with redness and tearing.

**Skin Contact:** Causes irritation with redness and drying of the skin. Prolonged contact may cause defatting of the skin and dermatitis. May cause an allergic skin reaction.

**Inhalation:** Inhalation of vapors may cause mucous membrane and respiratory irritation and central nervous system depression with symptoms of headache, dizziness, giddiness, intoxication, nausea, vomiting, disorientation, stupor and unconscious. Severe exposures may cause pulmonary edema. **Ingestion:** Ingestion may cause mucous membrane and gastrointestinal irritation and nervous system depression with symptoms of headache, dizziness, nausea, narcosis and unconsciousness. Aspiration into the lungs during ingestion or vomiting may cause serious lung damage which may be fatal. **Chronic Effects of Overexposure:** None known.

Sensitization: This product is classified as a skin sensitizer. Cinnamal and Butanedioic acid ((4,5dihydro-5-thioxo-1,3,4-thiadiazol-2-yl) thio-bis (2-ethylhexyl) ester are classified as skin sensitizers. Mutagenicity: No data available for mixture. Components are not germ cell mutagens. Reproductive Toxicity: This product contains hexane, which is suspected of damaging fertility or the unborn child. In an acute inhalation toxicity study researchers exposed male Sprague-Dawley rats (12–39/group) to 5000 ppm n-hexane (99% pure) in either a single 24-hour exposure, repeated 16hour/day exposures for up to 8 days, or repeated 16-hour/day exposures, 6 hours/day for up to 6 weeks. Animals exposed for 16 hr/day, 6 days/week at the same concentration of 5000 ppm for up to 6 weeks induced progressive increases in testicular and epididymal lesions, which, after 5 weeks (when most animals began to show clinical symptoms of polyneuropathy), reached aplasia of the germinal epithelium involving also the spermatogonia. After interruption of the treatment, the testicular lesions became increasingly severe, up to complete atrophy of the seminiferous tubules, which suggests irreversible sterility.

**Carcinogenicity**: None of the components of this product are listed as a carcinogen or suspected carcinogen by IARC, NTP, or OSHA.

### Acute Toxicity:

Product ATE: Oral LD50: 100,000 mg/kg, Dermal LD50: 220,000 mg/kg

Petroleum Distillates: Oral rat LD50 >5000 mg/kg, Inhalation rat LC50 2.18 mg/L, Dermal rabbit LD50 >2000 mg/kg

Heptane: Oral rat LD50 >5000 mg/kg, Inhalation rat LC50 >29.29 mg/L/4 hr, Dermal rabbit LD50 >2000 mg/kg.

Cyclohexane: Oral rat LD50 >5000 mg/kg, Inhalation rat LC50 19.27 mg/L/4 hr, Dermal rabbit LD50 >2000 mg/kg



Released: 2016-05-03

Version: 1.1 Revision Date: 2016-05-03

Stoddard Solvent: Oral rat LD50 > 5000 mg/kg, inhalation rat LC50 > 5.5 mg/L/4 hr

Hydrotreated light distillate (Petroleum): Oral rat LD50 >5000 mg/kg, Inhalation rat LC50 >4.3 mg/L/4 hr, Dermal rabbit LD50 >2000 mg/kg

Acetone: Oral rat LD50: 5800 mg/kg, inhalation rat LC50: 50.1 mg/L/4 hr, dermal rabbit LD50 > 15800 mg/kg.

Hexane: Oral rat LD50 16000 mg/kg, Inhalation rat LC50 17.6 mg/L/4 hr, Dermal rabbit LD50 3.35 g/kg Cinnamal: Oral guinea pig LD50: 3400 mg/kg, inhalation rat LD50: 68.88 mg/L/4 hr, dermal rat LD50 > 2000 mg/kg.

Benzyl benzoate: Oral rat LD50 > 2000 mg/kg, dermal rabbit LD50 > 2000 mg/kg

Butanedioic acid ((4,5-dihydro-5-thioxo-1,3,4-thiadiazol-2-yl) thio-bis (2-ethylhexyl) ester: No data available

## **12. ECOLOGICAL INFORMATION**

### Ecotoxicity

Petroleum Distillates: 96 hr LL50 Pimephales promelas >100 mg/L, 48 hr EL50 >10000 mg/L Heptane: 96 hr LL50 Oncorhynchus mykiss 5.29 mg/L, 48 hr EC50 daphnia magna 1.5 mg/L, 72 hr EC50 Pseudokirchnerella subcapitata 4.338 mg/L, 21 days NOEC daphnia magna: 0.17 mg/L Cyclohexane: 96 hr LC50 Pimephales promelas 4.53 mg/L, 48 hr EC50 daphnia magna 0.9 mg/L, 72 hr EC50 Pseudokirchnerella subcapitata 9.317 mg/L Hydrotreated light distillate (Petroleum): 96 hr LL50 Oncorhynchus mykiss: 2-5 mg/L Acetone: 96 hr LC50 Oncorhynchus mykiss: 5540 mg/L Hexane: 96 hr LL50 Oncorhynchus mykiss 12.51 mg/L, 48 hr LC50 Daphnia magna 21.85 mg/L, 72 hr EL50 Pseudokirchnerella subcapitata 9.285 mg/L Cinnamal: 96 hr LC50 Poecilia reticulate > 3.5 mg/L Benzyl benzoate: 96 hr LC50 Danio rerio: 2.3 mg/L

This product is very toxic to aquatic life with long lasting effects. Releases to the environment should be avoided.

Biodegradation	Heptane, cyclohexane and hexane are readily biodegradable. Petroleum distillates are inherently biodegradable. Acetone: Readily biodegradable – 100% in 4 days. Cinnamal: Readily biodegradable – 100% in 28 days. Benzyl benzoate: Readily biodegradable 94% in 28 days.
Bioaccumulation	Heptane has BCF less than 3. This suggests the bioconcentration in aquatic organisms is expected to be low.
Mobility in soil Other adverse effects	Heptane and cyclohexane are moderately mobile in soil. None known.

### **13. DISPOSAL CONSIDERATIONS**

Disposal

Dispose in accordance with all local, state and national regulations.



Version: 1.1 Revision Date: 2016-05-03

Released: 2016-05-03

### **14. TRANSPORT INFORMATION**

	UN	Proper shipping name	Hazard	Packing	Environmental
	Number		Class	Group	Hazard
DOT	UN1268	Petroleum distillates, n.o.s.	3	PGII	Marine Pollutant
TDG	UN1268	Petroleum distillates, n.o.s.	3	PGII	No
IMDG	UN1268	Petroleum distillates, n.o.s.	3	PGII	Marine Pollutant
ΙΑΤΑ	UN1268	Petroleum distillates, n.o.s.	3	PGII	No

Note: This product can be shipped as a limited quantity if the packaging complies.

Note: Inner packages with less than 5 liters of liquid/ 5 kg of solid are exempt from Marine Pollutant per DOT 171.4, IMDG Code 2.10.2.7 and ICAO Special Provision A197.

**Transport in bulk (according to Annex II of MARPOL 73/78 and the IBC Code):** Not applicable – product is transported only in packaged form

Special precautions: None known.

**CERCLA:** This product has a Reportable Quantity (RQ) of 12,500 lbs. (based on the RQ for cyclohexane of 1,000 lbs). Releases above the RQ must be reported to the National Response Center. Many states have more stringent release reporting requirements. Report spills required under federal, state and local regulations

**EPA SARA 302:** This product does not contain chemicals regulated under SARA Section 302.

EPA SARA 311 Hazard Classification: Acute Health, Chronic Health, Fire Hazard

**EPA SARA 313:** This product contains the following chemicals that are regulated under SARA Title III, section 313:

Components	Content %	CAS Number
Cyclohexane	4-8	110-82-7

**California Proposition 65:** This product contains chemicals known to the State of California to cause cancer and reproductive toxicity.

#### **Chemical Inventories**

Toxic Substances Control Act: All of the components of this product are listed on the TSCA inventory

16. OTHER	INFORMATION	
-----------	-------------	--

NFPA Rating (NFPA 704):	Health: 2	Fire: 3	Instability: 0
-------------------------	-----------	---------	----------------



Released: 2016-05-03

Version: 1.1 Revision Date: 2016-05-03

HMIS Rating: \*Chronic Health Hazard Health: 2\*

Fire: 3

Physical Hazard: 0

Supersedes: None Date Updated: May 3, 2016 Revision Summary: New document.

The above information is based on the data of which we are aware and is believed to be correct as of the date hereof. Since this information may be applied under conditions beyond our control and with which we may be unfamiliar and since data made available subsequent to the date hereof may suggest modifications of the information, we do not assume any responsibility for the results of its use. This information is furnished upon condition that the person receiving it shall make his own determination of the suitability of the material for his particular purpose.