



MATERIAL SAFETY DATA SHEET

1. Product and Company Identification

Material name	Bel-Ray EXL Mineral 4T Engine Oil 10W-40
Product Code	99090
MSDS Number	6394
Version #	1.0
Revision date	06-14-2010
Product use	Lubricant
Manufacturer information	Bel-Ray Company, Inc. P.O. Box 526 Farmingdale, NJ 07727 United States of America +1 732 938 2421 CHEMTREC: +1 703-527-3887 (outside USA) CHEMTREC: 800-424-9300 (USA)

2. Hazards Identification

Emergency overview	Health injuries are not known or expected under normal use. This is a consumer care product that is safe for consumers when used according to the label directions. Like many consumer products, a small number of individuals may experience reactions such as redness, rash and / or swelling upon prolonged or repeated skin contact or eye contact.
OSHA regulatory status	This product is considered not hazardous under 29 CFR 1910.1200 (Hazard Communication).
Potential health effects	
Eyes	Contact with eyes may cause irritation.
Skin	May cause skin irritation in susceptible persons.
Inhalation	Health injuries are not known or expected under normal use.
Ingestion	Health injuries are not known or expected under normal use.
Signs and symptoms	Irritation of eyes and mucous membranes.
Potential environmental effects	Not expected to be harmful to aquatic organisms.

3. Composition / Information on Ingredients

Non-hazardous components	CAS #	Percent
Interchangeable base oils, one or more: 64741-88-4, 64742-65-0, 64742-52-5		>= 80

4. First Aid Measures

First aid procedures	
Eye contact	Rinse with water. Get medical attention if irritation develops and persists.
Skin contact	Rinse skin with water/shower. Get medical attention if irritation develops and persists.
Inhalation	Move to fresh air. Call a physician if symptoms develop or persist.
Ingestion	Rinse mouth. Do not induce vomiting. If ingestion of a large amount does occur, call a poison control center immediately. Never give liquid to an unconscious person.
General advice	Call a physician if symptoms develop or persist.

5. Fire Fighting Measures

Flammable properties	Not flammable by OSHA criteria. Not combustible by OSHA criteria.
Extinguishing media	
Suitable extinguishing media	Water. Water spray. Foam. Dry powder. Carbon dioxide (CO2).
Fire fighting equipment/instructions	Not available.

Specific methods	Cool containers exposed to flames with water until well after the fire is out.
Hazardous combustion products	May include oxides of nitrogen. Carbon monoxide and carbon dioxide.

6. Accidental Release Measures

Personal precautions	Keep unnecessary personnel away. In case of spills, beware of slippery floors and surfaces.
Environmental precautions	Prevent further leakage or spillage if safe to do so. Do not contaminate water.
Methods for containment	ELIMINATE all ignition sources (no smoking, flares, sparks or flames in immediate area). Use water spray to reduce vapors or divert vapor cloud drift.
Methods for cleaning up	Should not be released into the environment. Dike far ahead of spill for later disposal. Wipe up with absorbent material (e.g. cloth, fleece). Following product recovery, flush area with water.
	Never return spills in original containers for re-use.

7. Handling and Storage

Handling	DO NOT handle, store or open near an open flame, sources of heat or sources of ignition. Protect material from direct sunlight. Avoid release to the environment. Handle and open container with care.
Storage	Keep away from heat, sparks and open flame. Room temperature - normal conditions. Keep out of the reach of children. Use care in handling/storage.

8. Exposure Controls / Personal Protection

Occupational exposure limits

ACGIH

Components	Type	Value	Form
Interchangeable base oils, one or more: 64741-88-4, 64742-65-0, 64742-52-5	STEL	10.0000 mg/m3	Mist.
	TWA	5.0000 mg/m3	Mist.

U.S. - OSHA

Components	Type	Value	Form
Interchangeable base oils, one or more: 64741-88-4, 64742-65-0, 64742-52-5	PEL	5.0000 mg/m3	Mist.
	TWA	2000.0000 mg/m3 500.0000 ppm 5.0000 mg/m3 400.0000 ppm 1600.0000 mg/m3	Mist.

Personal protective equipment

Eye / face protection	Not normally needed.
Skin protection	No special protective equipment required.
Respiratory protection	No personal respiratory protective equipment normally required.
General hygiene considerations	Handle in accordance with good industrial hygiene and safety practice.

9. Physical & Chemical Properties

Appearance	Oily.
Color	Amber.
Odor	Petroleum
Odor threshold	Not available.
Physical state	Liquid
Form	Liquid.
pH	Not available.
Melting point/Freezing point	Not available.
Boiling point	649.4 °F (343 °C) estimated

Flash point	370.4 °F (188 °C) Pensky-Martens Closed Cup
Evaporation rate	Not available.
Flammability limits in air, upper, % by volume	Not available.
Flammability limits in air, lower, % by volume	Not available.
Vapor pressure	0.13 hPa estimated
Density	872 kg/m ³
Vapor density	Not available.
Specific gravity	0.872
Relative density	Not available.
Solubility (water)	Negligible
Solubility (other)	Oil Solvents
Partition coefficient (n-octanol/water)	Not available.
Auto-ignition temperature	500 °F (260 °C) estimated
Decomposition temperature	Not available.
VOC	0.751998 % estimated
Percent volatile	0.0846 % estimated

10. Chemical Stability & Reactivity Information

Chemical stability	Material is stable under normal conditions.
Conditions to avoid	Heat, flames and sparks.
Hazardous decomposition products	Nitrogen oxides (NOx). At thermal decomposition temperatures, carbon monoxide and carbon dioxide.

11. Toxicological Information

Toxicological data

Product	Test Results
Bel-Ray EXL Mineral 4T Engine Oil 10W-40 (Mixture)	Acute Dermal LD50 Rabbit: 3425 mg/kg estimated Acute Oral LD50 Rat: 2364 g/kg estimated

* Estimates for product may be based on additional component data not shown.

Local effects	Ingestion may cause gastrointestinal irritation, nausea, vomiting and diarrhea. Contact with eyes may cause irritation. May cause skin irritation.
Carcinogenicity	This product is not considered to be a carcinogen by IARC, ACGIH, NTP, or OSHA.
Further information	This product has no known adverse effect on human health.

12. Ecological Information

Ecotoxicological data

Product	Test Results
Bel-Ray EXL Mineral 4T Engine Oil 10W-40 (Mixture)	EC50 Daphnia: 684 mg/l 48.00 hours estimated LC50 Fish: 801 mg/l 96.00 hours estimated

* Estimates for product may be based on additional component data not shown.

Ecotoxicity	Contains a substance which causes risk of hazardous effects to the environment.
Environmental effects	An environmental hazard cannot be excluded in the event of unprofessional handling or disposal.
Persistence and degradability	Not available.

13. Disposal Considerations

Disposal instructions	Do not allow this material to drain into sewers/water supplies. This product, in its present state, when discarded or disposed of, is not a hazardous waste according to Federal regulations (40 CFR 261.4 (b)(4)). Under RCRA, it is the responsibility of the user of the product to determine, at the time of disposal, whether the product meets RCRA criteria for hazardous waste. Dispose in accordance with all applicable regulations.
Waste from residues / unused products	Dispose of in accordance with local regulations.

14. Transport Information

DOT
Not regulated as dangerous goods.
IATA
Not regulated as dangerous goods.
IMDG
Not regulated as dangerous goods.

15. Regulatory Information

US federal regulations	This product is not known to be a "Hazardous Chemical" as defined by the OSHA Hazard Communication Standard, 29 CFR 1910.1200. All components are on the U.S. EPA TSCA Inventory List.
-------------------------------	---

CERCLA (Superfund) reportable quantity

None

Superfund Amendments and Reauthorization Act of 1986 (SARA)

Hazard categories	Immediate Hazard - No Delayed Hazard - No Fire Hazard - No Pressure Hazard - No Reactivity Hazard - No
Section 302 extremely hazardous substance	No
Section 311 hazardous chemical	No

Inventory status

Country(s) or region	Inventory name	On inventory (yes/no)*
Australia	Australian Inventory of Chemical Substances (AICS)	Yes
Canada	Domestic Substances List (DSL)	Yes
China	Inventory of Existing Chemical Substances in China (IECSC)	Yes
Europe	European Inventory of Existing Commercial Chemical Substances (EINECS)	Yes
Korea	Existing Chemicals List (ECL)	Yes
Philippines	Philippine Inventory of Chemicals and Chemical Substances (PICCS)	Yes
United States & Puerto Rico	Toxic Substances Control Act (TSCA) Inventory	Yes

*A "Yes" indicates that all components of this product comply with the inventory requirements administered by the governing country(s)

State regulations	WARNING: This product contains a chemical known to the State of California to cause cancer and birth defects or other reproductive harm.
--------------------------	--

US - California Proposition 65 - CRT: Listed date/Carcinogenic substance

ARSENIC (CAS 7440-38-2)	Listed: February 27, 1987 Carcinogenic.
CADMIUM AND COMPOUNDS (CAS 7440-43-9)	Listed: October 1, 1987 Carcinogenic.
LEAD (CAS 7439-92-1)	Listed: October 1, 1992 Carcinogenic.

US - California Proposition 65 - CRT: Listed date/Developmental toxin

CADMIUM AND COMPOUNDS (CAS 7440-43-9)	Listed: May 1, 1997 Developmental toxin.
LEAD (CAS 7439-92-1)	Listed: February 27, 1987 Developmental toxin.

US - California Proposition 65 - CRT: Listed date/Female reproductive toxin

LEAD (CAS 7439-92-1)	Listed: February 27, 1987 Female reproductive toxin.
----------------------	--

US - California Proposition 65 - CRT: Listed date/Male reproductive toxin

CADMIUM AND COMPOUNDS (CAS 7440-43-9)

Listed: May 1, 1997 Male reproductive toxin.

LEAD (CAS 7439-92-1)

Listed: February 27, 1987 Male reproductive toxin.

16. Other Information**Further information**

HMIS® is a registered trade and service mark of the NPCA.

HMIS® ratings

Health: 1

Flammability: 1

Physical hazard: 0

NFPA ratings

Health: 0

Flammability: 1

Instability: 0

Disclaimer

Bel-Ray Company cannot anticipate all conditions under which this information and its product, or the products of other manufacturers in combination with its product, may be used. It is the user's responsibility to ensure safe conditions for handling, storage and disposal of the product, and to assume liability for loss, injury, damage or expense due to improper use. The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

Issue date

06-14-2010