

Printing date 01/20/2017 Reviewed on 01/01/2022

#### 1 Identification

- Product identifier
- Trade name: Muc-Off Bio Degreaser
- · Article number: 948US
- · Application of the substance / the mixture Cleaner solvent
- Details of the supplier of the safety data sheet
- · Manufacturer/Supplier:

UK - Muc-Off Ltd, Unit 23 Branksome Business Park, Bourne Valley Road, Poole, Dorset, BH12 1DW

· EU- Muc-Off Ltd, Unit 3D North Point House, North Point Business Park, New Mallow Road, Cork, Ireland, T23 AT2P

Tel: +44(0)1202 307790 Email: info@muc-off.com

- · Information department: Research & Development/E-mail: info@muc-off.com
- Emergency telephone number: during normal opening hours: CHEMTREC: 1-800-424-9300 24HR

### 2 Hazard(s) identification

· Classification of the substance or mixture



GHS02 Flame

Flam. Aerosol 1 H222-H229 Extremely flammable aerosol. Pressurized container: May burst if heated.



GHS08 Health hazard

Asp. Tox. 1 H304 May be fatal if swallowed and enters airways.

- · Label elements
- · GHS label elements

The product is classified and labeled according to the Globally Harmonized System (GHS).

· Hazard pictograms





GHS02

GHS08

- · Signal word Danger
- · Hazard-determining components of labeling:

Hydrocarbons,C10-C13,n-alkanes,cyclic,<2% aromates, Benzene <0.1%

· Hazard statements

H222-H229 Extremely flammable aerosol. Pressurized container: May burst if heated.

H304 May be fatal if swallowed and enters airways.

· Precautionary statements

P210 Keep away from heat/sparks/open flames/hot surfaces. No smoking.

P251 Do not pierce or burn, even after use.

P260 Do not breathe spray.

P211 Do not spray on an open flame or other ignition source.

P280 Wear protective gloves / eye protection.

P273 Avoid release to the environment.

P271 Use only outdoors or in a well-ventilated area.

P301+P310 IF SWALLOWED: Immediately call a doctor.

P304+P340 IF INHALED: Remove person to fresh air and keep comfortable for breathing.

P331 Do NOT induce vomiting.

P410+P412 Protect from sunlight. Do not expose to temperatures exceeding 50°C/122°F.

(Contd. on page 2)

(Contd. of page 1)

## **Safety Data Sheet** acc. to OSHA HCS

Reviewed on 01/01/2022 Printing date 01/20/2017

#### Trade name: Muc-Off Bio Degreaser

P403 Store in a well-ventilated place.

P501 Dispose of contents/container in accordance with local/regional/national/international regulations.

- · Classification system:
- · NFPA ratings (scale 0 4)



Health = 0Fire = 4Reactivity = 3

· WHMIS-ratings (scale 0 - 4)



Fire = 4

- · Other hazards
- · Results of PBT and vPvB assessment
- · PBT: Not applicable.
- · vPvB: Not applicable.

## 3 Composition/information on ingredients

· Chemical characterization: Mixtures

· Description: Cleansing agent

· Dangerous components:		
Reg.nr.: 01-2119457273-39	Hydrocarbons,C10-C13,n-alkanes,cyclic,<2% aromates, Benzene <0.1%	50-<75%
CAS: 106-97-8 Reg.nr.: 01-2119474691-32	butane (containing < 0.1% butadiene (203-450-8))	10-<25%
CAS: 74-98-6 Reg.nr.: 01-2119486944-21	propane	10-<25%

## 4 First-aid measures

- · Description of first aid measures
- · After inhalation: Supply fresh air; consult doctor in case of complaints.
- · After skin contact: Generally the product does not irritate the skin.
- · After eye contact: Rinse opened eye for several minutes under running water.
- · After swallowing: Do not induce vomiting; immediately call for medical help.
- · Information for doctor:
- · Most important symptoms and effects, both acute and delayed No further relevant information available.
- · Indication of any immediate medical attention and special treatment needed

No further relevant information available.

#### 5 Fire-fighting measures

- · Extinguishing media
- · Suitable extinguishing agents:

Water haze

Fire-extinguishing powder

Carbon dioxide

Alcohol resistant foam

- · For safety reasons unsuitable extinguishing agents: Water with full jet
- · Special hazards arising from the substance or mixture No further relevant information available.

(Contd. on page 3)

Printing date 01/20/2017 Reviewed on 01/01/2022

Trade name: Muc-Off Bio Degreaser

(Contd. of page 2)

· Advice for firefighters

· Protective equipment: Mount respiratory protective device.

#### 6 Accidental release measures

#### · Personal precautions, protective equipment and emergency procedures

Wear protective equipment. Keep unprotected persons away.

#### · Environmental precautions:

Do not allow product to reach sewage system or any water course.

Inform respective authorities in case of seepage into water course or sewage system.

Do not allow to enter sewers/ surface or ground water.

### · Methods and material for containment and cleaning up:

Ensure adequate ventilation.

Do not flush with water or aqueous cleansing agents

### · Reference to other sections

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

#### · Protective Action Criteria for Chemicals

· PAC-1:					
106-97-8	butane (containing < 0.1% butadiene (203-450-8))	5500* ppm			
74-98-6	propane 5500				
· PAC-2:	· PAC-2:				
106-97-8	butane (containing < 0.1% butadiene (203-450-8))	17000** ppm			
74-98-6	propane 17000** pp				
· PAC-3:					
106-97-8	butane (containing < 0.1% butadiene (203-450-8)) 53000*** pp				
74-98-6	propane	33000*** ppm			

#### 7 Handling and storage

#### · Handling:

#### · Precautions for safe handling

Ensure good ventilation/exhaustion at the workplace.

Open and handle receptacle with care.

### · Information about protection against explosions and fires:

Do not spray on a naked flame or any incandescent material.

Keep ignition sources away - Do not smoke.

Protect against electrostatic charges.

Pressurized container: protect from sunlight and do not expose to temperatures exceeding 50 °C, i.e. electric lights. Do not pierce or burn, even after use.

#### · Conditions for safe storage, including any incompatibilities

· Storage:

#### · Requirements to be met by storerooms and receptacles:

Store in a cool location.

Observe official regulations on storing packagings with pressurized containers.

#### · Information about storage in one common storage facility:

Observe official regulations on storing packagings with pressurized containers.

#### · Further information about storage conditions:

Keep receptacle tightly sealed.

Do not gas tight seal receptacle.

Store in cool, dry conditions in well sealed receptacles.

Protect from heat and direct sunlight.

(Contd. on page 4)

Printing date 01/20/2017 Reviewed on 01/01/2022

Trade name: Muc-Off Bio Degreaser

· Specific end use(s) No further relevant information available.

(Contd. of page 3)

### 8 Exposure controls/personal protection

- · Additional information about design of technical systems: No further data; see item 7.
- · Control parameters
- · Components with limit values that require monitoring at the workplace:

The following constituents are the only constituents of the product which have a PEL, TLV or other recommended exposure limit.

At this time, the remaining constituent has no known exposure limits.

### **106-97-8 butane (containing < 0.1% butadiene (203-450-8))**

REL Long-term value: 1900 mg/m³, 800 ppm
TLV Short-term value: (2370) mg/m³, (1000) ppm
NIC-EX

### 74-98-6 propane

PEL Long-term value: 1800 mg/m³, 1000 ppm
REL Long-term value: 1800 mg/m³, 1000 ppm
TLV refer to Appendix F inTLVs&BEIs book; NIC-EX

- · Additional information: The lists that were valid during the creation were used as basis.
- · Exposure controls
- · Personal protective equipment:
- · General protective and hygienic measures:

Wash hands before breaks and at the end of work.

Do not inhale gases / fumes / aerosols.

· Breathing equipment:

In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use respiratory protective device that is independent of circulating air.

Filter AX/P2

Use suitable respiratory protective device in case of insufficient ventilation.

Filter A/P2

#### · Protection of hands:

Wear gloves for the protection against chemicals according to EN 374



Protective gloves

Solvent resistant gloves

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

#### · Material of gloves

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

Nitrile rubber, NBR

Recommended thickness of the material:  $\geq 0.5 \text{ mm}$ 

#### · Penetration time of glove material

For continuous contact we recommend gloves with breakthrough time of at least 240 minutes, with the preference given to a breakthrough time greater than 480 minutes. For short-term or splash guard we recommend the same. We are aware that suitable gloves that offer this level of protection may not be available. In that case, a shorter breakthrough time are acceptable as long as the procedures governing maintenance and timely replacement are followed. The thickness of the gloves is not a good measure of the resistance of the gloves against a chemical substance, because this depends on the exact composition of the material from which the gloves are made.

(Contd. on page 5)

Printing date 01/20/2017 Reviewed on 01/01/2022

Trade name: Muc-Off Bio Degreaser

(Contd. of page 4)

The exact break trough time has to be found out by the manufacturer of the protective gloves and has to be observed.

• Eye protection: Safety glasses



Tightly sealed goggles

· Body protection: Use protective suit.

## 9 Physical and chemical properties

71 Hysicai and chemicai proper	91 hysical and chemical properties		
<ul> <li>Information on basic physical and chemical properties</li> <li>General Information</li> <li>Appearance:</li> </ul>			
Form:	Aerosol		
Color:	According to product specification		
· Odor:	Characteristic		
· Odor threshold:	Not determined.		
· pH-value:	Not determined.		
· Change in condition			
Melting point/Melting range:	Undetermined.		
Boiling point/Boiling range:	-44 °C (-47 °F)		
· Flash point:	-97 °C (-143 °F)		
· Flammability (solid, gaseous):	Not applicable.		
· Ignition temperature:	236 °C (457 °F)		
· Decomposition temperature:	Not determined.		
· Auto igniting:	Product is not selfigniting.		
· Danger of explosion:	Product is not explosive. However, formation of explosive air/vapor mixtures are possible.		
· Explosion limits:			
Lower:	0.7 Vol %		
Upper:	10.9 Vol %		
· Vapor pressure at 20 °C (68 °F):	8300 hPa (6226 mm Hg)		
Density at 20 °C (68 °F):	0.7 g/cm³ (5.842 lbs/gal)		
· Relative density	Not determined.		
· Vapor density	Not determined.		
· Evaporation rate	Not applicable.		
<u> </u>	ног аррисаоте.		
· Solubility in / Miscibility with			
Water:	Not miscible or difficult to mix.		
· Partition coefficient (n-octanol/water): Not determined.			
· Viscosity:			
Dynamic:	Not determined.		
Kinematic:	Not determined.		
Calana Anna Anna			
· Solvent content:			
Organic solvents:	94.8 %		
Solids content:	0.2 %		
	(Contd. on mage 6)		

(Contd. on page 6)

Printing date 01/20/2017 Reviewed on 01/01/2022

Trade name: Muc-Off Bio Degreaser

(Contd. of page 5)

· Other information

No further relevant information available.

## 10 Stability and reactivity

- · Reactivity No further relevant information available.
- · Chemical stability
- Thermal decomposition / conditions to be avoided: No decomposition if used according to specifications.
- · Possibility of hazardous reactions No dangerous reactions known.
- · Conditions to avoid No further relevant information available.
- · Incompatible materials: No further relevant information available.
- · Hazardous decomposition products: No dangerous decomposition products known.

### 11 Toxicological information

- · Information on toxicological effects
- · Acute toxicity:
- · LD/LC50 values that are relevant for classification:

#### Hydrocarbons, C10-C13, n-alkanes, cyclic, <2% aromates, Benzene <0.1%

Oral	LD50	>5000 mg/kg (rat)
Dermal	LD50	>5000 mg/kg (rabbit)
Inhalative	LC50/4h	>4951 mg/l (rat)

- · Primary irritant effect:
- · on the skin: No irritant effect.
- · on the eye: No irritating effect.
- · Sensitization: No sensitizing effects known.
- · Additional toxicological information:
- · Carcinogenic categories
- · IARC (International Agency for Research on Cancer)

None of the ingredients is listed.

· NTP (National Toxicology Program)

None of the ingredients is listed.

· OSHA-Ca (Occupational Safety & Health Administration)

None of the ingredients is listed.

#### 12 Ecological information

· Toxicity

### · Aquatic toxicity:

#### Hydrocarbons, C10-C13, n-alkanes, cyclic, <2% aromates, Benzene <0.1%

EL0 (48h) 1000 mg/l (Daphnia magna)
EL0(72h) 1000 mg/l (Pseudokirchneriella subcapitata)
LL0(96h) 1000 mg/l (Oncorhynchus mykiss (96h))

- · Persistence and degradability No further relevant information available.
- · Behavior in environmental systems:
- · Bioaccumulative potential No further relevant information available.
- · Mobility in soil No further relevant information available.
- · Ecotoxical effects:
- · **Remark:** Harmful to fish

(Contd. on page 7)

Printing date 01/20/2017 Reviewed on 01/01/2022

Trade name: Muc-Off Bio Degreaser

(Contd. of page 6)

- · Additional ecological information:
- · General notes:

Water hazard class 1 (Self-assessment): slightly hazardous for water

Do not allow undiluted product or large quantities of it to reach ground water, water course or sewage system. Harmful to aquatic organisms

- · Results of PBT and vPvB assessment
- · PBT: Not applicable.
- · vPvB: Not applicable.
- · Other adverse effects No further relevant information available.

## 13 Disposal considerations

- · Waste treatment methods
- · Recommendation:

Must not be disposed of together with household garbage. Do not allow product to reach sewage system.

- · Uncleaned packagings:
- · Recommendation: Disposal must be made according to official regulations.

### 14 Transport information

	<b>T</b> T	ъ. т			
٠	U	N.	· N	III	ıber

· DOT, ADR, ADN, IMDG, IATA UN1950

· UN proper shipping name

DOT Aerosols, flammable
 ADR, ADN UN1950 Aerosols
 IMDG AEROSOLS

· IATA AEROSOLS, flammable

- · Transport hazard class(es)
- $\cdot$  DOT



· Class 2.1 · Label 2.1

 $\cdot$  ADR



Class
 Label
 2 5F Gases
 2.1

 $\cdot$  ADN

 $\cdot$  ADN/R Class: 2 5F

· IMDG, IATA



· Class 2.1

(Contd. on page 8)

Printing date 01/20/2017 Reviewed on 01/01/2022

Trade name: Muc-Off Bio Degreaser

	(Contd. of page
Label	2.1
Packing group DOT, ADR, IMDG, IATA	Void
Environmental hazards: Marine pollutant:	No
Special precautions for user Danger code (Kemler): EMS Number: Stowage Code Segregation Code	Warning: Gases  F-D,S-U SW1 Protected from sources of heat. SW22 For AEROSOLS with a maximum capacity of 1 litre: Category A. For AEROSOLS with a capacity above 1 litre: Category B. For WASTE AEROSOLS: Category C, Clear of living quarters. SG69 For AEROSOLS with a maximum capacity of 1 litre: Segregation as for class 9. Stow "separated from" class 1 except for division 1.4. For AEROSOLS with a capacity abov 1 litre: Segregation as for the appropriate subdivision of class 2. For WASTE AEROSOLS: Segregation as for the
Transport in bulk according to Annex MARPOL73/78 and the IBC Code	appropriate subdivision of class 2.  II of  Not applicable.
Transport/Additional information:	1 tot applicable.
• ADR • Excepted quantities (EQ)	Code: E0 Not permitted as Excepted Quantity
· IMDG · Limited quantities (LQ) · Excepted quantities (EQ)	1L Code: E0 Not permitted as Excepted Quantity
UN "Model Regulation":	UN 1950 AEROSOLS, 2.1

## 15 Regulatory information

- · Safety, health and environmental regulations/legislation specific for the substance or mixture
- · Sara
- · Section 355 (extremely hazardous substances):

None of the ingredient is listed.

· Section 313 (Specific toxic chemical listings):

None of the ingredients is listed.

· TSCA (Toxic Substances Control Act):

106-97-8 butane (containing < 0.1% butadiene (203-450-8))

74-98-6 propane

1338-43-8 Sorbitanoleate

- · Proposition 65
- · Chemicals known to cause cancer:

None of the ingredients is listed.

· Chemicals known to cause reproductive toxicity for females:

None of the ingredients is listed.

(Contd. on page 9)

Printing date 01/20/2017 Reviewed on 01/01/2022

Trade name: Muc-Off Bio Degreaser

(Contd. of page 8)

· Chemicals known to cause reproductive toxicity for males:

None of the ingredients is listed.

· Chemicals known to cause developmental toxicity:

None of the ingredients is listed.

· Cancerogenity categories

· EPA (Environmental Protection Agency)

None of the ingredients is listed.

· TLV (Threshold Limit Value established by ACGIH)

None of the ingredients is listed.

· MAK (German Maximum Workplace Concentration)

None of the ingredients is listed.

· NIOSH-Ca (National Institute for Occupational Safety and Health)

None of the ingredients is listed.

· National regulations:

Class	Share in %
NK	75-<100

· Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

#### 16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

- · Department issuing SDS: Research & Development
- · Date of preparation / last revision 01/20/2017 / 6
- · Abbreviations and acronyms:

ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

DOT: US Department of Transportation

IATA: International Air Transport Association

ACGIH: American Conference of Governmental Industrial Hygienists

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

NFPA: National Fire Protection Association (USA)

HMIS: Hazardous Materials Identification System (USA)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

PBT: Persistent, Bioaccumulative and Toxic

vPvB: very Persistent and very Bioaccumulative

NIOSH: National Institute for Occupational Safety

OSHA: Occupational Safety & Health

TLV: Threshold Limit Value

PEL: Permissible Exposure Limit

REL: Recommended Exposure Limit

Flam. Aerosol 1: Aerosols – Category 1

Asp. Tox. 1: Aspiration hazard - Category 1

- US