

MATERIAL SAFETY DATA SHEET

(If eventually identical to Form OSHA 201, it complies with 29 CFR 1910.1200)

SECTION I

TRADE NAME: WATERPROOF GREASE 80916

CODE NUMBER: 80916

DATE 9/14/94
SUPERCEDES

CHEMICAL FAMILY: Petroleum Hydrocarbon

CARCINOGENIC INGREDIENTS OSHA/NTP/IARC: NONE

C.A.S. NO. MIXTURE

TCSA INFORMATION: COMPONENTS OF THIS PRODUCT ARE LISTED.

SECTION II-HAZARDOUS INGREDIENTS

COMPONENTS	C.A.S. NOS.	TLV/PEL		% BY WEIGHT VOLUME
		PPM	mg/m3	
SOLVENT REFINED PETROLEUM BASE STOCK	64742183		5*	<95
* AS A MIST				
THIS PRODUCT DEFINED AS NON-HAZARDOUS				

SECTION III-FIRE AND EXPLOSION HAZARD DATA

HAZARDOUS THERMAL DECOMPOSITION CARBON MONOXIDE & ASPHYXIANTS		FLAMMABLE LIMITS: N/A
EXTINGUISHING MEDIA: WATER FOG, CO ₂ , FOAM & DRY CHEMICAL		FLASHPOINT: >200°C
UNUSUAL FIRE AND EXPLOSION HAZARDS: WATER MAY CAUSE FOAMING. FIRE MAY CAUSE DENSE SMOKE. CAN RELEASE FLAMMABLE VAPORS IF HEATED ABOVE FLASH POINT.		DOT INFORMATION: NOT REGULATED
SPECIAL FIRE FIGHTING PROCEDURES: DO NOT ENTER ANY ENCLOSED OR CONFINED AREA WITHOUT PROPER PROTECTIVE EQUIPMENT & SELF-CONTAINED BREATHING APPARATUS.		

SECTION IV-PHYSICAL DATA

BOILING RANGE: N/D		SOLUBILITY: NEGLIGIBLE PH: N/D		
VAPOR PRESSURE: N/D		APPEARANCE AND ODOR: BROWN SEMI-SOLID MINERAL OIL ODOR		
VAPOR DENSITY	EVAPORATION RATE	SPECIFIC GRAVITY	WEIGHT PER GALLON	% VOLATILE BY VOLUME
HEAVIER THAN AIR	LESS THAN ETHER	0.91	7.6	0

SECTION V-REACTIVITY DATA

INCOMPATIBILITY <MATERIAL TO AVOID>: AVOID CONTACT WITH STRONG OXIDIZERS	
STABILITY: STABLE	CONDITION TO AVOID: EXTREME HEAT
HAZARDOUS DECOMPOSITION PRODUCTS: CARBON MONOXIDE & ASPHYXIANTS	
HAZARDOUS POLYMERIZATION NONE	

SWL
A Division of Southwest Lubricants
9286 Abraham Way Santa, CA 92071
(619) 448-8000
SERV 24 HOURS
TOLL FREE: 800-424-8800

FIRE
HEALTH
REACTIVITY
PERSONAL PROTECTION (NFPA)

1

0

0

A

0

0

SECTION VI-HEALTH HAZARD DATA

80916

ROUTE OF EXPOSURE	ADVERSE AFFECTS	FIRST AID PROCEDURES	NFPA
	INQ INTESTINAL DISTRESS, VOMITTING & NAUSEA	SEE A PHYSICIAN IMMEDIATELY	
	INH ONLY APPLICABLE WITH HEATED MATERIAL. DIZZINESS, NAUSEA OR RESPIRATORY DISTRESS.	REMOVE VICTIM TO FRESH AIR. IF DISCOMFORT PERSISTS, GET MEDICAL HELP.	
	ECYON MAY CAUSE IRRITATION	FLUSH EYES WITH WATER FOR 15 MINUTES. IF DISCOMFORT PERSISTS, SEE A PHYSICIAN.	
	ASCQUINTE MAY CAUSE MINOR SKIN IRRITATION.	REMOVE EXCESS WITH PAPER OR CLOTH & WASH WITH SOAP & WATER.	
	CSCORINONIC MAY CAUSE DERMATITIS. IF INJECTED UNDER SKIN MAY CAUSE INFECTION, LOSS OF BLOOD CIRCULATION & POSSIBLE AMPUTATION.	IF SYMPTOMS PERSISTS, SEE A PHYSICIAN. IF INJECTED, GET IMMEDIATE MEDICAL HELP	

<DOT> SECTION VII-SPILL OR LEAK PROCEDURES <EPA>

STEPS TO BE TAKEN IN CASE

MATERIAL IS RELEASED OR SPILLED: TRANSFER BULK TO ANOTHER CONTAINER. ABSORB RESIDUE WITH AN INERT MATERIAL. SWEEP.

WASTE DISPOSAL METHOD: IN ACCORDANCE WITH ALL APPLICABLE FEDERAL, STATE & LOCAL REGULATIONS.

TRANSPORTATION INFORMATION: NOT D.O.T. REGULATED.

FREIGHT CLASSIFICATION: PETROLEUM LUBRICANT GREASE

SECTION VIII-SPECIAL PROTECTION INFORMATION

RESPIRATORY PROTECTION: NONE REQUIRED

PROTECTIVE GLOVES: RECOMMENDED

OTHER PROTECTIVE EQUIPMENT: NONE

VENTILATION: NONE

SECTION IX-SPECIAL PRECAUTIONS

PRECAUTION TO BE TAKEN WHEN HANDLING OR STORING:
KEEP CONTAINERS CLOSED EXCEPT WHEN IN USE.

PERSONAL HYGIENE: WASH WITH SOAP & WATER

OTHER PRECAUTIONS: LAUNDER SOILED CLOTHING.

APPROVED BY:

R. Reed

DATE: 9/14/94

A Division of Southwest Lubricants

WATERPROOF GREASE
PRODUCT

