

300V FACTORY LINE 15W-50

8362

Version nr : 1.00

Revised: 03/10/2005 Supersedes: 15/09/2005

1. IDENTIFICATION OF THE SUBSTANCE/PREPARATION AND THE COMPANY/UNDERTAKING

Product Information

Commercial Product Name

300V FACTORY LINE 15W-50

Product code

8362

Use of the Substance/Preparation

4 Stroke engine lubricant

1) 36010074

Manufacturer, importer, supplier

MOTUL - Regulation Departement

Zone Industrielle - Chemin du Corps de Garde

77360 VAIRES SUR MARNE - FRANCE

Telephone Telefax

Supplier

33.1.64.72.86.23 33.1.64.72.86.28

EMERGENCY TELEPHONE NUMBER

ORFILA: 33.1.45.42.59.59

Responsible Department

Health and Safety Department

2. COMPOSITION/INFORMATION ON INGREDIENTS

Identification of the preparation

<u>Hazardous components</u> Polyolefin polyamine succinimide polyol Weight %

CAS-No.

EINECS-No.

yolen

R53
Calcium long chain Alkaryl sulfonate

< 3 %

polymer

polymer

Xi,R43,R53

% 68610-84-4

271-877-7

3. HAZARDS IDENTIFICATION

EC Label

Specific hazards

none under normal use

- physico-chemical properties

No hazards resulting from material as supplied.

- properties affecting health

None known

- environmental properties

Ecological injuries are not known or expected under normal use.

4. FIRST AID MEASURES

General advice

In the case of accident or if you feel unwell, seek medical advice

immediately (show the label where possible).

- Inhalation

Move to fresh air.
If symptoms persist, call a physician.

- Eye contact

Rinse immediately with plenty of water, also under the eyelids.

Consult a physician if necessary

- Skin contact

Take off all contaminated clothing immediately.

Wash off immediately with soap and plenty of water.

Ingestion

Clean mouth with water and drink afterwards plenty of water.

Do not induce vomiting without medical advice.

5. FIRE-FIGHTING MEASURES

- Suitable extinguishing media

dry powder foam

MOTUL

France

119, bd Félix Faure

119, ba Felb B.P. 94

93303 Aubervilliers Cedex

fax: 0033.1.48.33.28.79 Email: alafeuil@motul.fr

phone: 0033.1.48.11.70.00

Page: 1/5



300V	FAC1	CORY	LINE	15W-50	
3007	FAU			1344-30	

8362

Version nr: 1.00

Revised: 03/10/2005

Supersedes: 15/09/2005

- Extinguishing media which must not be

used for safety reasons

carbon dioxide (CO2) high volume water jet

- Specific hazards

Incomplete combustion produces toxic gases, such as CO, CO2, various forms of hydrocarbons, aldehydes etc., and soots. Inhalation

is extremely dangerous.

- Specific methods

- Under fire conditions:

In the event of fire, wear self-contained breathing apparatus.

Dispose of promptly.

6. ACCIDENTAL RELEASE MEASURES

Personal precautions Depending on the risk of exposure, wear gloves, goggles, and

protective clothing.

Choose body protection according to the amount and concentration

of the dangerous substance at the work place.

Environmental precautions Do not let product enter drains.

Local authorities should be advised if significant spillages cannot be

contained.

For environmental protection remove and wash all contaminated

protective equipment before re-use.

Soak up with inert absorbent material (e.g. sand, silica gel, acid Methods for cleaning up

binder, universal binder, sawdust).

Contaminated surfaces will be extremely slippery.

Use personal protective equipment. Shovel into suitable container for disposal.

7. HANDLING AND STORAGE

- Safe handling advice

Handling

- Technical measures/Precautions

Provide sufficient air exchange and/or exhaust in work rooms.

Avoid contact with skin and eyes.

Storage

- Technical measures/Storage conditions

Use only receptacles, joints, pipes, etc, which are resistant to

hydrocarbons.

Keep containers tightly closed in a dry, cool and well-ventilated

place.

Keep away from food, drink and animal feeding stuffs.

Do not let product enter drains.

Keep at temperatures between 5 and 40 °C.

Keep out of reach of children.

Do not smoke.

Store in original container. Keep in a bunded area.

- Incompatible products

Incompatible with oxidising agents.

8. EXPOSURE CONTROLS / PERSONAL PROTECTION

MOTUL

119, bd Félix Faure

B.P. 94

93303 France Aubervilliers Cedex

phone: 0033.1.48.11.70.00

fax: 0033.1.48.33.28.79 Email: alafeuil@motul.fr Page:



300V FACTORY LINE 15W-50

8362

Version nr : 1.00

Revised: 03/10/2005

Supersedes: 15/09/2005





Personal protective equipment

Respiratory protection

Hand protection (EN 420, EN 374-3)

Breathing apparatus needed only when aerosol or mist is formed.

protective gloves

safety glasses

Glove material: nitrile rubber Layer thickness: 0,11 mm Breakthrough time: > 480 Min.

Eye protection (EN 166)

Skin and body protection (DIN - EN 465)

As required, wear a face mask, fluid-proof protective clothing, and

safety boots (when handling

drums)

Don't wear ring, watch or similar thing which will be able to hold the

product and may give rise to

some skin diseases,

Hygiene measures

Take off all contaminated clothing immediately.

When using do not eat or drink.

Avoid contact with the skin and the eyes.

Handle in accordance with good industrial hygiene and safety

practice.

9. PHYSICAL AND CHEMICAL PROPERTIES

Form

Colour

pΗ

Flash point

open cup

Water solubility

Solubility in other solvents

Viscosity **Explosion limits**

Specific gravity

liquid

amber

Not applicable

293 °C ASTM D 92

insoluble soluble

Soluble in hydrocarbons

115,7 mm²/s 40°C ASTM D 445

not applicable

866 kg/m3 20°C ISO 12185

10. STABILITY AND REACTIVITY

Stability

Stable at normal conditions

Materials to avoid

Incompatible with oxidising agents.

Hazardous decomposition products

Incomplete combustion produces toxic gases, such as CO, CO2, various forms of hydrocarbons, aldehydes etc., and soots. Inhalation

is extremely dangerous.

11. TOXICOLOGICAL INFORMATION

MOTUL

119, bd Félix Faure

B.P. 94

93303 France Aubervilliers Cedex

phone: 0033.1.48.11.70.00

fax: 0033.1.48.33.28.79 Email: alafeuil@motul.fr Page:

3/5



300V FACTORY LINE 15W-50				
Version nr : 1.00	Revised : 03/10/2005			
	Supersedes: 15/09/2005			

Local effects The following toxicological data shown are those obtained from tests

> on products of similar composition in accordance with The Chemicals (Hazard Information and Packaging for Supply)

Regulations 1994.

Acute toxicity Health injuries are not known or expected under normal use.

Ingestion Weakly toxic Eye contact Mild eye irritation

Skin contact Repeated or prolonged contact with the preparation may cause

removal of natural fat from the skin resulting in non-allergic contact

dermatitis and absorption through the skin.

Inhalation of vapours may cause irritation of the respiratory system

in very susceptible persons.

Chronic toxicity Repeated or prolonged exposure may cause skin irritation and

dermatitis, due to degreasing properties of the product.

12. ECOLOGICAL INFORMATION

Soil: In consideration of its physical and chemical characteristics, Mobility

the prodcut has only slight mobility in the soil.

Water: Insoluble, the product spreads over the surface of the water.

Do not flush into surface water or sanitary sewer system.

Aquatic toxicity Ecotoxicity effects

Inhalation

8362

no data available

13. DISPOSAL CONSIDERATIONS

Waste from residues / unused products Send to an approved Waste Collector

> Collect all waste in suitable and labelled containers and dispose of in compliance with licence from HMIP issued under sections 6 & 7 of

the Radioactive Substances Act 1960.

Do not flush into surface water or sanitary sewer system.

Contaminated packaging Where possible recycling is preferred to disposal or incineration.

The user's attention is drawn to the possible existence of local

regulations regarding disposal.

Send to an approved Waste Collector

In accordance with local and national regulations.

13 02 06 - synthetic engine, gear and lubricating oils

"Avis relatif à la nomenclature ds déchets du 11/11/1997"

14. TRANSPORT INFORMATION

EWC waste disposal No:

Land transport

NOTE

Class not regulated

Sea transport

Class not regulated

Air transport

Class not regulated

15. REGULATORY INFORMATION

EC Label

The product contains no substances classified as hazardous to health in concentrations which should be taken into account according to EC directive.

MOTUL

119, bd Félix Faure

B.P. 94

93303 Aubervilliers Cedex

France

fax: 0033.1.48.33.28.79 Email: alafeuil@motul.fr

phone: 0033.1.48.11.70.00

Page:

4/5



300V FACTORY LINE 15W-50

8362

Version nr: 1.00

Revised: 03/10/2005 Supersedes: 15/09/2005

Special regulations on certain preparations

This product contains - Calcium long chain Alkaryl sulfonate

May produce an allergic reaction.

France

This safety data sheet complies with the recommendations of European Community and French regulations. Contact your local branch for adaptation to spécific national requirements.

15-36

16. OTHER INFORMATION

16. Other information

This dossier supplements the technical notifications for use, but does not replace them. The information which it contains is based on our knowledge relating to the product in question on the date indicated. The information is given in good faith. The user's attention is also drawn to possible risks incurred if a product is employed for uses other than those for which it was designed. The information dossier does not, under any circumstances, discharge the user from the obligation of being aware of , and of applying , all the texts which govern his sphere of activity. He shall be solely responsible for taking the precautions associated with the use which he makes of the product. All the statutory provisions referred to are intended simply to assist the recipient in fulfilling the obligations encumbent upon him. This enumeration must not be considered to be exhaustive. The recipient must ensure that no obligations are encumbent upon him, as a result of texts other than those cited, relating to the holding and handling of the product, for which he alone is responsible.

Text of R phrases mentioned in Section 2

R38 - Irritating to skin.

R41 - Risk of serious damage to eyes.

R43 - May cause sensitization by skin contact.

R51/53 - Toxic to aquatic organisms, may cause long-term adverse

effects in the aquatic environment.

R53 - May cause long-term adverse effects in the aquatic

environment.

This data sheet conforms to standards defined by directives 2001/58/CE Data sheet prepared by MOTUL.

IMPORTANT: The information in this Data Sheet applies only to the products designated herein and produced or supplied by us. It is based on our experience and on the data available to us at the time of its issue and is accurate to the best of our knowledge.

MOTUL

119, bd Félix Faure

B.P. 94

93303

Aubervilliers Cedex France

phone: 0033.1.48.11.70.00

fax: 0033.1.48.33.28.79 Email: alafeuil@motul.fr Page:

5/5