

10969 WHEATLANDS AVE, #A, SANTEE, CA 92071 CA (619) 449-5000

Page 1

MATERIAL SAFETY DATA SHEET

Froduct Code: Racing Shock Fluid - Light

HAZARD RATING

4 - Extreme N

- High

2 - Moderate

1 - Slight

- Insignificant

Toxicity

Fire Reactivity

Special

DIVISION AND LOCATION --- SECTION I

MAXIMA PRODUCTS

10969 Wheatland Ave., Suite A

92071 Santee, CA.

Emergency Telephone No:

(619) 449-5000

Transportation Emergency:

CHEMICAL AND PHYSICAL PROPERTIES---SECTION II

Chemical Name:

Petroleum Lubricating Oil

Formula:

Complex mixture. CAS not available

Hazardous Decompositon Products:

Fumes, smoke, carbon monoxide, sulfur oxides, aldehydes

compatability (Keep away from):

Liquid chlorine, concentrated oxygen, sodium hypochlorite, calcium hypochlorite Toxic and Hazardous Incredients:

none

faint petroleum hydrocarbon :mrc: Odor: liquid

Color: red Popearance: liquid

Specific Gravity (water=1): .86

IBP approximately 154°C (310°F) Boiling Point:

 -60° C (-76° F) Melting Point:

Solubility in Water (by weight %): neglibile; less than 0.1

Volatile (by weight %): neglibile from open container in 4 hrs. @ 38°C

less than 0.01 Evaporation Rate:

Vapor Pressure (mm Hg at 20°C): less than 0.01

Vapor Density (air=1): greater than 5

essentially neutral pH (as is):

Product is stable under normal conditions Stability:

Viscosity SUS at 100°F: 13.5 cSt @ 40°C

FIRE AND EXPLOSION DATA---SECTION III

Special Fire Fighting Procedures: Fire fighters should wear an approved self contained

breathing apparatus

Unusual Fire and Explosion Hazards:

none



10969 WHEATLANDS AVE, #A, SANTEE, CA 92071 CA (619) 449-5000

MATERIAL SAFETY DATA SHEET

coduct Code:

Racing Shock Fluid - Light

Page 2

(Section III Continued)

Flashpoint: (Method Used) Cleveland open cup greater than 204°C (400°F)

Flammable limits %: lower .09 upper 7%

Extinguishing agents:

Foam, water spray (fog), dry chemical, carbon dioxide vaporizing liquid.

HEALTH HAZARD DATA --- SECTION IV

Permissible concentrations (air): If used in application where mist may be generated, observe TWA/PEL mg/m3 for oil mist in area (OSNA).

Chronic effects of overexposure:

Prolonged skin contact may cause dermititus (skin irritation)

Acute toxicological properties:

no data available

Emergency First Aid procedures:

Eyes: Immediately flush for 15 minutes

Skin Contact: Remove excess with cloth or paper. Wash thoroughly with soap & water.

Inhalation: Remove exposed person to fresh air.

If Swallowed: DO NOT induce vomiting. Call a physician.

PECAIL PROTECTION INFORMATION --- SECTION V

Ventilation Type Required (Local, mechanical, special):

Local exhaust to capture vapor, mist or fume if necessary.

Respiratory Protection (Specify type):

Use supplied-air respiratory protection in confined or enclosed area.

Protective Gloves: chemical resistant gloves.

Eve Protection: chemical safety goggles.

Other Protective Equipment:

chemical resistant apron if necessary

HANDLING OF SPILLS OR LEAKS---SECTION VI

Procedures for Clean-Up: Transfer bulk of mixture into another container. Absorb residue with an inert material such as earth, sand, or vermiculite. Sweep up and dispose in accordance with local, state and federal regulations. Open all windows and doors. Keep product out of sewers and watercourses.

Waste Disposal:

Dispose of in accordance with all applicable federal, state and local regulations.

(Continued Next Page)



10969 WHEATLANDS AVE, #A, SANTEE, CA 92071 CA (619) 449-5000

MATERIAL SAFETY DATA SHEET

roduct Code: Racing Shock Fluid - Light

Page 3

SPECIAL PRECAUTIONSSECTION VII
Precautions to be taken in handling and storage: Keep containers and storage containers closed when not in use. Avoid prolonged or repeated contact with skin or breath
closed when not in use. Avoid prolonged or repeated contact with skin or breath
of-vapors. Use product with caution around heat, sparks, pilot lights, static
electricitý and open flame.
TRANSPORTATION DATASECTION VIII
D.O.T.: not applicable
Reportable Quantity: not applicable
Freight Classification: petroleum lubricating oil
Special Transportation Notes:
none
COMMENTS—SECTION IX
Signature: RICHARD D. LECHIEN Title: President te: evision Date: Supercedes:
Sent To: Date:

We believe the statements, technical information and recommendations contained herein are reliable, but they are given without warranty or guarantee of any kind, express or implied, and we assume no responsibility for any loss, damage, or expense, direct or consequential, arising out of their use.