

Printing date 12/18/2018

Reviewed on 12/20/2016

1 Identification

- · Product identifier
- Trade name: TOP SPEED 4T SAE 15W/50 JASO MA2
- · Application of the substance / the mixture Only for proper handling. Engine oil
- · Details of the supplier of the safety data sheet
- Manufacturer/Supplier:

BUCHER AG LANGENTHAL MOTOREX-Schmiertechnik Bern-Zürich-Strasse 31 CH-4901 Langenthal Telefon +41 (0)62 919 75 75

Lube-Tech Lubrication Technologies, Inc. 900 Mendelssohn Avenue North US-55427 Golden Valley, Minnesota Phone: 001 763 417 1357

- · Information department: msds@motorex.com
- · Emergency telephone number:

USA + Kanada: 1 800 424 9300 (Chemtrec Chemical Manufacturers Association, Arlington, VA 22209)

2 Hazard(s) identification

- Classification of the substance or mixture The product is not classified, according to the Globally Harmonized System (GHS).
- · Label elements
- · GHS label elements Void
- · Hazard pictograms Void
- · Signal word Void
- · Hazard statements Void
- · Classification system:
- · NFPA ratings (scale 0 4)



Health = 0Fire = 1Reactivity = 0

· HMIS-ratings (scale 0 - 4)



*0 Health = *0 Fire = 1

- · Other hazards
- · Results of PBT and vPvB assessment
- · PBT: Not applicable. · vPvB: Not applicable.

Printing date 12/18/2018

Reviewed on 12/20/2016

Trade name: TOP SPEED 4T SAE 15W/50 JASO MA2

(Contd. of page 1)

3 Composition/information on ingredients

- · Chemical characterization: Mixtures
- · Description: Mixture of the substances listed below with nonhazardous additions.
- · Dangerous components:

Mineral oils (mixture)

Asp. Tox. 1, H304

≥1-≤7.5%

· Additional information:

Note L: The classification as carcinogen does not apply because the mixture (or substance) contains less than 3% dimethyl sulfoxide extract (DMSO), measured according to IP 346.

4 First-aid measures

- · Description of first aid measures
- General information: No special measures required.
- · After inhalation: Supply fresh air; consult doctor in case of complaints.
- · After skin contact:

Remove residues with soap and water.

Remove contaminated clothing immediately.

· After eye contact:

Rinse opened eye for several minutes under running water.

Consult a physician if irritation develops.

· After swallowing:

Do not induce vomitting. Do not take in resorption stimulating agents.

Consult a physician who will decide on need and method of emptying the stomach.

- · Information for doctor:
- · Most important symptoms and effects, both acute and delayed No further relevant information available.
- · Indication of any immediate medical attention and special treatment needed No further relevant information available.

5 Fire-fighting measures

- · Extinguishing media
- Suitable extinguishing agents: Use fire fighting measures that suit the environment.
- Special hazards arising from the substance or mixture No further relevant information available.
- · Advice for firefighters
- · Protective equipment: No special measures required.

6 Accidental release measures

- · Personal precautions, protective equipment and emergency procedures Not required.
- · Environmental precautions: Do not allow to enter sewers/ surface or ground water.
- · Methods and material for containment and cleaning up:

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).

Reference to other sections

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

(Contd. on page 3)

Printing date 12/18/2018

Reviewed on 12/20/2016

. Protoctivo	Action Criteria for Chemicals	(Contd. of page 2
· Protective	Action Criteria for Chemicals	
1330-20-7	xylene	130 ppm
100-41-4	ethylbenzene	33 ppm
· PAC-2:		·
1330-20-7	xylene	920* ppm
100-41-4	ethylbenzene	1100* ppm
· PAC-3:		•
1330-20-7	xylene	2500* ppm
100-41-4	ethylbenzene	1800* ppm

7 Handling and storage

- · Handling:
- · Precautions for safe handling No special measures required.
- · Information about protection against explosions and fires: No special measures required.
- · Conditions for safe storage, including any incompatibilities
- · Storage:
- Requirements to be met by storerooms and receptacles: No special requirements.
- · Information about storage in one common storage facility: Not required.
- · Further information about storage conditions: None.
- · Storage class: 10
- · Specific end use(s) No further relevant information available.

8 Exposure controls/personal protection

- · Additional information about design of technical systems: No further data; see section 7.
- · Control parameters
- Components with limit values that require monitoring at the workplace:

The product does not contain any relevant quantities of materials with critical values that have to be monitored at the workplace.

- · Additional information: The lists that were valid during the creation were used as basis.
- · Exposure controls
- · Personal protective equipment:
- General protective and hygienic measures:

Keep away from foodstuffs, beverages and feed.

Wash hands before breaks and at the end of work.

Do not inhale gases / fumes / aerosols.

· Breathing equipment:

Not necessary if room is well-ventilated.

Respiratory protection if formation of aerosol or mist: use mask with filter type A2, A2/P2 or ABEK.

· Protection of hands:

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

(Contd. on page 4)

Printing date 12/18/2018

Reviewed on 12/20/2016

Trade name: TOP SPEED 4T SAE 15W/50 JASO MA2

(Contd. of page 3)

· Material of gloves

Protective gloves to EN374, resistant to oil in use. Standard EN 374 Level 3 control G1 The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer.

Fluorocarbon rubber (Viton)

Nitrile rubber, NBR

Recommended thickness of the material: ≥ 0.4 mm

· Penetration time of glove material

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

For the mixture of chemicals mentioned below the penetration time has to be at least 60 minutes (Permeation according to EN 374 Part 3: Level 1).

- Eye protection: Goggles recommended during refilling.
- · Body protection: Protective work clothing

Information on basic physical and	chemical properties
General Information Appearance:	
Form:	Fluid
Color:	Brown
Odor:	Characteristic
Odor threshold:	Not determined.
pH-value:	Not determined.
Change in condition	
Melting point/Melting range:	Undetermined.
Boiling point/Boiling range:	Undetermined.
Flash point:	>200 °C (>392 °F)
Flammability (solid, gaseous):	Not applicable.
Ignition temperature:	>260 °C (>500 °F) (DIN 51794)
Decomposition temperature:	Not determined.
Auto igniting:	Product is not selfigniting.
Danger of explosion:	Product does not present an explosion hazard
Explosion limits:	
Lower:	Not determined.
Upper:	Not determined.
Vapor pressure:	Not determined.
Density at 20 °C (68 °F):	0.86 g/cm³ (7.177 lbs/gal) (ASTM D 4052)
Relative density	Not determined.
Vapor density	Not determined.
Evaporation rate	Not determined.
Solubility in / Miscibility with	
Water:	Not miscible or difficult to mix.
Partition coefficient (n-octanol/wat	er): Not determined.

(Contd. on page 5)

Printing date 12/18/2018 Reviewed on 12/20/2016

Trade name: TOP SPEED 4T SAE 15W/50 JASO MA2

(Contd. of page 4)

Kinematic: 130 mm²/s @ 40 °C (266 °F)

VOC content: 0.00 %

Solids content: 0.0 %

Other information No further relevant information available.

10 Stability and reactivity

- · Reactivity No further relevant information available.
- · Chemical stability
- · Thermal decomposition / conditions to be avoided:

No decomposition if used according to specifications.

- · Possibility of hazardous reactions No dangerous reactions known.
- · Conditions to avoid No further relevant information available.
- · Incompatible materials: No further relevant information available.
- · Hazardous decomposition products: No dangerous decomposition products known.

11 Toxicological information

- · Information on toxicological effects
- · Acute toxicity:
- Primary irritant effect:
- · on the skin: No irritant effect.
- · on the eye: No irritating effect.
- · Sensitization: No sensitizing effects known.
- Additional toxicological information:

The product is not subject to classification according to internally approved calculation methods for preparations:

When used and handled according to specifications, the product does not have any harmful effects according to our experience and the information provided to us.

· Carcinogenic categories

· IARC (Inte	rnational Agency for Research on Cancer)	
1330-20-7	xylene	3
100-41-4	ethylbenzene	2B
· NTP (Natio	onal Toxicology Program)	
None of the	e ingredients is listed.	
· OSHA-Ca	(Occupational Safety & Health Administration)	
None of the	e ingredients is listed.	

12 Ecological information

- · Toxicity
- · Aquatic toxicity: No further relevant information available.
- Persistence and degradability No further relevant information available.
- Behavior in environmental systems:
- · Bioaccumulative potential No further relevant information available.
- · Mobility in soil No further relevant information available.

(Contd. on page 6)

Printing date 12/18/2018

Trade name: TOP SPEED 4T SAE 15W/50 JASO MA2

Reviewed on 12/20/2016

(Contd. of page 5)

- · Additional ecological information:
- · General notes:

Water hazard class 1 (according to Appendix 1 AwSV): slightly hazardous for water Do not allow undiluted product or large quantities of it to reach ground water, water course or sewage system.

- Results of PBT and vPvB assessment
- · PBT: Not applicable.
- · vPvB: Not applicable.
- · Other adverse effects No further relevant information available.

13 Disposal considerations

- · Waste treatment methods
- · Recommendation:

Must not be disposed of together with household garbage. Do not allow product to reach sewage system.

Contact waste processors for recycling information.

- · Uncleaned packagings:
- · Recommendation: Disposal must be made according to official regulations.

UN-Number DOT, ADR/RID/ADN, ADN, IMDG, IATA	Void
UN proper shipping name DOT, ADR/RID/ADN, ADN, IMDG, IATA	Void
Transport hazard class(es)	
DOT, ADR/RID/ADN, ADN, IMDG, IATA Class	Void
Packing group DOT, ADR/RID/ADN, IMDG, IATA	Void
Environmental hazards: Marine pollutant:	No
Special precautions for user	Not applicable.
Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code	f Not applicable.
UN "Model Regulation":	Void

15 Regulatory information

- · Safety, health and environmental regulations/legislation specific for the substance or mixture
- · Sara
- · Section 355 (extremely hazardous substances):

None of the ingredients is listed.

(Contd. on page 7)

Printing date 12/18/2018

Reviewed on 12/20/2016

Trade name: TOP SPEED 4T SAE 15W/50 JASO MA2

<u> </u>	(Contd. of pa
	(Specific toxic chemical listings):
	liphenylamine
1330-20-7 x	•
100-41-4	ethylbenzene
•	c Substances Control Act):
84605-29-8	Phosphorodithioic acid, mixed O,O-bis (1,3-diethylbutyl and iso-Pr)este zinc salts
	White mineral oil, petroleum
	diphenylamine
1330-20-7	•
	2-Naphthalenol,1-((4-(phenylazo)phenyl)azo)-,ar-heptylar,ar,Methylderivate
	ethylbenzene
104-75-6	2-ethylhexylamine
· TSCA new (21st Century Act) (Substances not listed)
Mineral oils	(mixture)
· Proposition	65
· Chemicals	known to cause cancer:
100-41-4 et	hylbenzene
· Chemicals	known to cause reproductive toxicity for females:
None of the	ingredients is listed.
· Chemicals	known to cause reproductive toxicity for males:
	ingredients is listed.
· Chemicals	known to cause developmental toxicity:
None of the	ingredients is listed.
· Carcinogen	ic categories
· EPA (Enviro	onmental Protection Agency)
1330-20-7 x	ylene
100-41-4 ε	thylbenzene
· TLV (Thresi	hold Limit Value established by ACGIH)
122-39-4	liphenylamine
1330-20-7 x	ylene
100-41-4 e	thylbenzene
	National Institute for Occupational Safety and Health)

16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

· Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

The classification of the mixture was carried out by calculation in accordance with the rules laid down in Annex I of Regulation (EC) No 1272/2008.

No special training instructions to ensure protection of human health and environment are required.

· Department issuing SDS: Abteilung Produktsicherheit

(Contd. on page 8)

Printing date 12/18/2018

Reviewed on 12/20/2016

Trade name: TOP SPEED 4T SAE 15W/50 JASO MA2

(Contd. of page 7)

· Date of preparation / last revision 12/18/2018 / -

· Abbreviations and acronyms:

ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

DOT: US Department of Transportation

IATA: International Air Transport Association ACGIH: American Conference of Governmental Industrial Hygienists

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

NFPA: National Fire Protection Association (USA) HMIS: Hazardous Materials Identification System (USA) VOC: Volatile Organic Compounds (USA, EU)

PBT: Persistent, Bioaccumulative and Toxic vPvB: very Persistent and very Bioaccumulative NIOSH: National Institute for Occupational Safety

OSHA: Occupational Safety & Health

TLV: Threshold Limit Value PEL: Permissible Exposure Limit REL: Recommended Exposure Limit Asp. Tox. 1: Aspiration hazard - Category 1