Trade name: Novus Plastic Polish #3 Product. No: 7080, 7081, 7082, 7085 Specification No: PC30 Page 1 of 11

Print date: 05OCT2011 Revision date: 05OCT2011

Section 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product Identifier

- 1.1.1 Trade name/designation: Novus Plastic Polish #3
- 1.2 Relevant identified uses of the substance or mixture and uses advised against
- 1.2.1 Relevant identified uses: Heavy Scratch Remover
- 1.3 Details of the supplier
- 1.3.1 Supplier: Novus, Inc
- 1.3.2 E-Mail: msds-info@novusglass.com
- 1.3.3 U.S. Address Novus, Inc. 12800 Highway 13 South, Suite 500 Savage, MN 55378
 1.3.4 European Address
- Novus Europe Zinkstraat 53A 4823 Breda AC The Netherlands
- 1.4
 Emergency Telephone Number

 U.S. Phone:
 1-800-424-9300

 1
 800-420

 8036 (Medical E

1-800-420-8036 (Medical Emergencies)

1-703-527-3887 (International Collect) ne: 011-31-76-5426000

European Phone: 011-31-76-542600

Section 2: Hazards identification

- 2.1 Classification of the substance or mixture:
- 2.1.1 Classification according to Regulation (EC) No 1272/2008
- 2.1.2 Classification according to 67/548/EEC or 1999/45/EC
 This product does not meet the classification of hazardous, as defined by the European Community Council Directive 67/548/EEC and subsequent Directives.
 EU Hazard Classification: Not Applicable
 EU Risk Phrases: Not Applicable
 EU Safety Phrases: Not Applicable
- 2.1.3 Additional information:
- 2.2 Label elements
- 2.2.1 Labeling according to Regulation (EC) No 1272/2008 Signal word: Caution! Hazard statements: Not Applicable Precautionary statements: Not Applicable
- 2.3 Other hazards Adverse human health effects and symptoms:

Trade name: Novus Plastic Polish #3 Product. No: 7080, 7081, 7082, 7085 Specification No: PC30 Page 2 of 11

Print date: 05OCT2011 Revision date: 05OCT2011

Inhalation: Inhalation is not anticipated to be a significant route of overexposure to this product. If mists or sprays of this product are inhaled, they may mildly irritate the nose and other tissues of the upper respiratory system. Symptoms are generally alleviated upon breathing fresh air. Contact with Skin or Eyes: Depending on the duration and concentration of overexposure, eye contact may cause tearing and redness. Skin contact may cause mild redness, discomfort, and irritation. Symptoms are

generally alleviated upon rinsing. Repeated skin contact may cause dermatitis (dry, red skin). Skin Absorption: The Dipropylene Glycol Methyl Ether component of this product can be absorbed through intact skin. Skin absorption is not anticipated to cause adverse effects.

Ingestion: Ingestion is not anticipated to be a likely route of exposure to this product. If this material is swallowed, it may cause headache, nausea, and vomiting.

Injection: Though not anticipated to be a likely route of occupational exposure, injection of this material (via puncture or laceration by a contaminated object) may cause local reddening, tissue swelling, and discomfort in addition to the wound.

Section 3: Composition/information on ingredients

3.1 Description of the mixture:

CAS No	EC No	%	Name	Classification according to
		[weight]		67/548/EEC
L	1	1.0-5.0	Proprietary Copolymer Dispersed in Isoparaffin	Not Applicable
34590-94-8	252-104-2	3.0-7.0	Dipropylene Glycol Methyl Ether	Not Applicable
66402-68-4	266-340-9	3.0-7.0	Calcined Kaolin Clay	Not Applicable
1344-28-1	215-691-6	7.0-13.0	Aluminum Oxide	Not Applicable
		Balance	Water and other components. Each of the other components is present in less than 1% concentration (or 0.1% concentration for potential carcinogens, reproductive toxins, respiratory tract sensitizers, and mutagens).	Not Applicable

Section 4: First Aid Measures

4.1 Description of first aid measures

4.1.1 General information:

Contaminated individuals should be taken for medical attention if they feel unwell or if adverse effects occur. Take copy of label and MSDS to physician or health professional with contaminated individual.

4.1.2 Eye contact: If this product enters the eyes, open contaminated individual's eyes while under gently running water. Use sufficient force to open evolide. Have contaminated individual "rell" eyes. Minimum fluching is for 15

sufficient force to open eyelids. Have contaminated individual "roll" eyes. Minimum flushing is for 15 minutes. Contaminated individual must seek medical attention.

4.1.3 Inhalation:

If this product is inhaled, remove contaminated individual to fresh air.

4.1.4 Skin contact:

If this material contaminates the skin, begin decontamination with running water. Recommended flushing is for 15 minutes if any sign of skin irritation develops. Contaminated individual should seek immediate medical attention if any adverse exposure symptoms develop.

4.1.5 Ingestion:

Trade name: Novus Plastic Polis	h #3
Product. No: 7080, 7081, 7082,	7085
Specification No: PC30	Page 3 of 11

Print date: 05OCT2011 Revision date: 05OCT2011

If this material is swallowed, Call Physician or Poison Control Center for most current information. Do not induce vomiting. Have victim rinse mouth thoroughly with water, if conscious. Never induce vomiting or give diluents (milk or water) to someone who is unconscious, having convulsions, or unable to swallow. Notes for the doctor:

4.1.6 Notes for the doctor: Treat sympotoms and eliminate overexposure.
4.2 Medical conditions aggravated by exposure: Dermatitis and other pre-existing skin disorders may be aggravated by prolonged overexposure to this

Section 5: Firefighting measures

5.1 Extinguishing media:

product.

- 5.1.1 Suitable extinguishing media:
 - Water spray, foam, halon, carbon dioxide, dry chemical, any "ABC" class
- 5.1.2 Unsuitable extinguishing media: No Data
- 5.2 Special hazards arising from the substance or mixture
- 5.2.1 Hazardous combustion products: When involved in a fire this material may decompose and produce irritating vapors and toxic gases (e.g. oxides of aluminum, silicon, and carbon).
- 5.3 Advice for fire-fighters: As with all chemical products, structural firefighters must wear Self-Contained Breathing Apparatus and full protective equipment when responding to fires involving this product. Move containers from fire area if it can be done without risk to personnel. If possible, prevent runoff water from entering storm drains, bodies of water, or other environmentally sensitive areas.

Section 6: Accidental release measures

- 6.1 Personal precautions, protective equipment and emergency procedures
- 6.1.1 For non-emergency personnel Protective equipment: Wear butyl rubber or nitrile rubber gloves for incidental releases
- 6.1.2 For emergency responders Personal protective equipment: Wear gloves, goggles, and appropriate body protection. An airpurifying respirator with an organic vapor cartridge must be worn during spill responses in which excessive vapors are generated or it the area of the release is poorly ventilated. In the event of a non-incidental or when the oxygen level is below 19.5% or is unknown, minimum Personal Protective Equipment should be Level B: triple-gloves, chemical resistant suit and boots, hard hat, and Self-Contained Breathing Apparatus.
- 6.2 Methods and material for containment and cleaning up

6.2.1 For containment:

Absorb spilled liquid with polypads or other suitable absorbent materials. Close off sewers and take other measures to protect human health and the environment, as necessary.

6.2.2 For cleaning up: Rinse area with water. Decontaminate the area thoroughly. Place all spill residue in an appropriate container and seal. Dispose of in accordance with applicable U.S. Federal, State, or local procedures or appropriate standards of Canada or EU Member States (see Section 13, Disposal Considerations).

Section 7: Handling and storage

7.1 Precautions for safe handling

Trade name: Novus Plastic Polish #3 Product. No: 7080, 7081, 7082, 7085 Specification No: PC30 Page 4 of 11

Print date: 05OCT2011 Revision date: 05OCT2011

- 7.1.1 Advice on general occupational hygiene
 As with all chemicals, avoid getting this product on you or in you. Wash thoroughly after using this
 material. Do not eat, smoke, apply cosmetics, or drink while handling this material. Avoid breathing
 vapors. Use in a well-ventilated location. Remove contaminated clothing immediately.
- 7.2 Conditions for safe storage, including any incompatibilities Store containers in a cool, dry location, away from direct sunlight, sources of intense heat, or where freezing is possible. Store away from incompatible materials (see Section 10, Stability and Reactivity). Material should be stored in secondary containers or in a diked area, as appropriate. Keep container tightly closed when not in use. Inspect all incoming containers before storage to ensure containers are properly labeled and not damaged. Storage class:
- 7.3 Specific end uses: Heavy Scratch Remover

Section 8: Exposure controls/personal protection

8.1 Control parameters

8.1.1 Occupational exposure limits:

Limit value type	Substance name	EC-No.	CAS-No	Limit value	Monitoring
(country of origin)		_			and
					observation
					processes
TWA (AU)	Aluminum	2115-691-6	1344-28-1	10 mg/m3	
MAK (AT)	Oxide			5 mg/m3	Dust
TWA (BE)				10 mg/m3	
TWA (DK)				10 mg/m3	
VME (FR)				10 mg/m3	
MAK (DE)				6 mg/m3	
TWA(NO)				2 mg/m3	
TWA(PL)				2 mg/m3	
STEL(PL)				16 mg/m3	
MAC-TGG (NLD)				10 mg/m3	
TWA (RU)				6 mg/m3	
TWA (SE)				4 mg/m3	Resp. Dust
TWA (SE)				10 mg/m3	Total dust
MAK-W (CH)				2 mg/m3	
TWA (UK)				10 mg/m3	Inhalable dust
TWA (UK)				4 mg/m3	Res. dust
TWA (AU)	Dipropylene	252-104-2	34590-94-8	100 ppm	Skin
STEL (AU)	Glycol Methyl			150 ppm	Skin
MAK (AT)	Ether			50 ppm	
TWA (BE)				100 ppm	Skin
STEL (BE)				150 ppm	Skin
TWA (DK)				50 ppm	Skin
TWA (FN)				100 ppm	
STEL (FN)				150 ppm	
VME (FR)				100 ppm	
MAK (DE)				50 ppm	Skin
MAC-TGG (NLD)				300 mg/m3	Skin

Trade name: Novus Plastic Polish #3 Product. No: 7080, 7081, 7082, 7085 Specification No: PC30 Page 5 of 11

Print date: 05OCT2011 Revision date: 05OCT2011

TWA (PH)		100 ppm	Skin
		100 ppm	JKIII GL I
TWA (SE)		50 ppm	Skin
STEL (SE)		75 ppm	Skin
MAK-W (CH)		50 ppm	
STEL (CH)		100 ppm	
TWA (TR)		300 ppm	Skin
TWA (UK)		50 ppm	Skin

Chemical	CAS #	Exposure Limits in Air							
Name		ACGIH – TLV OSHA-PEL NIOSH			Other				
		TWA	STEL	TWA	STEL	TWA	STEL	IDLH	
		Mg/m3	Mg/m3	Mg/m3	Mg/m	Mg/m3	Mg/m3	Mg/m3	Mg/m3
					3				
Aluminum Oxide	1344-28-1	10	NE	15 mg/m3	NE	NE	NE	NE	DFG MAK: $TWA = 1.5$
		mg/m3		(total dust);					mg/m3 (fume)
				5 mg/m3					[respirable fraction]
				(respirable					$PEAK = 8 \cdot MAK 15$
				fraction) 10					min, average value, 1-hr
				mg/m3					interval (fume)
				(total dust)					Carcinogen: MAK-2
				[Vacated					(fibrous dust), TLV-A4
				1989 PEL					
Calcined Kaolin	66402-68-	NE	NE	NE	NE	NE	NE	NE	NE
Clay	4								
Dipropylene Glycol	34590-94-	100	150	100 (Skin)	150	100	150	600	DFG MAK: TWA = 50
Methyl Ether	8	(Skin)	(Skin)		(Skin)				PEAK = 1•MAK 30 min,
Copolymer Disp	ersed in	NF	NF	NF	NF	NF	NF	NF	NF
Isoparaffi	n		112	112	TTL.	ILL.	TTL .		THE .
Water and other components. Each of		None of the	e other comp	onents of this proc	luct contrib	ute significar	it, additional.	hazards at th	e concentrations present in this
the other components is present in less		product. All pertinent hazard information has been provided in this document, per the requirements of the Federal							
than 1% concentration (or 0.1 %		Occupational Safety and Health Administration Standard (29 CFR 1910.1200), U.S. State equivalent Standards, Canadian							
concentration for potential carcinogens,		Workplace hazardous materials Identification System Standards (CPR 4) and European Community Standards							
reproductive toxins, respiratory tract		(Commission Directive 93/112/EEC).							
sensitizers, and mutagens).		l							

- 8.2 Exposure controls
- 8.2.1 Appropriate engineering controls:
 - None normally needed under typical circumstances of use. Local exhaust may be necessary under some usage and handling situations. Prudent practice is to ensure eyewash/safety shower stations are available near areas where this product is used. If necessary, refer to U.S. OSHA Standards, Canadian WHMIS Standards and EU Directives regarding ventilation standards.
- 8.2.2 Personal protective equipment:
- 8.2.2.1 Eye/Face protection:

Not normally needed during normal use. If necessary, refer to U.S. OSHA 29 CFR 1910.133, the European Standard CR 13464:1999 and the Canadian CSA Standard Z94.3-M1982, Industrial Eye and Face Protectors for further information.

8.2.2.2 Skin protection:

During patient administration, use of light-weight cotton gown or other medical attire is recommended. If necessary, refer to appropriate Standards of Canada or the European Standard CEN/TR 15419:2006 for other requirements. If a hazard of injury to the feet exists due to falling objects, rolling objects, where objects may pierce the soles of the feet or where employee's feet may be exposed to electrical hazards, use foot protection, as described in U.S. OSHA 29 CFR 1910.136 and the Canadian CSA Standard Z195-M1984, Protective Footwear.

Trade name: Novus Plastic Polish #3

Product. No: 7080, 7081, 7082, 7085 Specification No: PC30 Page 6 of 11 Print date: 05OCT2011 Revision date: 05OCT2011

For situations in which skin contact is anticipated, use gloves, including nitrile, or rubber gloves. Check gloves for leaks. Wash hands before putting on gloves and after removing gloves. If necessary, refer to U.S. OSHA 29 CFR 1910.138, the European Standard CEN/TR 15419:2006 and the appropriate Standards of Canada.

8.2.2.3 Respiratory protection:

None normally needed under typical circumstances of use. Maintain airborne contaminant concentrations below guidelines listed above if applicable. If respiratory protection is needed, use only protection authorized in the U.S. Federal OSHA Standard (29 CFR 1910.134), equivalent U.S. State standards, Canadian CSA Standard Z94.4-93, the European Standard EN 529:2005, and EU member states. Oxygen levels below 19.5% are considered IDLH by OSHA. In such atmospheres, use of a full-facepiece pressure/demand SCBA or a full facepiece, supplied air respirator with auxiliary self-contained air supply is required under OSHA's Respiratory Protection Standard (1910.134-1998).

Section 9: Physical and Chemical Properties

9.1 Information on basic physical and chemical properties 9.1.1 Appearance Physical state: Liquid Color: Opaque white Odor: Mild lemon odor Odor threshold: 9.1.2 Safety relevant basic data pH (20 °C): Not Established Melting point/range(°C): Not Established Initial boiling point/range (°C): Not Established Decomposition temperature (°C): Not Established Flash point (°C): > 93CIgnition temperature (°C): Not Established Vapor pressure (mm Hg) at 50°C: Not Established Vapor density (air = 1): Not Established Density (g/cm3)at °C: Not Established Bulk density (kg/m3): Not Established Water solubility (20°C in g/l): Soluble Solubility(ies): Not Established Partition coefficient: Not Established N-Octanol/Water (log Po/w): Not Established Viscosity, dynamic (mPa s): Not Established 9.1.3 Physical hazards: Flammable Liquid 9.2 Other safety information: Properties of explosive atmospheres (mixtures): Gases and vapors: Not Established **Dusts:** Not Established Physical chemical properties of nanoparticles: Not Established Limiting oxygen concentration: Not Established Bulk density: Not Established Solubility in different media: Not Established Stability in organic solvents and identity of relevant degradation products: Not Established Evaporation rate: Not Established Conductivity: Not Established Surface tension: Not Established

Trade name: Novus Plastic Polish #3 Product. No: 7080, 7081, 7082, 7085 Specification No: PC30 Page 7 of 11

Print date: 05OCT2011 Revision date: 05OCT2011

Dissociation constant in water (pKa): Not Established Oxidation-reduction Potential: Not Established Fat solubility (solvent – oil to be specified): Not Established Critical temperature: Not Established

Section 10: Stability and reactivity

10.1	Reactivity:
10.1	Reactivity.
	Not Established
10.2	Chemical stability:
	Stable
10.3	Possibility of hazardous Polymerization
	Will not occur
10.4	Conditions to avoid:
	Contact with or exposure to incompatible chemicals
10.5	Incompatible materials:
	Strong oxidizers, water-reactive materials
10.6	Hazardous decomposition products:

The products of thermal decomposition of this material include irritating vapors and toxic gases (e.g. oxides of aluminum, silicon, and carbon).

Section 11: Toxicological Information						
11.1 Information on toxicologica	l effects:					
Aluminum Oxide	Effect dose /	Species	Method	Time		
	Concentration					
Acute inhalative toxicity (gas)	200 mg/m3	Rabbit	TCLo	5 hours/28 weeks-		
				intermittent		

Dipropylene Glycol Methyl Ether	Effect dose /	Species	Method	Time
	Concentration			
Acute oral toxicity	5.5 mL/kg	Rat	LD50	
Acute dermal toxicity	10 mL/kg	Rabbit	LD50	
Acute inhalative toxicity (gas)	2000 mg/m3	Rat	TCLo	7 hours/26 weeks-
				intermittent

Calcined Kaolin Clay: Currently there are not toxicological data available for this compound. Copolymer: Currently, there are not toxicological data available for this compound.

11.2 Other information:

IRRITANCY OF PRODUCT: This product may mildly irritate contaminated eyes, skin, and mucous membranes. SENSITIZATION TO THE PRODUCT: The components of this product are not known to be skin or respiratory sensitizers. REPRODUCTIVE TOXICITY INFORMATION: Listed below is information concerning the effects of this product and its components on the human reproductive system.

Mutagenicity: The components of this product are not reported to produce mutagenic effects in humans. Embryotoxicity: The components of this product are not reported to produce embryotoxic effects in humans. Teratogenicity: The components of this product are not reported to cause teratogenic effects in humans. Reproductive Toxicity: The components of this product are not reported to cause reproductive effects in humans. A mutagen is a chemical that causes permanent changes to genetic material (DNA) such that the changes will propagate through generational lines. An embryotoxin is a chemical that causes damage to a developing embryo (i.e. within the first eight weeks of pregnancy in humans), but the damage does not propagate across generational lines. A

SUSPECTED CANCER AGENT: The components of this product are listed by agencies tracking potential carcinogenic effects, as follows: ALUMINUM OXIDE: MAK-2 Compound (Substances which are considered to be carcinogenic) Fibrous forms only; ACGIH-TLV-A4 Compound (Not Classifiable as a Human Carcinogen). The remaining components of this product are not found on the following lists: U.S. FEDERAL OSHA Z LIST, NTP, IARC, and CAL/OSHA and therefore are neither considered to be nor suspected to be cancer-causing agents by these agencies.

Trade name: Novus Plastic Polish #3 Product. No: 7080, 7081, 7082, 7085 Specification No: PC30 Page 8 of 11

Print date: 05OCT2011 Revision date: 05OCT2011

teratogen is a chemical that causes damage to a developing fetus, but the damage does not propagate across generational lines. A
SYNERGISTIC PRODUCTS: Not applicable.
BIOLOGICAL EXPOSURES INDICES (BEIs): Currently, there are no BEIs determined for any component of this product.
Section 12: Ecological information
12.1 Toxicity:
Environmental Stability:
The components of this product are relatively stable under ambient environmental conditions. Additional
environmental data for components of this product are available as follows:
Dipropylene Glycol Methyl Ether:
Solubility: Miscible with water.
Biodegradation: Five-, ten-, and twenty-day BOD values for Dipropylene Glycol Monomethyl
Ether were reported as 0, 0, and 31%, respectively (expressed as percentage of theoretical oxygen
demand). The type of inoculum, however, was not specified. This delayed oxygen demand
suggests that an acclimation period is required in order for a Dipropylene Glycol Monomethyl
Ether –degrading population to become established. Thus, intermittent releases of Dipropylene
Glycol monomethyl Ether to the environment or to wastewater treatment plants may also require
an acclimation period before significant amounts of Dipropylene Glycol Monomethyl Ether are
removed. No information was found on the biodegradation of Dipropylene Glycol Monomethyl
Ether in soil or natural waters.
Bioconcentration: Because Dipropylene Glycol Monomethyl Ether is infinitely soluble in water, it
will not be expected to bioconcentrate in aquatic organisms.
Effect of Material on Plants or Animals:
This product may be harmful or fatal to contaminated plant and animal-life (especially if large quantities
are released).
Aquatic toxicity:
This product may be harmful or fatal to contaminated aquatic plant and animal life.
Section 13: Disposal considerations

- 13.1 Waste treatment methods
- 13.1.1 Product/packaging disposal:

Waste disposal must be in accordance with appropriate U.S. Federal, State, and local regulations or with regulations of Canada or EU Member States. This product, if unaltered by use, may be disposed of by treatment at a permitted facility or as advised by yout local waste regulatory authority. Empty containers as defined by appropriate sections of RCRA, are not RCRA hazardous wastes. Insure proper management of any residuals remaining in containers.

- 13.1.2 Waste codes/waste designations according to EWC/AVV:
- 13.1.3 U.S. EPA Waste Number: Not applicable to wastes consisting of only this product.

Section 14: Transport Information

 14.1 Land transport (CFR 49: DOT) This product is not hazardous as defined by 49CFR 172.101 by the U.S. Department of Transportation UN-No: Not Applicable Proper shipping name: Not Regulated Class(es): Not Applicable Classification Code: Not Applicable Packing group: Not Applicable Hazard label(s) Not Applicable

Trade name: Novus Plastic Polish #3 Product. No: 7080, 7081, 7082, 7085 Specification No: PC30 Page 9 of 11

Print date: 05OCT2011 Revision date: 05OCT2011

Special provision(s): Not Applicable

14.2 Land transport (ADR/RID/GGVSE): This product is not classified by the United Nations Economic Commission for Europe to be dangerous goods. UN-No: Not Applicable Proper shipping name: Not Regulated Class(es): Not Applicable Classification Code: Not Applicable Packing group: Not Applicable Hazard label(s): Not Applicable Special provision(s): Not Applicable

 14.3 Sea transport (IMDG-Code/GGVSee): This product is not classified as dangerous goods by the IMO UN No: Not Applicable Proper shipping name: Not Regulated Class(es): Not Applicable Packing group: Not Applicable Marine Pollutant: Not Applicable Special provision(s): Not Applicable

 14.4 Air transport (ICAO-IATA/DGR): This product is not classified as dangerous goods by the International Air Transport Association (IATA) or the ICAO UN No: Not Applicable Proper shipping name: Not Regulated Class(es): Not Applicable Packing group: Not Applicable Special provision(s): Not Applicable

Section 15: Regulatory Information

- 15.1 Safety, health and environmental regulations/legislation specific for the mixture
- 15.1.1 National regulations(U.S.):

U.S. SARA REPORTING REQUIREMENTS: The components of this product are not subject to the reporting requirements of Sections 302, 304, and 313 of Title III of the Superfund Amendments and Reauthorization Act.

U.S. SARA THRESHOLD PLANNING QUANTITY: There are no specific Threshold Planning Quantities for this product. The default Federal MSDS submission and inventory requirement filing threshold of 10,000 lb (4,540 kg) may apply, per 40 CFR 370.20.

U.S. CERCLA REPORTABLE QUANTITY (RQ): Not applicable.

U.S. TSCA INVENTORY STATUS: The components of this product listed by CAS # in Section 2 (Composition and Information on Ingredients) are listed on the TSCA Inventory. Dipropylene Glycol Methyl Ether, a component of this product, is subject to a TSCA Section 4(a) Test Rule (69 Fed Reg 22,204 – April 26, 2004) for in vitro dermal absorption rate testing.

OTHER U.S. FEDERAL REGULATIONS: Not applicable.

CALIFORNIA SAFE DRINKING WATER AND TOXIC ENFORCEMENT ACT (PROPOSITION 65): No component of this product is on the California Proposition 65 lists.

U.S. ANSI STANDARD LABELING (Z129.1): CAUTION! MAY CAUSE SKIN AND EYE IRRITATION. Do not taste or swallow. Do not get on skin or in eyes. Avoid breathing sprays or mists.

Trade name: Novus Plastic Polish #3 Product. No: 7080, 7081, 7082, 7085 Specification No: PC30 Page 10 of 11 05OCT2011

Print date: 05OCT2011 Revision date:

Keep container closed. Use only with adequate ventilation. Wash thoroughly after handling. Wear gloves and eye protection.
FIRST-AID: In case of contact, immediately flush skin or eyes with plenty of water for at least 15 minutes. If inhaled, remove to fresh air. If ingested, do not induce vomiting and get medical attention. Get medical attention if any adverse reaction occurs.
IN CASE OF FIRE: Use water fog, dry chemical, CO2, or "alcohol" foam.
IN CASE OF SPILL: Absorb spill with inert material and place in suitable container. Consult Material Safety Data Sheet for additional information.

15.1.2 National regulations(Canada):

CANADIAN DSL INVENTORY: The components of this product listed by CAS # in Section 2 (Composition and Information on Ingredients) are listed on the DSL Inventory. CANADIAN WHMIS IDL DISCLOSURE STATUS: The Dipropylene Glycol Methyl Ether component of this product has a 1% disclosure requirement level. OTHER CANADIAN REGULATIONS: Not applicable. CANADIAN ENVIRONMENTAL PROTECTION AGENCY (CEPA) PRIORITY SUBSTANCES LISTS: The Aluminum Oxide component is on the National Pollutant Release Inventory (NPRI) substance for 2006, but only in fibrous form. CANADIAN WHMIS CLASSIFICATION and SYMBOLS: Not applicable.

15.1.3 National regulations(European Community):

EU LABELING AND CLASSIFICATION: This product does not meet the definition of any hazard classes as defined by the European Community Council Directive 67/548/EEC.

EU CLASSIFICATION: Not applicable.

EU RISK PHRASES: Not applicable.

EU SAFETY PHRASES: Not applicable.

EUROPEAN COMMUNITY ANNEX II HAZARD SYMBOLS: Not applicable.

EU INFORMATION FOR COMPONENTS:

Aluminum Oxide: EU EINECS/ELINCS NUMBER: 215-691-6. EU CLASSIFICATION: An official classification for this substance has not been published in Commission Directives 93/72/EEC or 94/69EC. Calcined Kaolin Clay: EU EINECS/ELINCS NUMBER: 266-340-9 EU CLASSIFICATION: An official classification for this substance has not been published in Commission Directives 93/72/EEC or 94/69EC. Copolymer: EU EINECS/ELINCS NUMBER: Not established. EU CLASSIFICATION: An official classification for this substance has not been published in Commission Directives 93/72/EEC or 94/69EC. Dipropylene Glycol Methyl Ether: EU EINECS/ELINCS NUMBER: 252-104-2 EU CLASSIFICATION: An official classification for this substance has not been published in Commission Directives 93/72/EEC or 94/69EC. Dipropylene Glycol Methyl Ether: EU EINECS/ELINCS NUMBER: 252-104-2 EU CLASSIFICATION: An official classification for this substance has not been published in Commission Directives 93/72/EEC or 94/69EC.

15.1.4 National regulations(Denmark):

NEUROTOXIC SUBSTANCES IN THE WORKING ENVIRONMENT: No component of this product is listed as a Neurotoxic Substance in the Working Environment in Denmark. REPRODUCTIVE TOXICANTS IN THE WORKING ENVIRONMENT: No component of this product is listed as a Reproductive Toxicant in the Working Environment in Denmark.

 15.2 INTERNATIONAL CHEMICAL INVENTORY LISTING FOR COMPONENTS: EUROPEAN EINECS: The following components are on the EINECS Inventory: ALUMINUM OXIDE: EINECS #: 215-691-5; CALCINED KAOLIN CLAY: EINCES # 266-340-9; DIPROPYLENE GLYCOL METHYL ETHER: EINECS # 252-104-2; JAPANESE ENCS: The following components are on the ENCS Inventory: ALUMINUM OXIDE:: ENCS # 1-23, DIPROPYLENE GLYCOL METHYL ETHER: ENCS # 2-426X

Trade name: Novus Plastic Polish #3 Product. No: 7080, 7081, 7082, 7085 Specification No: PC30 Page 11 of 11 05OCT2011

Print date: 05OCT2011 Revision date:

KOREAN KECI: The following components are on the ECL Inventory: ALUMINUM OXIDE: ECL Serial # KE-01012, CALCINED KAOLIN CLAY: ECL Serial # KE-05377, DIPROPYLENE GLYCOL METHYL ETHER: EINECS: ECL Serial # KE-12230 SWISS GIFTLISTE 1: The following components are on the SWISS Giftliste: ALUMINUM OXIDE: List of Toxic Substances 1, # G-7734, DIPROPYLENE GLYCOL METHYL ETHER: List of Toxic Substances 1, Toxic Category 5, Swiss # G-1590

U.S. TSCA INVENTORY: All components are on the TSCA Inventory.

Section 16: Other Information

The information contained herein is based on data considered accurate. However, no warranty is expressed or implied regarding the accuracy of these data or the results to be obtained from the use thereof. Novus, Inc assumes no responsibility for injury to the vendee or third persons proximately caused by the material if reasonable safety procedures are not adhered to as stipulated in the data sheet. Additionally, Novus, Inc assumes no responsibility for injury to vendee or third persons proximately caused by abnormal use of the material even if reasonable safety procedures are followed. Furthermore, vendee assumes the risk in his use of the material.

