



SAFETY DATA SHEET

SECTION 1 : IDENTIFICATION OF THE SUBSTANCE/MIXTURE AND OF THE COMPANY/UNDERTAKING

1.1. Product identifier

Product name : FORK OIL FL V L 2.5W 6X1L

Product code : 31900northamerica

1.2. Relevant identified uses of the substance or mixture and uses advised against

Fluid for fork

1.3. Details of the supplier of the safety data sheet

Registered company name : MOTUL.

Address : 119 BOULEVARD FELIX FAURE.93300.AUBERVILLIERS CEDEX.FRANCE.

Telephone : +33 (0)1.48.11.70.00. Fax : +33 (0)1.48.33.28.79.

Email: motul_hse@motul.fr

1.4. Emergency telephone number : +44 (0) 1235 239 670.

Association/Organisation : .

Other emergency numbers

UNITED STATES AND CANADA : 001 866 928 0789

BRAZIL : +55 11 3197 5891

MEXICO : +52 55 5004 8763

CHILE : +562 2582 9336

SECTION 2 : HAZARDS IDENTIFICATION

2.1. Classification of the substance or mixture

HCS compliant.

Aspiration hazard, Category 1 (Asp. Tox. 1).

2.2. Label elements

HCS compliant.

Hazard pictograms :



GHS08

Signal Word :

DANGER

Product identifiers :

CAS 72623-87-1 LUBRICATING OILS (PETROLEUM), C20-50, HYDROTREATED NEUTRAL OIL-BASED

Hazard statements :

H304 May be fatal if swallowed and enters airways.

Precautionary statements - General :

P101 If medical advice is needed, have product container or label at hand.

P102 Keep out of reach of children.

Precautionary statements - Response :

P301 + P310 IF SWALLOWED: Immediately call a POISON CENTER/doctor.

P331 Do NOT induce vomiting.

Precautionary statements - Disposal :

P501 Dispose of contents/container in accordance with local/regional/national/international regulations.

2.3. Other hazards

No data available.

SECTION 3 : COMPOSITION/INFORMATION ON INGREDIENTS**3.2. Mixtures****Composition :**

Identification	HCS	Nota	%
CAS: 72623-87-1 EC: 276-738-4 REACH: 01-2119474889-13-XXXX LUBRICATING OILS (PETROLEUM), C20-50, HYDROTREATED NEUTRAL OIL-BASED	GHS08 Dgr Asp. Tox. 1, H304 Carc. 1A, H350	[2]	50 <= x % < 100
CAS: 72623-87-1 EC: 276-738-4 REACH: 01-2119474889-13 LUBRICATING OILS (PETROLEUM), C20-50, HYDROTREATED NEUTRAL OIL-BASED	GHS08 Dgr Asp. Tox. 1, H304 Carc. 1A, H350	[2]	25 <= x % < 50

Information on ingredients :

[2] Carcinogenic, mutagenic or reprotoxic (CMR) substance.

SECTION 4 : FIRST AID MEASURES

As a general rule, in case of doubt or if symptoms persist, always call a doctor.
NEVER induce swallowing by an unconscious person.

4.1. Description of first aid measures**In the event of exposure by inhalation :**

Remove the victim to fresh air. If the symptoms persist, call a physician.

In the event of splashes or contact with eyes :

Wash immediately and abundantly with water, including under the eyelids.

In the event of splashes or contact with skin :

Immediately remove all soiled clothing.

Wash immediately and abundantly with soap and water.

In the event of swallowing :

Do not give the patient anything orally.

Seek medical attention, showing the label.

If swallowed accidentally, do not allow to drink, do not induce vomiting and transfer to hospital immediately by ambulance. Show the label to the doctor.

4.2. Most important symptoms and effects, both acute and delayed

No data available.

4.3. Indication of any immediate medical attention and special treatment needed

No data available.

SECTION 5 : FIREFIGHTING MEASURES

Non-flammable.

5.1. Extinguishing media**Suitable methods of extinction**

Dry agent, foam, carbon dioxide.

Unsuitable methods of extinction

High volume water jet

5.2. Special hazards arising from the substance or mixture

A fire will often produce a thick black smoke. Exposure to decomposition products may be hazardous to health.

Do not breathe in smoke.

In the event of a fire, the following may be formed :

- carbon monoxide (CO)

- carbon dioxide (CO₂)

5.3. Advice for firefighters

No data available.

SECTION 6 : ACCIDENTAL RELEASE MEASURES

6.1. Personal precautions, protective equipment and emergency procedures

Consult the safety measures listed under headings 7 and 8.
Spilled product may make surfaces slippery.

For first aid worker

First aid workers will be equipped with suitable personal protective equipment (See section 8).

6.2. Environmental precautions

Contain and control the leaks or spills with non-combustible absorbent materials such as sand, earth, vermiculite, diatomaceous earth in drums for waste disposal.
Prevent any material from entering drains or waterways.

6.3. Methods and material for containment and cleaning up

Clean preferably with a detergent, do not use solvents.

6.4. Reference to other sections

No data available.

SECTION 7 : HANDLING AND STORAGE

Requirements relating to storage premises apply to all facilities where the mixture is handled.

7.1. Precautions for safe handling

Always wash hands after handling.
Remove and wash contaminated clothing before re-using.
Avoid contact with eyes.

Fire prevention :

Never inhale this mixture.
Prevent access by unauthorised personnel.
Take precautionary measures against static discharges by bonding and grounding equipment.
No smoking.

Recommended equipment and procedures :

For personal protection, see section 8.
Observe precautions stated on label and also industrial safety regulations.
Ensure good ventilation at the workplace

Prohibited equipment and procedures :

No smoking, eating or drinking in areas where the mixture is used.
Do not breathe fumes, vapour, spray.

7.2. Conditions for safe storage, including any incompatibilities

Store between 5°C and 40°C in a dry, well ventilated place.
Only use hydrocarbon-resistant containers, joints and pipes.

Storage

Keep out of reach of children.
Keep away from food and drink, including those for animals.

Packaging

Always keep in packaging made of an identical material to the original.

7.3. Specific end use(s)

No data available.

SECTION 8 : EXPOSURE CONTROLS/PERSONAL PROTECTION

8.1. Control parameters

No data available.

Derived no effect level (DNEL) or derived minimum effect level (DMEL):

LUBRICATING OILS (PETROLEUM), C20-50, HYDROTREATED NEUTRAL OIL-BASED (CAS: 72623-87-1)

Final use:	Workers.
Exposure method:	Inhalation.
Potential health effects:	Long term local effects.
DNEL :	5.4 mg de substance/m3

Final use:	Consumers.
Exposure method:	Inhalation.

Potential health effects: Long term local effects.
DNEL : 1.2 mg de substance/m3

LUBRICATING OILS (PETROLEUM), C20-50, HYDROTREATED NEUTRAL OIL-BASED (CAS: 72623-87-1)

Final use: **Workers.**
Exposure method: Inhalation.
Potential health effects: Long term local effects.
DNEL : 5.4 mg de substance/m3

Final use: **Consumers.**
Exposure method: Inhalation.
Potential health effects: Long term local effects.
DNEL : 1.2 mg de substance/m3

8.2. Exposure controls

Appropriate engineering controls

Ensure adequate ventilation, if possible with extractor fans at work posts and appropriate general extraction.
Personnel shall wear regularly laundered overalls.

Personal protection measures, such as personal protective equipment

Pictogram(s) indicating the obligation of wearing personal protective equipment (PPE) :



Use personal protective equipment that is clean and has been properly maintained.
Store personal protective equipment in a clean place, away from the work area.
Never eat, drink or smoke during use. Remove and wash contaminated clothing before re-using. Ensure that there is adequate ventilation, especially in confined areas.

- Eye / face protection

Avoid contact with eyes.
Use eye protectors designed to protect against liquid splashes
Before handling, wear safety goggles in accordance with standard EN166.

- Hand protection

Use suitable protective gloves that are resistant to chemical agents in accordance with standard EN374.
Gloves must be selected according to the application and duration of use at the workstation.
Protective gloves need to be selected according to their suitability for the workstation in question : other chemical products that may be handled, necessary physical protections (cutting, pricking, heat protection), level of dexterity required.
Type of gloves recommended :
- Nitrile rubber (butadiene-acrylonitrile copolymer rubber (NBR))
Recommended properties :
- Impervious gloves in accordance with standard EN374

- Body protection

Work clothing worn by personnel shall be laundered regularly.
After contact with the product, all parts of the body that have been soiled must be washed.

- Respiratory protection

Breathing apparatus only when aerosol or spray are formed.

SECTION 9 : PHYSICAL AND CHEMICAL PROPERTIES

9.1. Information on basic physical and chemical properties

General information :

Physical state :	Fluid liquid.
Color:	Amber

Important health, safety and environmental information

pH :	Not relevant.
Flash Point Interval :	FP > 100°C (212 °F)
Vapour pressure (50°C) :	Not relevant.
Density :	< 1
Water solubility :	Insoluble.
Viscosity :	15 mm²/s à 40°C

Viscosity : 14 mm²/s < v <= 20,5 mm²/s (40°C)

9.2. Other information

No data available.

SECTION 10 : STABILITY AND REACTIVITY

10.1. Reactivity

No data available.

10.2. Chemical stability

This mixture is stable under the recommended handling and storage conditions in section 7.

10.3. Possibility of hazardous reactions

No data available.

10.4. Conditions to avoid

Keep away from heat and from sources of ignition

10.5. Incompatible materials

Strong oxidants

10.6. Hazardous decomposition products

The thermal decomposition may release/form :

- carbon monoxide (CO)
- carbon dioxide (CO₂)

SECTION 11 : TOXICOLOGICAL INFORMATION

11.1. Information on toxicological effects

Aspiration toxicity includes severe acute effects such as chemical pneumonia, varying degrees of pulmonary injury or death following aspiration.

11.1.1. Substances

No toxicological data available for the substances.

Acute toxicity :

LUBRICATING OILS (PETROLEUM), C20-50, HYDROTREATED NEUTRAL OIL-BASED (CAS: 72623-87-1)

Oral route : LD50 > 5000 mg/kg
Species : Rat
OCDE Ligne directrice 401 (Toxicité aiguë par voie orale)

Dermal route : LD50 > 2000 mg/kg
Species : Rabbit
OCDE Ligne directrice 402 (Toxicité aiguë par voie cutanée)

Inhalation route (Dusts/mist) : LC50 > 5.53 mg/l
Species : Rat
OCDE Ligne directrice 403 (Toxicité aiguë par inhalation)

11.1.2. Mixture

Skin corrosion/skin irritation :

Repeated or prolonged contact with the preparation may cause removal of natural fat from the skin resulting in non allergic contact dermatitis and absorption through the skin.

Serious damage to eyes/eye irritation :

Mild eye irritation

Aspiration hazard :

May be fatal if swallowed and enters airways.

Aspiration toxicity includes severe acute effects such as chemical pneumonia, varying degrees of pulmonary injury or death following aspiration.

SECTION 12 : ECOLOGICAL INFORMATION

The product must not be allowed to run into drains or waterways.

12.1. Toxicity

12.1.1. Substances

LUBRICATING OILS (PETROLEUM), C20-50, HYDROTREATED NEUTRAL OIL-BASED (CAS: 72623-87-1)

Fish toxicity : LC50 > 100 mg/l
Duration of exposure : 96 h
OCDE Ligne directrice 203 (Poisson, essai de toxicité aiguë)

NOEC >= 1000 mg/l
Species : Oncorhynchus mykiss
Duration of exposure : 14 jours

Crustacean toxicity :

EC50 > 10000 mg/l
Duration of exposure : 48 h
OCDE Ligne directrice 202 (Daphnia sp., essai d'immobilisation immédiate)

NOEC = 10 mg/l
Species : Daphnia magna
Duration of exposure : 21 jours

Algae toxicity :

ECr50 > 100 mg/l
Duration of exposure : 72 h
OCDE Ligne directrice 201 (Algues, Essai d'inhibition de la croissance)

12.1.2. Mixtures

Fish toxicity :

Harmful.
10 < LC50 <= 100 mg/l

12.2. Persistence and degradability

12.2.1. Substances

LUBRICATING OILS (PETROLEUM), C20-50, HYDROTREATED NEUTRAL OIL-BASED (CAS: 72623-87-1)
Biodegradability : Non-rapidly degradable.

12.2.2. Mixtures

Biodegradability : no degradability data is available, the substance is considered as not degrading quickly.

12.3. Bioaccumulative potential

No data available.

12.3.1. Substances

LUBRICATING OILS (PETROLEUM), C20-50, HYDROTREATED NEUTRAL OIL-BASED (CAS: 72623-87-1)
Octanol/water partition coefficient : log K_{ow} > 6

12.4. Mobility in soil

Not very mobile in soil.
The product is insoluble in water and will spread on the surface

12.5. Results of PBT and vPvB assessment

No data available.

12.6. Other adverse effects

Do not dispose of the product in the natural environment, effluents or surface waters.

SECTION 13 : DISPOSAL CONSIDERATIONS

The appropriate waste management of the mixture and/or its container must be determined in accordance with local regulations.

13.1. Waste treatment methods

Do not pour into drains or waterways.

Waste :

Waste management is carried out without endangering human health, without harming the environment and, in particular without risk to water, air, soil, plants or animals.
Recycle or dispose of waste in compliance with current legislation, preferably via a certified collector or company.
Do not contaminate the ground or water with waste, do not dispose of waste into the environment.

Soiled packaging :

Empty container completely. Keep label(s) on container.
Give to a certified disposal contractor.

SECTION 14 : TRANSPORT INFORMATION

Exempt from transport classification and labelling.

14.1. UN number

-

14.2. UN proper shipping name

-

14.3. Transport hazard class(es)

-

14.4. Packing group

-

14.5. Environmental hazards

-

14.6. Special precautions for user

-

SECTION 15 : REGULATORY INFORMATION

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

The following regulations have been used:

- OSHA Hazard Communication Standard 29 CFR 1910.1200

- Container information:


No data available.

- Particular provisions :

No data available.

- Standardised American system for the identification of hazards presented by the product in view of emergency procedures (NFPA 704) :

NFPA 704, Labelling: Health=0 Inflammability=1 Instability/Reactivity=1 Specific Risk=none



- Clean Water Act : Toxic Pollutants (CWA 307A)

Unlisted.

- Clean Water Act : Hazardous Substances (CWA 311)

Unlisted.

- Clean Water Act : Hazardous Substances (CWA 304b)

Unlisted.

- Clean Water Act : Priority Pollutants (CWA Priority)

Unlisted.

- Clean Air Act : Hazardous Air Pollutants (CAA 112(b) HAP (188))

Unlisted.

- Clean Air Act : Organic Hazardous Air Pollutants National Emission Standards (CAA 112(b) HON (387))

Unlisted.

- Clean Air Act : Protection of Stratospheric Ozone (CAA 602)

Unlisted.

- SARA 110

Unlisted.

- SARA 302/304

Unlisted.

- SARA 313

Unlisted.

- California proposition 65 : Chemicals known to the state to cause cancer or reproductive toxicity

Unlisted.

- Massachusetts : Right to Know

Unlisted.

- New Jersey : Right to Know

Unlisted.

- Pennsylvania : Hazardous Substance

Unlisted.

- Rhode Island : Hazardous substance list

Unlisted.

72623-87-1

LUBRICATING OILS (PETROLEUM), C20-50, HYDROTREATED NEUTRAL OIL-BASED

72623-87-1

LUBRICATING OILS (PETROLEUM), C20-50, HYDROTREATED NEUTRAL OIL-BASED

15.2. Chemical safety assessment

No data available.

SECTION 16 : OTHER INFORMATION

Since the user's working conditions are not known by us, the information supplied on this safety data sheet is based on our current level of knowledge and on national and community regulations.

The mixture must not be used for other uses than those specified in section 1 without having first obtained written handling instructions.

It is at all times the responsibility of the user to take all necessary measures to comply with legal requirements and local regulations.

The information in this safety data sheet must be regarded as a description of the safety requirements relating to the mixture and not as a guarantee of the properties thereof.

Wording of the phrases mentioned in section 3 :

H304	May be fatal if swallowed and enters airways.
H350	May cause cancer .

Abbreviations :

DNEL : Derived No-Effect Level

CMR: Carcinogenic, mutagenic or reprotoxic.

ADR : European agreement concerning the international carriage of dangerous goods by Road.

IMDG : International Maritime Dangerous Goods.

IATA : International Air Transport Association.

ICAO : International Civil Aviation Organisation

RID : Regulations concerning the International carriage of Dangerous goods by rail.

GHS08 : Health hazard

PBT: Persistent, bioaccumulable and toxic.

vPvB : Very persistent, very bioaccumulable.

HCS : Hazard Communication standard (OSHA).