


MATERIAL SAFETY DATA SHEET

Product Code: Super M
HAZARD RATING

- N 4 - Extreme
- E 3 - High
- P 2 - Moderate
- A 1 - Slight
- 0 - Insignificant



DIVISION AND LOCATION---SECTION I

MAXIMA PRODUCTS
 10969 Wheatland Ave., Suite A
 Santee, CA. 92071
 Emergency Telephone No: (619) 449-5000
 Transportation Emergency: Chem Trec 1 (800) 424-9300 (U.S. and Canada)

CHEMICAL AND PHYSICAL PROPERTIES---SECTION II

Chemical Name:
 Petroleum distillate
 Formula:

not applicable
 Hazardous Decomposition Products:

Incompatibility (Keep away from):
 oxidizing agents
 Toxic and Hazardous Ingredients:

Form: liquid
 Odor: slight
 Appearance: liquid
 Color: blue/green
 Specific Gravity (water=1): .90
 Boiling Point: 480°F
 Melting Point:

Solubility in Water (by weight %): 0
 Volatile (by weight %): less than .03 @ 25 C
 Evaporation Rate: less than .02
 Vapor Pressure (mm Hg at 20°C): less than 1
 Vapor Density (air=1): less than .1
 Stability: Stable under normal conditions
 Viscosity SUS at 100°F:

FIRE AND EXPLOSION DATA---SECTION III

Special Fire Fighting Procedures:
 Avoid use of water. Do not enter fire without protective self-contained breathing apparatus
 Unusual Fire and Explosion Hazards:
 Dense smoke

10969 WHEATLANDS AVE, #A, SANTEE, CA 92071

CA (619) 449-5000

MATERIAL SAFETY DATA SHEET

Product Code: Super M

Page 2

(Section III Continued)

Flashpoint: (Method Used) greater than 149°C (300°F)

Flammable limits %: not available

Extinguishing agents:

Water, dry chemical, foam

HEALTH HAZARD DATA---SECTION IV

Permissible concentrations (air):

no data available

Chronic effects of overexposure:

Not considered hazardous to health in low to moderate accidental dosages.

Acute toxicological properties:

none

Emergency First Aid procedures:

Eyes: Flush with water for 15 minutes.

Skin Contact: Wash with soap and water

Inhalation: Remove to fresh air

If Swallowed: DO NOT induce vomiting. Call a physician.

SPECIAL PROTECTION INFORMATION---SECTION V

Ventilation Type Required (local, mechanical, special):

Respiratory Protection (Specify type):

NIOSH/OSHA approved respirator.

Protective Gloves: Neoprene or nitrile rubber gloves.

Eye Protection: chemical resistant goggles

Other Protective Equipment:

none

HANDLING OF SPILLS OR LEAKS---SECTION VI

Procedures for Clean-Up:

Absorb with clay, diatomaceous earth, or other suitable material. Do not
us water.

Waste Disposal:

Bury in disposable containers in approved dumping area in accordance with
governmental regulations.

(Continued Next Page)

10969 WHEATLANDS AVE, #A, SANTEE, CA 92071

CA (619) 449-5000

MATERIAL SAFETY DATA SHEET

Product Code: Super M

Page 3



MAXIMA
Heavy Lubricants

SPECIAL PRECAUTIONS---SECTION VII

Precautions to be taken in handling and storage: Store at ambient temperatures in tightly closed containers. Keep away from sparks or flames

Maximum Storage Temperature:

TRANSPORTATION DATA---SECTION VIII

D.O.T.: Not regulated

Reportable Quantity: Not applicable

Freight Classification: Petroleum oil

Special Transportation Notes:

COMMENTS---SECTION IX

Signature: RICHARD D. LECHEN

Title: President

Date:

Revision Date: 06-07-88

Supersedes:

Sent To:

Date:

We believe the statements, technical information and recommendations contained herein are reliable, but they are given without warranty or guarantee of any kind, express or implied, and we assume no responsibility for any loss, damage, or expense, direct or consequential, arising out of their use.

MAXIMA RACING OILS

004

MATERIAL SAFETY DATA SHEET

(Essentially Similar To Form OSHA-201 - Complies with 29CFR 1910.1200)

SECTION 1		TRADE NAME: Super M		CODE NUMBER: 20916/20901/20964/20505/20055		CHEMICAL FAMILY: Petroleum hydrocarbon		C.A.S. NO. mixture		TCSA INFORMATION: Components of this product are listed.	
DATE 1-1-01		SUPERCEDES		TRADE NAME: Super M		CODE NUMBER: 20916/20901/20964/20505/20055		CHEMICAL FAMILY: Petroleum hydrocarbon		C.A.S. NO. mixture	
SECTION II-HAZARDOUS INGREDIENTS											
COMPONENTS		C.A.S. NOS.	PPM	TLV/PEL	mg/m3	% BY WEIGHT					
Petroleum base stocks and/or	64742650	5*	>70	5*	none	<10					
Petroleum base stock and/or	64741964	5*	>70	5*	none	<10					
Petroleum base stock and/or	64741961	5*	>70	5*	none	<10					
Polybutene	9003296	5*	>70	5*	none	<10					
Ester	68424317	5*	>70	5*	none	<10					
SECTION III-FIRE AND EXPLOSION HAZARD DATA											
HAZARDOUS THERMAL DECOMPOSITION						FLAMMABLE LEL-UEL					
EXTINGUISHING						FLASHPOINT: ASTM D92					
MEDIA: Carbon Dioxide, Dry chemical, Foam, water fog.						DOT INFORMATION:					
UNUSUAL FIRE AND EXPLOSION HAZARDS: Slightly combustible. When heated above flash point will release flammable vapors which can burn in the open or explode confined if ignited.						FLASHPOINT: ASTM D92					
SPECIAL FIRE FIGHTING PROCEDURES: Do not enter any enclosed or confined area without proper protective equipment & self contained breathing apparatus.						DOT INFORMATION:					
SECTION IV-PHYSICAL DATA											
BOILING RANGE: >300°C						SOLUBILITY: Neg.					
VAPOR PRESSURE: 0.01mmHg @ 20°C						APPEARANCE AND ODOR: oily liquid, petroleum odor					
VAPOR DENSITY		EVAPORATION RATE		SPECIFIC GRAVITY		WEIGHT PER GALLON		% VOLATILE		% VOLATILE	
Heavier than air		Less than ether		0.88		7.4		nll		nll	
SECTION V-REACTIVITY DATA											
INCOMPATIBILITY											
MATERIAL TO AVOID: Strong oxidizers											
STABILITY: stable											
CONDITION TO AVOID: Do not heat above flash point.											
HAZARDOUS DECOMPOSITION PRODUCTS: Carbon Monoxide & asphyxiants											
HAZARDOUS POLYMERIZATION											
none											
occupational exposure limit: 1LV = 5mg/m as oil mist.											

PERSONAL PROTECTION (NFPA)

HEALTH



FIRE

REACTIVITY

A Division of Southwest Lubricants
 8200 Alvarado Way, San Jose, CA 95071
 (408) 448-8000
 EMERGENCY 24 HOURS
 CHEMTEC: 800-424-9300

NFPA

Not normally expected to cause any ill effects except in very sensitive individuals.	Remove from contaminated area. Apply artificial respiration. If unconscious consult a physician.
No significant adverse health effects are expected to occur on short time exposure.	Flush with copious amounts of water.
Not normally expected to cause any ill effects.	Wash with soap & water. Consult physician if irritation occurs.
Not normally expected to cause any ill effects.	Wear protective clothing to avoid skin contact. Consult physician if irritation should develop.

STEPS TO BE TAKEN IN CASE MATERIAL IS RELEASED

TRANSPORTATION INFORMATION: Consult 46CFR parts 1-300 and refer to section III of this MSDS for additional information.

OTHER PROTECTIVE EQUIPMENT: Eye protection recommended.

SECTION IX-SPECIAL PRECAUTIONS

OTHER PRECAUTIONS: Wash or shower if general contact occurs. Remove oil-soaked clothing & launder before reuse.

DATE: 1-1-01



PERSONAL PROTECTION (NFPA)

3A/3

20916/20901/20964/20505/20055

**Super M
PRODUCT**

A Division of Southwest Lubricants

