

# SAFETY DATA SHEET

(REACH regulation (EC) n° 1907/2006 - n° 2020/878)



## SECTION 1 : IDENTIFICATION OF THE SUBSTANCE/MIXTURE AND OF THE COMPANY/UNDERTAKING

### 1.1. Product identifier

Product name : A3 AIR FILTER OIL

Product code : 18502

### 1.2. Relevant identified uses of the substance or mixture and uses advised against

Air filter oil

### 1.3. Details of the supplier of the safety data sheet

Registered company name : MOTUL

Address : 119, Boulevard Felix Faure. 93300 AUBERVILLIERS CEDEX FRANCE

Telephone : 33.1.48.11.70.00. Fax: 33.1.48.33.28.79. Telex: .

Email : motul\_hse@motul.fr

### 1.4. Emergency telephone number : +44 (0) 1235 239 670.

Association/Organisation : CARECHEM 24/7 NCEC..

### Other emergency numbers

UNITED STATES: 001 866 928 0789 / CANADA: 001 800 579 7421 / MEXICO : +52 55 5004 8763 / MIDDLE EAST - AFRICA : +44 1235 239671

BRAZIL : +55 11 3197 5891 / COLOMBIA : +57 601 508 7337 / ARGENTINA : +54 11 5984 3690 / CHILE : +562 2582 9336

Ireland : +353 1 8092566

24 hours a day, 7 days a week

## SECTION 2 : HAZARDS IDENTIFICATION

### 2.1. Classification of the substance or mixture

#### In compliance with EC regulation No. 1272/2008 and its amendments.

Flammable liquid, Category 3 (Flam. Liq. 3, H226).

Repeated exposure may cause skin dryness or cracking (EUH066).

Specific target organ toxicity (single exposure), Category 3 (STOT SE 3, H336).

Hazardous to the aquatic environment - Chronic hazard, Category 3 (Aquatic Chronic 3, H412).

### 2.2. Label elements

#### In compliance with EC regulation No. 1272/2008 and its amendments.

Hazard pictograms :



GHS02



GHS07

Signal Word :

WARNING

Product identifiers :

EC 927-241-2

HYDROCARBONS, C9-C10, N-ALKANES, ISOALKANES, CYCLICS, <2% AROMATICS

Hazard statements :

H226

Flammable liquid and vapour.

H336

May cause drowsiness or dizziness.

H412

Harmful to aquatic life with long lasting effects.

EUH066

Repeated exposure may cause skin dryness or cracking.

Precautionary statements - General :

P101

If medical advice is needed, have product container or label at hand.

P102

Keep out of reach of children.

Precautionary statements - Prevention :

P210

Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

P261

Avoid breathing vapours.

P271

Use only outdoors or in a well-ventilated area.

P273

Avoid release to the environment.

Precautionary statements - Storage :

P403 + P235 Store in a well-ventilated place. Keep cool.

Precautionary statements - Disposal :

P501 Dispose of contents / container in accordance with local / regional / national / international regulations



### 2.3. Other hazards

The mixture does not contain substances classified as 'Substances of Very High Concern' (SVHC)  $\geq 0.1\%$  published by the European Chemicals Agency (ECHA) under article 57 of REACH: <http://echa.europa.eu/fr/candidate-list-table>

The mixture fulfils neither the PBT nor the vPvB criteria for mixtures in accordance with annexe XIII of the REACH regulations EC 1907/2006.

The mixture does not contain substances  $\geq 0.1\%$  with endocrine disrupting properties in accordance with the criteria of the Delegated Regulation (EU) 2017/2100 of the Commission or Regulation (EU) 2018/605 of the Commission.

## SECTION 3 : COMPOSITION/INFORMATION ON INGREDIENTS

### 3.2. Mixtures

#### Composition :

Identification	(EC) 1272/2008	Note	%
CAS: 64742-65-0 EC: 265-169-7 REACH: 01-2119471299-27  DISTILLATES (PETROLEUM), SOLVENT-DEWAXED HEAVY PARAFFINIC		L	25 $\leq$ x % < 50
CAS: 64742-48-9 EC: 927-241-2 REACH: 01-2119471843-32  HYDROCARBONS, C9-C10, N-ALKANES, ISOALKANES, CYCLICS, <2% AROMATICS	GHS07, GHS08, GHS02 Dgr Flam. Liq. 3, H226 Asp. Tox. 1, H304 STOT SE 3, H336 Aquatic Chronic 3, H412 EUH:066		25 $\leq$ x % < 50



#### Information on ingredients :

(Full text of H-phrases: see section 16)

Note L: The carcinogen classification does not apply because the substance contains less than 3 % w/w of dimethyl sulphoxide (DMSO) measured using the IP 346 method.

## SECTION 4 : FIRST AID MEASURES

As a general rule, in case of doubt or if symptoms persist, always call a doctor.

NEVER induce swallowing by an unconscious person.



### 4.1. description of first aid measures

#### In the event of exposure by inhalation :

In the event of massive inhalation, remove the person exposed to fresh air. Keep warm and at rest.

If the person is unconscious, place in recovery position. Notify a doctor in all events, to ascertain whether observation and supportive hospital care will be necessary.

If breathing is irregular or has stopped, effect mouth-to-mouth resuscitation and call a doctor.

Remove the victim to fresh air. If the symptoms persist, call a physician.

#### In the event of splashes or contact with eyes :

Wash immediately and abundantly with water, including under the eyelids.



#### In the event of splashes or contact with skin :

Remove contaminated clothing and wash the skin thoroughly with soap and water or a recognised cleaner.

Watch out for any remaining product between skin and clothing, watches, shoes, etc.

If the contaminated area is widespread and/or there is damage to the skin, a doctor must be consulted or the patient transferred to hospital.

Immediately remove all soiled clothing.

Wash immediately and abundantly with soap and water.

#### In the event of swallowing :

Seek medical attention, showing the label.

### 4.2. Most important symptoms and effects, both acute and delayed

No data available.

### 4.3. Indication of any immediate medical attention and special treatment needed

No data available.

## SECTION 5 : FIREFIGHTING MEASURES

Flammable.

Chemical powders, carbon dioxide and other extinguishing gas are suitable for small fires.

### 5.1. Extinguishing media

Keep packages near the fire cool, to prevent pressurised containers from bursting.

### Suitable methods of extinction

Prevent the effluent of fire-fighting measures from entering drains or waterways.

Dry agent, foam, carbon dioxide.

### Unsuitable methods of extinction

High volume water jet

### 5.2. Special hazards arising from the substance or mixture

A fire will often produce a thick black smoke. Exposure to decomposition products may be hazardous to health.

Do not breathe in smoke.

In the event of a fire, the following may be formed :

- carbon monoxide (CO)
- carbon dioxide (CO<sub>2</sub>)

### 5.3. Advice for firefighters

Fire-fighting personnel are to be equipped with autonomous insulating breathing apparatus.

## SECTION 6 : ACCIDENTAL RELEASE MEASURES

### 6.1. Personal precautions, protective equipment and emergency procedures

Consult the safety measures listed under headings 7 and 8.

Spilled product may make surfaces slippery.

### For non first aid worker

Avoid inhaling the vapors.

Avoid any contact with the skin and eyes.

If a large quantity has been spilt, evacuate all personnel and only allow intervention by trained operators equipped with safety apparatus.

### For first aid worker

First aid workers will be equipped with suitable personal protective equipment (See section 8).

### 6.2. Environmental precautions

Contain and control the leaks or spills with non-combustible absorbent materials such as sand, earth, vermiculite, diatomaceous earth in drums for waste disposal.

Prevent any material from entering drains or waterways.

If the product contaminates waterways, rivers or drains, alert the relevant authorities in accordance with statutory procedures

Use drums to dispose of collected waste in compliance with current regulations (see section 13).

### 6.3. Methods and material for containment and cleaning up

Clean preferably with a detergent, do not use solvents.

### 6.4. Reference to other sections

No data available.

## SECTION 7 : HANDLING AND STORAGE

Requirements relating to storage premises apply to all facilities where the mixture is handled.

### 7.1. Precautions for safe handling

Always wash hands after handling.

Remove and wash contaminated clothing before re-using.

Remove contaminated clothing and protective equipment before entering eating areas.

Do not swallow

Do not get in eyes, on skin, or on clothing.

### Fire prevention :

Handle in well-ventilated areas.

Prevent the formation of flammable or explosive concentrations in air and avoid vapor concentrations higher than the occupational exposure limits.

Prevent the accumulation of electrostatic charges with connections to earth.

The mixture can become electrostatically charged: always ground when decanting. Wear antistatic shoes and clothing and make floors of non-conductive

Use the mixture in premises free of naked flames or other sources of ignition and ensure that electrical equipment is suitably protected.  
Keep packages tightly closed and away from sources of heat, sparks and naked flames.  
Do not use tools which may produce sparks. Do not smoke.  
Prevent access by unauthorised personnel.  
Take precautionary measures against static discharges by bonding and grounding equipment.  
No smoking.

**Recommended equipment and procedures :**

For personal protection, see section 8.  
Observe precautions stated on label and also industrial safety regulations.  
Avoid inhaling vapors.  
Avoid inhaling vapors. Carry out any industrial operation which may give rise to this in a sealed apparatus.  
Provide vapor extraction at the emission source and also general ventilation of the premises.  
Also provide breathing apparatus for certain short tasks of an exceptional nature and for emergency interventions.  
In all cases, recover emissions at source.  
Ensure good ventilation at the workplace

**Prohibited equipment and procedures :**

No smoking, eating or drinking in areas where the mixture is used.  
Never open the packages under pressure.  
Do not breathe fumes, vapour, spray.

**7.2. Conditions for safe storage, including any incompatibilities**

Store between -5°C and 40°C in a dry, well ventilated place.  
Only use hydrocarbon-resistant containers, joints and pipes.

**Storage**

Keep out of reach of children.  
Keep the container tightly closed in a dry, well-ventilated place.  
Keep away from all sources of ignition - do not smoke.  
Keep well away from all sources of ignition, heat and direct sunlight.  
Avoid accumulation of electrostatic charges.

**Packaging**

Always keep in packaging made of an identical material to the original.

**7.3. Specific end use(s)**

No data available.

**SECTION 8 : EXPOSURE CONTROLS/PERSONAL PROTECTION****8.1. Control parameters**

No data available.

**8.2. Exposure controls****Appropriate engineering controls**

Ensure adequate ventilation, if possible with extractor fans at work posts and appropriate general extraction.  
Personnel shall wear regularly laundered overalls.

**Personal protection measures, such as personal protective equipment**

Use personal protective equipment that is clean and has been properly maintained.  
Store personal protective equipment in a clean place, away from the work area.  
Never eat, drink or smoke during use. Remove and wash contaminated clothing before re-using. Ensure that there is adequate ventilation, especially in confined areas.

**- Eye / face protection**

Avoid contact with eyes.  
Use eye protectors designed to protect against liquid splashes  
Before handling, wear safety goggles in accordance with standard EN166.

**- Hand protection**

Use suitable protective gloves that are resistant to chemical agents in accordance with standard EN ISO 374-1.  
Gloves must be selected according to the application and duration of use at the workstation.  
Protective gloves need to be selected according to their suitability for the workstation in question : other chemical products that may be handled, necessary physical protections (cutting, pricking, heat protection), level of dexterity required.  
Type of gloves recommended :  
- Nitrile rubber (butadiene-acrylonitrile copolymer rubber (NBR))

Glove thickness:	0.38 mm
Break-through time:	> 480 mn

**- Body protection**

Avoid skin contact.

Wear suitable protective clothing.

Suitable type of protective clothing :

In the event of substantial spatter, wear liquid-tight protective clothing against chemical risks (type 3) in accordance with EN14605/A1 to prevent skin contact.

In the event of a risk of splashing, wear protective clothing against chemical risks (type 6) in accordance with EN13034/A1 to prevent skin contact.

Work clothing worn by personnel shall be laundered regularly.

After contact with the product, all parts of the body that have been soiled must be washed.

**- Respiratory protection**

Avoid inhaling vapors.

If the ventilation is insufficient, wear appropriate breathing apparatus.

When workers are confronted with concentrations that are above occupational exposure limits, they must wear a suitable, approved, respiratory protection device.

Anti-gas and vapour filter(s) (Combined filters) in accordance with standard EN14387 :

- A1 (Brown)

Breathing apparatus only when aerosol or spray are formed.

**SECTION 9 : PHYSICAL AND CHEMICAL PROPERTIES****9.1. Information on basic physical and chemical properties****Physical state**

Physical state :	Viscous liquid.
------------------	-----------------

**Colour**

Color:	Blue
--------	------

**Odour**

Odour threshold :	Not stated.
-------------------	-------------

**Melting point**

Melting point/melting range :	Not relevant.
-------------------------------	---------------

**Freezing point**

Freezing point / Freezing range :	Not stated.
-----------------------------------	-------------

**Boiling point or initial boiling point and boiling range**

Boiling point/boiling range :	Not relevant.
-------------------------------	---------------

**Flammability**

Flammability (solid, gas) :	Not stated.
-----------------------------	-------------

**Lower and upper explosion limit**

Explosive properties, lower explosivity limit (%) :	Not stated.
-----------------------------------------------------	-------------

Explosive properties, upper explosivity limit (%) :	Not stated.
-----------------------------------------------------	-------------

**Flash point**

Flash Point :	42.00 °C.
---------------	-----------

**Auto-ignition temperature**

Self-ignition temperature :	Not relevant.
-----------------------------	---------------

**Decomposition temperature**

Decomposition point/decomposition range :	Not relevant.
-------------------------------------------	---------------

**pH**

pH (aqueous solution) :	Not stated.
-------------------------	-------------

pH :	Not relevant.
------	---------------

**Kinematic viscosity**

Viscosity :	247.7 mm²/s à 40°C
-------------	--------------------

**Solubility**

Water solubility :	Insoluble.
--------------------	------------

Fat solubility :	Not stated.
------------------	-------------

**Partition coefficient n-octanol/water (log value)**

Partition coefficient: n-octanol/water :	Not stated.
------------------------------------------	-------------

**Vapour pressure**

Vapour pressure (50°C) :	Not relevant.
--------------------------	---------------

**Density and/or relative density**

Density :	< 1
-----------	-----

**Relative vapour density**

Vapour density :	Not stated.
------------------	-------------

**9.2. Other information**

No data available.

**9.2.1. Information with regard to physical hazard classes**

No data available.

**9.2.2. Other safety characteristics**

No data available.

**SECTION 10 : STABILITY AND REACTIVITY****10.1. Reactivity**

No data available.

**10.2. Chemical stability**

This mixture is stable under the recommended handling and storage conditions in section 7.

**10.3. Possibility of hazardous reactions**

No data available.

**10.4. Conditions to avoid**

Any apparatus likely to produce a flame or to have a metallic surface at high temperature (burners, electric arcs, furnaces etc.) must not be allowed on the premises.

Avoid :

- accumulation of electrostatic charges.
- heating
- heat
- flames and hot surfaces

Keep away from heat and from sources of ignition

Take precautionary measures against static discharges.

**10.5. Incompatible materials**

Strong oxidants

Acids

**10.6. Hazardous decomposition products**

The thermal decomposition may release/form :

- carbon monoxide (CO)
- carbon dioxide (CO<sub>2</sub>)

**SECTION 11 : TOXICOLOGICAL INFORMATION****11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008**

Repeated or prolonged contact with the mixture may cause removal of natural oil from the skin resulting in non-allergic contact dermatitis and absorption through the skin.

Narcotic effects may occur, such as drowsiness, narcosis, decreased alertness, loss of reflexes, lack of coordination or dizziness.

Effects may also occur in the form of violent headaches or nausea, judgement disorder, giddiness, irritability, fatigue or memory disturbance.

**11.1.1. Substances****Acute toxicity :**

HYDROCARBONS, C9-C10, N-ALKANES, ISOALKANES, CYCLICS, &lt;2% AROMATICS (CAS: 64742-48-9)

Oral route :

LD50 &gt; 5000 mg/kg

Species : Rat

OCDE Ligne directrice 401 (Toxicité aiguë par voie orale)

Dermal route :

LD50 &gt; 5000 mg/kg

Species : Rabbit

OCDE Ligne directrice 403 (Toxicité aiguë par inhalation)

**11.1.2. Mixture****Skin corrosion/skin irritation :**

Repeated or prolonged contact with the preparation may cause removal of natural fat from the skin resulting in non allergic contact dermatitis and absorption through the skin.

**Serious damage to eyes/eye irritation :**

Mild eye irritation

**Aspiration hazard :**

"Inhalation of vapours may cause irritation of the respiratory system in very susceptible persons."  
May cause lung damage if swallowed

**11.2. Information on other hazards**

**SECTION 12 : ECOLOGICAL INFORMATION**

Harmful to aquatic life with long lasting effects.

The product must not be allowed to run into drains or waterways.

**12.1. Toxicity**

**12.1.1. Substances**

HYDROCARBONS, C9-C10, N-ALKANES, ISOALKANES, CYCLICS, <2% AROMATICS (CAS: 64742-48-9)

Fish toxicity : LC50 < 30 mg/l  
Species : Oncorhynchus mykiss  
Duration of exposure : 96 h

Crustacean toxicity : EC50 < 46 mg/l  
Species : Daphnia magna  
Duration of exposure : 48 h

Algae toxicity : ECr50 > 1000 mg/l  
Species : Pseudokirchnerella subcapitata  
Duration of exposure : 72 h

**12.1.2. Mixtures**

**12.2. Persistence and degradability**

**12.2.1. Substances**

HYDROCARBONS, C9-C10, N-ALKANES, ISOALKANES, CYCLICS, <2% AROMATICS (CAS: 64742-48-9)

Biodegradability : Rapidly degradable.

**12.2.2. Mixtures**

Biodegradation : No data on decomposition is available, the mixture is not considered to decompose rapidly.

**12.3. Bioaccumulative potential**

No data available.

**12.4. Mobility in soil**

Not very mobile in soil.

The product is insoluble in water and will spread on the surface

**12.5. Results of PBT and vPvB assessment**

No data available.

**12.6. Endocrine disrupting properties**

No data available.

**12.7. Other adverse effects**

Do not dispose of the product in the natural environment, effluents or surface waters.

**German regulations concerning the classification of hazards for water (WGK, AwSV Annex I, KBws) :**

WGK 1 : Slightly hazardous for water.

**SECTION 13 : DISPOSAL CONSIDERATIONS**

Proper waste management of the mixture and/or its container must be determined in accordance with Directive 2008/98/EC.

**13.1. Waste treatment methods**

Do not pour into drains or waterways.

**Waste :**

Waste management is carried out without endangering human health, without harming the environment and, in particular without risk to water, air, soil, plants or animals.

Recycle or dispose of waste in compliance with current legislation, preferably via a certified collector or company.

Do not contaminate the ground or water with waste, do not dispose of waste into the environment.

**Soiled packaging :**

Empty container completely. Keep label(s) on container.  
Give to a certified disposal contractor.

## SECTION 14 : TRANSPORT INFORMATION

Transport product in compliance with provisions of the ADR for road, RID for rail, IMDG for sea and ICAO/IATA for air transport (ADR 2021 - IMDG 2020 [40-20] - ICAO/IATA 2022 [63]).

### 14.1. UN number or ID number

3295

### 14.2. UN proper shipping name

UN3295=HYDROCARBONS, LIQUID, N.O.S.

### 14.3. Transport hazard class(es)

- Classification :



3

### 14.4. Packing group

III

### 14.5. Environmental hazards

-

### 14.6. Special precautions for user

ADR/RID	Class	Code	Pack gr.	Label	Ident.	LQ	Provis.	EQ	Cat.	Tunnel
	3	F1	III	3	30	5 L	-	E1	3	D/E

\*If Q <450l, see 2.2.3.1.5.1.

IMDG	Class	2°Label	Pack gr.	LQ	EMS	Provis.	EQ	Stowage Handling	Segregation
	3	-	III	5 L	F-E, S-D	223	E1	Category A	-

\*if Q < 450 l see IMDG 2.3.2.5.

IATA	Class	2°Label	Pack gr.	Passager	Passager	Cargo	Cargo	note	EQ
	3	-	III	355	60 L	366	220 L	A3 A324	E1
	3	-	III	Y344	10 L	-	-	A3 A324	E1

For limited quantities, see part 2.7 of the OACI/IATA and chapter 3.4 of the ADR and IMDG.

For excepted quantities, see part 2.6 of the OACI/IATA and chapter 3.5 of the ADR and IMDG.

### 14.7. Maritime transport in bulk according to IMO instruments

No data available.

## SECTION 15: Regulatory information

### 15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

#### - Classification and labelling information included in section 2:

The following regulations have been used:

- EU Regulation No. 1272/2008 amended by EU Regulation No. 2022/692 (ATP 18)

#### - Container information:

The mixture does not contain any substance restricted under Annex XVII of Regulation (EC) No. 1907/2006 (REACH):

<https://echa.europa.eu/substances-restricted-under-reach>.

#### - Particular provisions :

No data available.

#### - German regulations concerning the classification of hazards for water (WGK, AwSV Annex I, KBws) :

WGK 1 : Slightly hazardous for water.

### 15.2. Chemical safety assessment

No data available.

## SECTION 16 : OTHER INFORMATION

Since the user's working conditions are not known by us, the information supplied on this safety data sheet is based on our current level of



knowledge and on national and community regulations.

The mixture must not be used for other uses than those specified in section 1 without having first obtained written handling instructions.

It is at all times the responsibility of the user to take all necessary measures to comply with legal requirements and local regulations.

The information in this safety data sheet must be regarded as a description of the safety requirements relating to the mixture and not as a guarantee of the properties thereof.

**Wording of the phrases mentioned in section 3 :**

H226	Flammable liquid and vapour.
H304	May be fatal if swallowed and enters airways.
H336	May cause drowsiness or dizziness.
H412	Harmful to aquatic life with long lasting effects.
EUH066	Repeated exposure may cause skin dryness or cracking.



**Abbreviations :**

LD50 : The dose of a test substance resulting in 50% lethality in a given time period.

LC50 : The concentration of a test substance resulting in 50% lethality in a given period.

EC50 : The effective concentration of substance that causes 50% of the maximum response.

ECr50 : The effective concentration of substance that causes 50% reduction in growth rate.

REACH : Registration, Evaluation, Authorization and Restriction of Chemical Substances.

ADR : European agreement concerning the international carriage of dangerous goods by Road.

IMDG : International Maritime Dangerous Goods.

IATA : International Air Transport Association.

ICAO : International Civil Aviation Organisation

RID : Regulations concerning the International carriage of Dangerous goods by rail.

WGK : Wassergefährdungsklasse (Water Hazard Class).

GHS02 : Flame

GHS07 : Exclamation mark

PBT: Persistent, bioaccumulable and toxic.

vPvB : Very persistent, very bioaccumulable.

SVHC : Substances of very high concern.