

Printing date 03/22/2016

Reviewed on 03/22/2016

#### 1 Identification

- · Product identifier
- · Trade name: AIR FILTER OIL SPRAY
- · Application of the substance / the mixture Only for proper handling.
- · Details of the supplier of the safety data sheet
- · Manufacturer/Supplier:

BUCHER\_AG\_LANGENTHAL MOTOREX-Schmiertechnik Bern-Zürich-Strasse\_31\_\_ CH-4901\_Langenthal\_\_ Telefon\_+41\_(0)62\_919\_75\_75

Lube-Tech Lubrication Technologies, Inc. 900 Mendelssohn Avenue North US-55427 Golden Valley, Minnesota

Phone: 001 763 417 1357

- Information department: msds@motorex.com
- Emergency telephone number: Toxicological Information Centre CH-8028 Zurich

<u>info@toxi.ch</u> T. +41 (0)44 251 51 51

USA + Kanada: 1 800 424 9300 (Chemtrec Chemical Manufacturers Association, Arlington,

VA 22209)

#### 2 Hazard(s) identification

· Classification of the substance or mixture



GHS02 Flame

Flam. Aerosol 1 H222-H229 Extremely flammable aerosol. Pressurized container: May burst if heated.



GHS07

STOT SE 3 H336 May cause drowsiness or dizziness.

Aquatic Acute 3 H402 Harmful to aquatic life.

Aquatic Chronic 3 H412 Harmful to aquatic life with long lasting effects.

- · Label elements
- · GHS label elements

The product is classified and labeled according to the Globally Harmonized System (GHS).

· Hazard pictograms





GHS02 GHS07

(Contd. on page 2)

Printing date 03/22/2016

Reviewed on 03/22/2016

Trade name: AIR FILTER OIL SPRAY

(Contd. of page 1)

· Signal word Danger

#### · Hazard-determining components of labeling:

Hydrocarbons, C7-C9, n-alkanes, isoalkanes, cyclics acetone

#### · Hazard statements

H222-H229 Extremely flammable aerosol. Pressurized container: May burst if heated.

H336 May cause drowsiness or dizziness.

H402 Harmful to aquatic life.

H412 Harmful to aquatic life with long lasting effects.

#### · Precautionary statements

P210 Keep away from heat/sparks/open flames/hot surfaces. No smoking.

P251 Do not pierce or burn, even after use.

P211 Do not spray on an open flame or other ignition source.

P261 Avoid breathing dust/fume/gas/mist/vapors/spray

P273 Avoid release to the environment.

P271 Use only outdoors or in a well-ventilated area.

P304+P340 IF INHALED: Remove person to fresh air and keep comfortable for breathing.

P312 Call a POISON CENTER/doctor if you feel unwell.

P405 Store locked up.

P410+P412 Protect from sunlight. Do not expose to temperatures exceeding 50°C/122°F.

P403+P233 Store in a well-ventilated place. Keep container tightly closed.

P501 Dispose of contents/container in accordance with local/regional/national/

international regulations.

· Classification system:

NFPA ratings (scale 0 - 4)



Health = 0 Fire = 4 Reactivity = 3

· HMIS-ratings (scale 0 - 4)



- Other hazards
- · Results of PBT and vPvB assessment
- · **PBT:** Not applicable.
- · vPvB: Not applicable.

#### 3 Composition/information on ingredients

- · Chemical characterization: Mixtures
- · **Description:** Mixture of the substances listed below with nonhazardous additions.
- · Dangerous components: Void

#### 4 First-aid measures

- · Description of first aid measures
- · After inhalation: Supply fresh air; consult doctor in case of complaints.
- After skin contact: Generally the product does not irritate the skin.
- · After eye contact: Rinse opened eye for several minutes under running water.
- · After swallowing: If symptoms persist consult doctor.

(Contd. on page 3)

Printing date 03/22/2016

Reviewed on 03/22/2016

Trade name: AIR FILTER OIL SPRAY

(Contd. of page 2)

- · Information for doctor:
- · Most important symptoms and effects, both acute and delayed No further relevant information available.
- · Indication of any immediate medical attention and special treatment needed No further relevant information available.

### 5 Fire-fighting measures

- · Extinguishing media
- Suitable extinguishing agents:

CO2, extinguishing powder or water spray. Fight larger fires with water spray or alcohol resistant foam.

- Special hazards arising from the substance or mixture No further relevant information available.
- · Advice for firefighters
- · Protective equipment: No special measures required.

### 6 Accidental release measures

- · Personal precautions, protective equipment and emergency procedures Wear protective equipment. Keep unprotected persons away.
- · Environmental precautions:

Do not allow product to reach sewage system or any water course.

Inform respective authorities in case of seepage into water course or sewage system.

Do not allow to enter sewers/ surface or ground water.

· Methods and material for containment and cleaning up:

Dispose contaminated material as waste according to item 13.

Ensure adequate ventilation.

· Reference to other sections

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

### 7 Handling and storage

- · Handling:
- · Precautions for safe handling Ensure good ventilation/exhaustion at the workplace.
- · Information about protection against explosions and fires:

Keep ignition sources away - Do not smoke.

Pressurized container: protect from sunlight and do not expose to temperatures exceeding 50 °C, i.e. electric lights. Do not pierce or burn, even after use.

Do not spray on a naked flame or any incandescent material.

- · Conditions for safe storage, including any incompatibilities
- · Storage:
- · Requirements to be met by storerooms and receptacles:

Observe official regulations on storing packagings with pressurized containers.

- · Information about storage in one common storage facility: Not required.
- · Further information about storage conditions: Keep receptacle tightly sealed.
- · Storage class: 2 B
- · Specific end use(s) No further relevant information available.

ıs -

Printing date 03/22/2016

Reviewed on 03/22/2016

Trade name: AIR FILTER OIL SPRAY

(Contd. of page 3)

### 8 Exposure controls/personal protection

- · Additional information about design of technical systems: No further data; see item 7.
- · Control parameters
- · Components with limit values that require monitoring at the workplace:

The product does not contain any relevant quantities of materials with critical values that have to be monitored at the workplace.

- · Additional information: The lists that were valid during the creation were used as basis.
- · Exposure controls
- Personal protective equipment:
- · General protective and hygienic measures:

Wash hands before breaks and at the end of work.

· Breathing equipment:

In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use respiratory protective device that is independent of circulating air.

· Protection of hands:

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

· Material of gloves

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

· Penetration time of glove material

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

· Eye protection: Not required.

### 9 Physical and chemical properties

· Information on basic physical and chemical properties · General Information		
· Appearance:		
Form:	Liquefied gas	
Color:	Blue	
· Odor:	Solvent-like	
· Odor threshold:	Not determined.	
· pH-value:	Not determined.	
· Change in condition Melting point/Melting range: Boiling point/Boiling range:	Undetermined. Not applicable, as aerosol.	
· Flash point:	< -30 °C (< -22 °F)	
· Flammability (solid, gaseous):	Not applicable.	
· Ignition temperature:	310 °C (590 °F) (DIN 51794)	
· Decomposition temperature:	Not determined.	
	(Contd. on no	

(Contd. on page 5)

Printing date 03/22/2016

Reviewed on 03/22/2016

Trade name: AIR FILTER OIL SPRAY

	(Contd. of page 4
· Auto igniting:	Product is not selfigniting.
Danger of explosion:	Product is not explosive. However, formation o explosive air/vapor mixtures are possible.
Explosion limits:	
Lower:	0.9 Vol %
Upper:	8.5 Vol %
Vapor pressure at 20 °C (68 °F):	2100 hPa (1575 mm Hg)
Density at 20 °C (68 °F):	0.796 g/cm³ (6.643 lbs/gal) (ASTM D 4052)
Relative density	Not determined.
Vapor density	Not determined.
Evaporation rate	Not applicable.
Solubility in / Miscibility with	
Water:	Not miscible or difficult to mix.
Partition coefficient (n-octanol/wate	er): Not determined.
· Viscosity:	
Dynamic:	Not determined.
Kinematic:	<1 mm²/s @ 40 °C (DIN 51562-1)
· Other information	No further relevant information available.

### 10 Stability and reactivity

- · Reactivity No further relevant information available.
- · Chemical stability
- · Thermal decomposition / conditions to be avoided:

No decomposition if used according to specifications.

- · Possibility of hazardous reactions No dangerous reactions known.
- · Conditions to avoid No further relevant information available.
- · Incompatible materials: No further relevant information available.
- · Hazardous decomposition products: No dangerous decomposition products known.

### 11 Toxicological information

- · Information on toxicological effects
- · Acute toxicity:
- · Primary irritant effect:
- · on the skin: No irritant effect.
- · on the eye: No irritating effect.
- · Sensitization: No sensitizing effects known.
- · Additional toxicological information:
- · Carcinogenic categories
- · IARC (International Agency for Research on Cancer)

  None of the ingredients is listed.
- · NTP (National Toxicology Program)

None of the ingredients is listed.

(Contd. on page 6)

Printing date 03/22/2016

Reviewed on 03/22/2016

Trade name: AIR FILTER OIL SPRAY

(Contd. of page 5)

· OSHA-Ca (Occupational Safety & Health Administration)

None of the ingredients is listed.

## 12 Ecological information

- · Toxicity
- · Aquatic toxicity: No further relevant information available.
- · Persistence and degradability No further relevant information available.
- · Behavior in environmental systems:
- · Bioaccumulative potential No further relevant information available.
- · Mobility in soil No further relevant information available.
- Ecotoxical effects:
- · Remark: Harmful to fish
- · Additional ecological information:
- · General notes:

Water hazard class 1 (Self-classification according VwVwS, 17.05.1999): slightly hazardous for water

Do not allow undiluted product or large quantities of it to reach ground water, water course or sewage system.

Harmful to aquatic organisms

- Results of PBT and vPvB assessment
- · **PBT:** Not applicable.
- · vPvB: Not applicable.
- · Other adverse effects No further relevant information available.

## 13 Disposal considerations

- · Waste treatment methods
- · Recommendation:

Must not be disposed of together with household garbage. Do not allow product to reach sewage system.

- · Uncleaned packagings:
- · Recommendation:

Disposal must be made according to official regulations.

Discharged containers can contain flammable or explosive vapours.

#### 14 Transport information

· UN-Number

· DOT, ADR,ADN, IMDG, IATA UN1950

· UN proper shipping name

DOT, IATA Aerosols, flammable
 ADR/ADN 1950 Aerosols
 IMDG AEROSOLS

(Contd. on page 7)

US

Printing date 03/22/2016

Reviewed on 03/22/2016

Trade name: AIR FILTER OIL SPRAY

(Contd. of page 6) · Transport hazard class(es) · DOT · Class 2.1 · Label 2.1 · ADR/ADN 2 5F Gases · Class · Label 2.1 · IMDG, IATA 2.1 · Class · Label 2.1 · Packing group · DOT, ADR, ADN, IMDG, IATA Void · Environmental hazards: · Marine pollutant: No · Special precautions for user Warning: Gases Danger code (Kemler): · EMS Number: F-D,S-U Stowage Code SW1 Protected from sources of heat. SW22 For AEROSOLS with a maximum capacity of 1 litre: Category A. For AEROSOLS with a capacity above 1 litre: Category B. For WASTE AEROSOLS: Category C, Clear of living quarters. · Segregation Code SG69 For AEROSOLS with a maximum capacity of 1 litre: Segregation as for class 9. Stow "separated from" class 1 except for division 1.4. For AEROSOLS with a capacity above 1 litre: Segregation as for the appropriate subdivision of class 2. For WASTE AEROSOLS: Segregation as for the appropriate subdivision of class 2. · Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code Not applicable. (Contd. on page 8)

ÚS.

Printing date 03/22/2016

Reviewed on 03/22/2016

Trade name: AIR FILTER OIL SPRAY

### 15 Regulatory information

- · Safety, health and environmental regulations/legislation specific for the substance or mixture
- · Sara
- · Section 355 (extremely hazardous substances):

None of the ingredients is listed.

· Section 313 (Specific toxic chemical listings):

None of the ingredients is listed.

· TSCA (Toxic Substances Control Act):

None of the ingredients is listed.

- · Proposition 65
- · Chemicals known to cause cancer:

None of the ingredients is listed.

· Chemicals known to cause reproductive toxicity for females:

None of the ingredients is listed.

· Chemicals known to cause reproductive toxicity for males:

None of the ingredients is listed.

· Chemicals known to cause developmental toxicity:

None of the ingredients is listed.

- · Carcinogenic categories
- EPA (Environmental Protection Agency)

None of the ingredients is listed.

· TLV (Threshold Limit Value established by ACGIH)

None of the ingredients is listed.

· NIOSH-Ca (National Institute for Occupational Safety and Health)

None of the ingredients is listed.

· Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

#### 16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

(Contd. on page 9)

Printing date 03/22/2016

Reviewed on 03/22/2016

Trade name: AIR FILTER OIL SPRAY

(Contd. of page 8)

- · Department issuing SDS: Abteilung Produktsicherheit
- · Date of preparation / last revision 03/22/2016 / -
- · Abbreviations and acronyms:

Flam. Aerosol 1: Flammable aerosols, Hazard Category 1 STOT SE 3: Specific target organ toxicity - Single exposure, Hazard Category 3 Aquatic Acute 3: Hazardous to the aquatic environment - AcuteHazard, Category 3 Aquatic Chronic 3: Hazardous to the aquatic environment - Chronic Hazard, Category 3

- US