

MATERIAL SAFETY DATA SHEET

Page 1

Product Code: Super M

HAZARD RATING


|   |   |   |               |
|---|---|---|---------------|
| N | 4 | - | Extreme       |
| F | 3 | - | High          |
| P | 2 | - | Moderate      |
| A | 1 | - | Slight        |
| 0 | - | - | Insignificant |

Fire

Toxicity

Reactivity

Special



DIVISION AND LOCATION---SECTION I

MAXIMA PRODUCTS  
 10969 Wheatland Ave., Suite A  
 Santee, CA. 92071  
 Emergency Telephone No: (619) 449-5000  
 Transportation Emergency: Chem Trec 1 (800) 424-9300 (U.S. and Canada)

CHEMICAL AND PHYSICAL PROPERTIES---SECTION II

Chemical Name:  
 Petroleum distillate  
 Formula:  
 not applicable  
 Hazardous Decomposition Products:

Incompatibility (Keep away from):  
 oxidizing agents  
 Toxic and Hazardous Ingredients:

Form: liquid  
 Odor: slight  
 Appearance: liquid  
 Color: blue/green  
 Specific Gravity (water=1): .90  
 Boiling Point: 480°F  
 Melting Point:

Solubility in Water (by weight %): 0  
 Volatile (by weight %): less than .03 @ 25 C  
 Evaporation Rate: less than .02  
 Vapor Pressure (mm Hg at 20°C): less than 1  
 Vapor Density (air=1): less than .1  
 Stability: Stable under normal conditions  
 Viscosity SUS at 100°F:

FIRE AND EXPLOSION DATA---SECTION III

Special Fire Fighting Procedures:  
 Avoid use of water. Do not enter fire without protective self-contained breathing apparatus  
 Unusual Fire and Explosion Hazards:  
 Dense smoke

10969 WHEATLANDS AVE, #A, SANTEE, CA 92071

CA (619) 449-5000

MATERIAL SAFETY DATA SHEET

Product Code: Super M

Page 2

(Section III Continued)

Flashpoint: (Method Used) greater than 149°C (300°F)

Flammable limits %: not available

Extinguishing agents:

Water, dry chemical, foam

HEALTH HAZARD DATA---SECTION IV

Permissible concentrations (air):

no data available

Chronic effects of overexposure:

Not considered hazardous to health in low to moderate accidental dosages.

Acute toxicological properties:

none

Emergency First Aid procedures:

Eyes: Flush with water for 15 minutes.

Skin Contact: Wash with soap and water

Inhalation: Remove to fresh air

If Swallowed: DO NOT induce vomiting. Call a physician.

SPECIAL PROTECTION INFORMATION---SECTION V

Ventilation Type Required (local, mechanical, special):

Respiratory Protection (Specify type):

NIOSH/OSHA approved respirator.

Protective Gloves: Neoprene or nitrile rubber gloves.

Eye Protection: chemical resistant goggles

Other Protective Equipment:

none

HANDLING OF SPILLS OR LEAKS---SECTION VI

Procedures for Clean-Up:

Absorb with clay, diatomaceous earth, or other suitable material. Do not  
us water.

Waste Disposal:

Bury in disposable containers in approved dumping area in accordance with  
governmental regulations.

(Continued Next Page)

10969 WHEATLANDS AVE, #A, SANTEE, CA 92071

CA (619) 449-5000

MATERIAL SAFETY DATA SHEET

Product Code: Super M

Page 3



**MAXIMA**  
Heavy Lubricants

**SPECIAL PRECAUTIONS---SECTION VII**

Precautions to be taken in handling and storage: Store at ambient temperatures in tightly closed containers. Keep away from sparks or flames

Maximum Storage Temperature:

**TRANSPORTATION DATA---SECTION VIII**

D.O.T.: Not regulated

Reportable Quantity: Not applicable

Freight Classification: Petroleum oil

Special Transportation Notes:

**COMMENTS---SECTION IX**

Signature: RICHARD D. LECHTEN

Title: President

Date:

Revision Date: 06-07-88

Supersedes:

Sent To:

Date:

We believe the statements, technical information and recommendations contained herein are reliable, but they are given without warranty or guarantee of any kind, express or implied, and we assume no responsibility for any loss, damage, or expense, direct or consequential, arising out of their use.

## MAXIMA RACING OILS

004

## MATERIAL SAFETY DATA SHEET

(Essentially Similar To Form OSHA-201 - Complies with 29CFR 1910.1200)

|                                                                                                                                                                                         |          |                            |            |                                                   |              |                                                         |  |                                               |  |                                                                 |  |
|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|----------|----------------------------|------------|---------------------------------------------------|--------------|---------------------------------------------------------|--|-----------------------------------------------|--|-----------------------------------------------------------------|--|
| <b>SECTION 1</b>                                                                                                                                                                        |          | <b>TRADE NAME:</b> Super M |            | <b>CODE NUMBER:</b> 20916/20901/20964/20505/20055 |              | <b>CHEMICAL FAMILY:</b> Petroleum hydrocarbon           |  | <b>C.A.S. NO. mixture</b>                     |  | <b>TCSA INFORMATION:</b> Components of this product are listed. |  |
| <b>DATE</b> 1-1-01                                                                                                                                                                      |          | <b>SUPERCEDES</b>          |            | <b>TRADE NAME:</b> Super M                        |              | <b>CODE NUMBER:</b> 20916/20901/20964/20505/20055       |  | <b>CHEMICAL FAMILY:</b> Petroleum hydrocarbon |  | <b>C.A.S. NO. mixture</b>                                       |  |
| <b>SECTION II-HAZARDOUS INGREDIENTS</b>                                                                                                                                                 |          |                            |            |                                                   |              |                                                         |  |                                               |  |                                                                 |  |
| <b>COMPONENTS</b>                                                                                                                                                                       |          | <b>C.A.S. NOS.</b>         | <b>PPM</b> | <b>TLV/PEL</b>                                    | <b>mg/m3</b> | <b>% BY WEIGHT</b>                                      |  |                                               |  |                                                                 |  |
| Petroleum base stocks and/or                                                                                                                                                            | 64742650 | 5*                         | >70        | 5*                                                | none         | <10                                                     |  |                                               |  |                                                                 |  |
| Petroleum base stock and/or                                                                                                                                                             | 64741964 | 5*                         | >70        | 5*                                                | none         | <10                                                     |  |                                               |  |                                                                 |  |
| Petroleum base stock and/or                                                                                                                                                             | 64741961 | 5*                         | >70        | 5*                                                | none         | <10                                                     |  |                                               |  |                                                                 |  |
| Polybutene                                                                                                                                                                              | 9003296  | 5*                         | >70        | 5*                                                | none         | <10                                                     |  |                                               |  |                                                                 |  |
| Ester                                                                                                                                                                                   | 68424317 | 5*                         | >70        | 5*                                                | none         | <10                                                     |  |                                               |  |                                                                 |  |
| <b>SECTION III-FIRE AND EXPLOSION HAZARD DATA</b>                                                                                                                                       |          |                            |            |                                                   |              |                                                         |  |                                               |  |                                                                 |  |
| <b>HAZARDOUS THERMAL DECOMPOSITION</b>                                                                                                                                                  |          |                            |            |                                                   |              | <b>FLAMMABLE</b> LEL-UEL                                |  |                                               |  |                                                                 |  |
| <b>EXTINGUISHING</b>                                                                                                                                                                    |          |                            |            |                                                   |              | <b>FLASHPOINT:</b> ASTM D92                             |  |                                               |  |                                                                 |  |
| <b>MEDIA:</b> Carbon Dioxide, Dry chemical, Foam, water fog.                                                                                                                            |          |                            |            |                                                   |              | <b>DOT INFORMATION:</b>                                 |  |                                               |  |                                                                 |  |
| <b>UNUSUAL FIRE AND EXPLOSION HAZARDS:</b> Slightly combustible. When heated above flash point will release flammable vapors which can burn in the open or explode confined if ignited. |          |                            |            |                                                   |              | <b>FLASHPOINT:</b> ASTM D92                             |  |                                               |  |                                                                 |  |
| <b>SPECIAL FIRE FIGHTING PROCEDURES:</b> Do not enter any enclosed or confined area without proper protective equipment & self contained breathing apparatus.                           |          |                            |            |                                                   |              | <b>DOT INFORMATION:</b>                                 |  |                                               |  |                                                                 |  |
| <b>SECTION IV-PHYSICAL DATA</b>                                                                                                                                                         |          |                            |            |                                                   |              |                                                         |  |                                               |  |                                                                 |  |
| <b>BOILING RANGE:</b> >300°C                                                                                                                                                            |          |                            |            |                                                   |              | <b>SOLUBILITY:</b> Neg.                                 |  |                                               |  |                                                                 |  |
| <b>VAPOR PRESSURE:</b> 0.01mmHg @ 20°C                                                                                                                                                  |          |                            |            |                                                   |              | <b>APPEARANCE AND ODOR:</b> oily liquid, petroleum odor |  |                                               |  |                                                                 |  |
| <b>VAPOR DENSITY</b>                                                                                                                                                                    |          | <b>EVAPORATION RATE</b>    |            | <b>SPECIFIC GRAVITY</b>                           |              | <b>WEIGHT PER GALLON</b>                                |  | <b>% VOLATILE</b>                             |  | <b>% VOLATILE</b>                                               |  |
| Heavier than air                                                                                                                                                                        |          | Less than ether            |            | 0.88                                              |              | 7.4                                                     |  | nll                                           |  | nll                                                             |  |
| <b>SECTION V-REACTIVITY DATA</b>                                                                                                                                                        |          |                            |            |                                                   |              |                                                         |  |                                               |  |                                                                 |  |
| <b>INCOMPATIBILITY</b>                                                                                                                                                                  |          |                            |            |                                                   |              |                                                         |  |                                               |  |                                                                 |  |
| <b>MATERIAL TO AVOID:</b> Strong oxidizers                                                                                                                                              |          |                            |            |                                                   |              |                                                         |  |                                               |  |                                                                 |  |
| <b>STABILITY:</b> stable                                                                                                                                                                |          |                            |            |                                                   |              |                                                         |  |                                               |  |                                                                 |  |
| <b>CONDITION TO AVOID:</b> Do not heat above flash point.                                                                                                                               |          |                            |            |                                                   |              |                                                         |  |                                               |  |                                                                 |  |
| <b>HAZARDOUS DECOMPOSITION PRODUCTS:</b> Carbon Monoxide & asphyxiants                                                                                                                  |          |                            |            |                                                   |              |                                                         |  |                                               |  |                                                                 |  |
| <b>HAZARDOUS POLYMERIZATION</b>                                                                                                                                                         |          |                            |            |                                                   |              |                                                         |  |                                               |  |                                                                 |  |
| <b>occupational exposure limit:</b> none                                                                                                                                                |          |                            |            |                                                   |              |                                                         |  |                                               |  |                                                                 |  |
| <b>occupational exposure limit:</b> none                                                                                                                                                |          |                            |            |                                                   |              |                                                         |  |                                               |  |                                                                 |  |

PERSONAL PROTECTION (NFPA)

HEALTH



FIRE

REACTIVITY

A Division of Southwest Lubricants  
 8200 Alvarado Way, San Jose, CA 95071  
 (408) 448-8000  
 EMERGENCY 24 HOURS  
 CHEMTEC: 800-424-9300

SECTION VI-HEALTH HAZARD DATA

ADVERSE AFFECTS FIRST AID PROCEDURES NFPA

| G N I                                                                                |                                                                                     | H N I                                                                                            |                                                 | E C Y O E N                          |  | A S C K O I N E                                                 |  | C S C K O I N E                                                                                                |  | C I N O N |  |
|--------------------------------------------------------------------------------------|-------------------------------------------------------------------------------------|--------------------------------------------------------------------------------------------------|-------------------------------------------------|--------------------------------------|--|-----------------------------------------------------------------|--|----------------------------------------------------------------------------------------------------------------|--|-----------|--|
| Do not induce vomiting. Consult a physician.                                         |                                                                                     | Remove from contaminated area. Apply artificial respiration. If unconscious consult a physician. |                                                 | Flush with copious amounts of water. |  | Wash with soap & water. Consult physician if irritation occurs. |  | Prolonged or repeated contact may produce mild irritation. Personnel with skin disorders should avoid contact. |  |           |  |
| Not normally expected to cause any ill effects except in very sensitive individuals. | No significant adverse health effects are expected to occur on short time exposure. | Not normally expected to cause any ill effects.                                                  | Not normally expected to cause any ill effects. |                                      |  |                                                                 |  |                                                                                                                |  |           |  |

PROCEDURES
NFPA