

MATERIAL SAFETY DATA SHEET

MEXIMB KACING 0115

NO. 5924 P. 2002

(Essentially Similar To Form OSHA 201 - Complies with 29 CFR 1910.1200)

SECTION 1

TRADE NAME: Formula K2 DATE 7/1/04
 CODE NUMBER: 22901/22505/22055/22916/22964 SUPERCEDES
 CHEMICAL FAMILY:

C.A.S. NO.
 CARCINOGENIC INGREDIENTS OSHA/NTP/IARC: NONE
 TCSA INFORMATION: COMPONENTS OF THIS PRODUCT ARE LISTED.

SECTION II-HAZARDOUS INGREDIENTS

COMPONENTS	C.A.S. NOS.	TLV/PEL PPM	mg/m3	% BY WEIGHT VOLUME
Lubricant Base Fluid	68424-40-8			%10
Lubricant Base Fluid	11138-60-6			>10
Lubricant Base Fluid	68552-19-2			<10
Synthetic Additive Fluid	9003-29-6			>20
Synthetic 2-Cycle Additive	N/A Mixture			<10

SECTION III-FIRE AND EXPLOSION HAZARD DATA

HAZARDOUS THERMAL DECOMPOSITION CARBON MONOXIDE & ASPHYXIANTS	FLAMMABLE LIMITS: LEL-UEL Not Determined
EXTINGUISHING MEDIA: WATER FOG, CO2, FOAM & DRY CHEMICAL	FLASHPOINT: 240°F
	DOT INFORMATION:

UNUSUAL FIRE AND EXPLOSION HAZARDS: Toxic Fumes, gases, or vapors may evolve in burning

SPECIAL FIRE FIGHTING PROCEDURES: DO NOT ENTER ANY ENCLOSED OR CONFINED AREA WITHOUT PROPER PROTECTIVE EQUIPMENT & SELF-CONTAINED BREATHING APPARATUS.

SECTION IV-PHYSICAL DATA

BOILING RANGE: >200 °C		SOLUBILITY: Insoluble PH		N/A	
VAPOR PRESSURE: <1		APPEARANCE AND ODOR: Red and Faint			
VAPOR DENSITY	EVAPORATION RATE	SPECIFIC GRAVITY	WEIGHT PER GALLON	% VOLATILE BY VOLUME	
Greater THAN AIR	Less THAN ETHER	.89	8.1 lbs	0	

SECTION V-REACTIVITY DATA

INCOMPATIBILITY <MATERIAL TO AVOID>: AVOID CONTACT WITH STRONG OXIDIZERS
STABILITY: STABLE CONDITION TO AVOID: EXTREME HEAT
HAZARDOUS DECOMPOSITION PRODUCTS: CARBON MONOXIDE & ASPHYXIANTS
HAZARDOUS POLYMERIZATION NONE

Division of Southwest Lubricants
 36 Abraham Way Santos, CA 92071
 (619) 449-8000
 EMERGENCY 24 HOURS
 TOLLFREE: 800-424-8300

HEALTH FIRE REACTIVITY
 PERSONAL PROTECTION (NFPA)
 36020022
 36020023
 36020024

SECTION VI-HEALTH HAZARD DATA

ROUTE OF EXPOSURE	ADVERSE AFFECTS		FIRST AID PROCEDURES	NFP
	ING	Not normally expected to cause any ill effects except in very sensitive individuals.	Do not induce vomitting. Consult a physician.	
	INH	No significant adverse health effects are expected to occur on short time exposure.	Remove from contaminated area. Apply artificial respiration. If unconscious consult a physician.	
	ECYEN	Not normally expected to cause any ill effects.	Flush with copious amounts of water.	
	ASCKO UIN TNE	Not normally expected to cause any ill effects.	Wash with soap & water. Consult physician if irritation occurs.	
	CSC HKO RIN ON NIC	Prolonged or repeated contact may produce mild irritation. Personnel with skin disorders should avoid contact.	Wear protective clothing to avoid skin contact. Consult physician if irritation should develop.	

SECTION VII-SPILL OR LEAK PROCEDURES -EPA-

STEPS TO BE TAKEN IN CASE MATERIAL IS RELEASED OR SPILLED: Stop flow. Wipe or mop up or absorb with inert material. Store in appropriate container for disposal.

WASTE DISPOSAL METHOD: In accordance with local, state & federal regulations.

TRANSPORTATION INFORMATION: Consult 46CFR parts 1-300 and refer to section III of this MSDS for additional information.

SECTION VIII-SPECIAL PROTECTION INFORMATION

RESPIRATORY PROTECTION: None normally required.

PROTECTIVE GLOVES: Recommended.

OTHER PROTECTIVE EQUIPMENT: Eye protection recommended.

VENTILATION: Sufficient to maintain atmosphere below TLV limit.

SECTION IX-SPECIAL PRECAUTIONS

PRECAUTION TO BE TAKEN WHEN HANDLING OR STORING: Avoid storage near open flame. Avoid spills as floor becomes very slippery.

PERSONAL HYGIENE: Wash with soap & water.

OTHER PRECAUTIONS: Wash or shower if general contact occurs. Remove oil-soaked clothing & laundry before reuse.

APPROVED BY: Danny Massie, Director

Date: 7/1/04

MAXIMS
A Division of Southwest Lubricants

Formula K2
PRODUCT

22901/22505/22055/22916/22964

