



10969 WHEATLANDS AVE, #A, SANTEE, CA 92071  
CA (619) 449-5000

PU

58932m

58901m


# MATERIAL SAFETY DATA SHEET

Product Code: -Racing Shock Fluid - Medium

Page 1

## HAZARD RATING

N 4 - Extreme  
F 3 - High  
P 2 - Moderate  
A 1 - Slight  
0 - Insignificant



## DIVISION AND LOCATION---SECTION I

### MAXIMA PRODUCTS

10969 Wheatland Ave., Suite A

Santee, CA. 92071

Emergency Telephone No: (619) 449-5000

Transportation Emergency: (Chem Trec 1-(800) 424-9300 (US.S and Canada)

## CHEMICAL AND PHYSICAL PROPERTIES---SECTION II

### Chemical Name:

Petroleum lubricating oil

### Formula:

Complex mixture. CAS not available

### Hazardous Decomposition Products:

Fumes, smoke, carbon monoxide, sulfur oxides, aldehydes

### Incompatibility (Keep away from):

liquid chlorine, concentrated oxygen, sodium hypochlorite or calcium hypochlorite.

### Toxic and Hazardous Ingredients:

none

Form: liquid

Odor: faint petroleum hydrocarbon odor

Appearance: liquid

Color: blue

Specific Gravity (water=1): .86

Boiling Point: IBP approximately 154°C (310°F)

Melting Point: -59°C (-75°F)

Solubility in Water (by weight %): negligible; less than 0.1

Volatile (by weight %): negligible from open container in 4 hrs @ 38°C (100°F)

Evaporation Rate: less than 0.01

Vapor Pressure (mm Hg at 20°C): less than 0.01

Vapor Density (air=1): greater than 5

pH (as is): essentially neutral

Stability: Product stable under normal conditions

Viscosity SUS at 100°F: 26 cSt @ 40°C

## FIRE AND EXPLOSION DATA---SECTION III

### Special Fire Fighting Procedures:

Fire fighters should wear an approved self contained breathing apparatus

### Unusual Fire and Explosion Hazards:

none

(Continued Next Page)



10969 WHEATLANDS AVE, #A, SANTEE, CA 92071  
CA (619) 449-5000

# MATERIAL SAFETY DATA SHEET

Product Code: Racing Shock Fluid - Medium

Page 2

(Section III Continued)

Flashpoint: (Method Used) Cleveland open cup greater than 204°C (400°F)

Flammable limits %: lower .9 upper 7

Extinguishing agents:

Foam, water spray (fog), dry chemical, carbon dioxide  
vaporizing liquid.

## HEALTH HAZARD DATA---SECTION IV

Permissible concentrations (air): If used in application where mist may be generated,  
observe TWA/PEL mg/m3 for oil mist in area (OSHA)

Chronic effects of overexposure:

Prolonged skin contact may cause dermatitis (skin irritation)

Acute toxicological properties:

no data available

Emergency First Aid procedures:

Eyes: Immediately flush for 15 minutes with water, call a physician

Skin Contact: Remove excess with cloth or paper. Wash thoroughly with soap & water.

Inhalation: Remove exposed person to fresh air.

If Swallowed: DO NOT induce vomiting. Call a physician

## ECAL PROTECTION INFORMATION---SECTION V

Ventilation Type Required (Local, mechanical, special):

Local exhaust to capture vapor, mist or fume if necessary.

Respiratory Protection (Specify type):

Use supplied-air respiratory protection in confined or enclosed area.

Protective Gloves: Chemical resistant gloves

Eye Protection: Chemical resistant goggles

Other Protective Equipment:

Chemical resistant apron if necessary

## HANDLING OF SPILLS OR LEAKS---SECTION VI

Procedures for Clean-Up: Transfer bulk of mixture into another container. Absorb residue  
with inert material such as earth, sand, or vermiculite. Sweep up and dispose  
in accordance with local, state and federal regulations. Open all windows and  
doors. Keep product out of sewers and watercourses.

Waste Disposal:

Dispose of in accordance with all applicable federal, state and local  
regulations.

(Continued Next Page)



10969 WHEATLANDS AVE, #A, SANTEE, CA 92071  
CA (619) 449-5000

MATERIAL SAFETY DATA SHEET

Product Code: Racing shock Fluid - Medium

Page 3

SPECIAL PRECAUTIONS---SECTION VII

Precautions to be taken in handling and storage: Keep containers and storage containers closed when not in use. Avoid prolonged or repeated contact with skin or breathing of vapors. Use product with caution around heat, sparks, pilot lights, static electricity and open flame.

TRANSPORTATION DATA---SECTION VIII

D.O.T.: not applicable

Reportable Quantity: not applicable

Freight Classification: petroleum lubricating oil

Special Transportation Notes:

none

COMMENTS---SECTION IX

Signature: RICHARD D. LECHIEN

Title: President

Date:

Revision Date:

Supersedes:

Sent To:

Date: \_\_\_\_\_

We believe the statements, technical information and recommendations contained herein are reliable, but they are given without warranty or guarantee of any kind, express or implied, and we assume no responsibility for any loss, damage, or expense, direct or consequential, arising out of their use.