US



Printing date 03/22/2016

Reviewed on 03/22/2016

#### 1 Identification

#### · Product identifier

- · Trade name: CHAINLUBE RACING SPRAY
- Application of the substance / the mixture
   Only for proper handling.
   Chain lubricant
- Details of the supplier of the safety data sheet
   Manufacturer/Supplier:

BUCHER\_AG\_LANGENTHAL MOTOREX–Schmiertechnik Bern–Zürich–Strasse\_31\_\_ CH–4901\_Langenthal\_\_ Telefon\_+41\_(0)62\_919\_75\_75

Lube-Tech Lubrication Technologies, Inc. 900 Mendelssohn Avenue North US-55427 Golden Valley, Minnesota Phone: 001 763 417 1357

· Information department: <u>msds@motorex.com</u>

• *Emergency telephone number:* Toxicological Information Centre CH-8028 Zurich <u>info@toxi.ch</u> T. +41 (0)44 251 51 51 USA + Kanada: 1 800 424 9300 (Chemtrec Chemical Manufacturers Association, Arlington, VA 22209)

Safety Data Sheet acc. to OSHA HCS

#### 2 Hazard(s) identification

Classification of the substance or mixture					
GHS02 F	-lame				
Flam. Aerosol 1	H222-H229	Extremely flammable aerosol. Pressurized container: May burst if heated.			
GHS07					
Skin Irrit. 2	H315	Causes skin irritation.			
STOT SE 3	H336	May cause drowsiness or dizziness.			
Aquatic Acute 3	H402	Harmful to aquatic life.			
Aquatic Chronic 3	H412	Harmful to aquatic life with long lasting effects.			
<ul> <li>Label elements</li> <li>GHS label element</li> <li>The product is class</li> </ul>		beled according to the Globally Harmonized System (GHS). (Contd. on page 2)			

Reviewed on 03/22/2016

#### Safety Data Sheet acc. to OSHA HCS Printing date 03/22/2016 Trade name: CHAINLUBE RACING SPRAY (Contd. of page 1) · Hazard pictograms GHS02 GHS07 · Signal word Danger · Hazard-determining components of labeling: Hydrocarbons, C7-C9, n-alkanes, isoalkanes, cyclics Hydrocarbons C6-C7, n-alkanes, iso-alkanes, cyclenes, <5% n-hexane · Hazard statements H222-H229 Extremely flammable aerosol. Pressurized container: May burst if heated. Causes skin irritation. H315 H336 May cause drowsiness or dizziness. H402 Harmful to aquatic life. Harmful to aquatic life with long lasting effects. H412 · Precautionary statements Keep away from heat/sparks/open flames/hot surfaces. No smoking. P210 P251 Do not pierce or burn, even after use. Do not spray on an open flame or other ignition source. P211 Avoid breathing dust/fume/gas/mist/vapors/spray P261 P280 Wear protective gloves. Avoid release to the environment. P273 Wash thoroughly after handling. P264 P271 Use only outdoors or in a well-ventilated area. P321 Specific treatment (see on this label). P304+P340 IF INHALED: Remove person to fresh air and keep comfortable for breathing. P312 Call a POISON CENTER/doctor if you feel unwell. P332+P313 If skin irritation occurs: Get medical advice/attention. P302+P352 IF ON SKIN: Wash with plenty of water. P362+P364 Take off contaminated clothing and wash it before reuse. P405 Store locked up. P410+P412 Protect from sunlight. Do not expose to temperatures exceeding 50°C/122°F. P403+P233 Store in a well-ventilated place. Keep container tightly closed. Dispose of contents/container in accordance with local/regional/national/ P501 international regulations. · Classification system: NFPA ratings (scale 0 - 4) Health = 1Fire = 4Reactivity = 3· HMIS-ratings (scale 0 - 4) HEALTH 1 Health = 1FIRE 4 Fire = 4Reactivity = 3REACTIVITY 3 · Other hazards · Results of PBT and vPvB assessment · PBT: Not applicable. · vPvB: Not applicable.

(Contd. on page 3)

## Safety Data Sheet

acc. to OSHA HCS

Printing date 03/22/2016

Reviewed on 03/22/2016

Trade name: CHAINLUBE RACING SPRAY

(Contd. of page 2)

#### 3 Composition/information on ingredients

· Chemical characterization: Mixtures

· **Description:** Mixture of the substances listed below with nonhazardous additions.

<ul> <li>Dangerous components:</li> </ul>		
CAS: 106-97-8 Reg.nr.: 01-2119474691-32	butane	10-25%
CAS: 9044-17-1	Butene, polymer with 2-methyl-1-propene	10-25%
CAS: 64745-49-0 Reg.nr.: 01-2119473851-33-xxxx	Hydrocarbons, C7-C9, n-alkanes, isoalkanes, cyclics Flam. Liq. 2, H225; S Asp. Tox. 1, H304; STOT SE 3, H336	10-25%
Reg.nr.: 01-2119475514-35-xxxx	Hydrocarbons C6-C7, n-alkanes, iso-alkanes, cyclenes, <5% n-hexane	10-25%
CAS: 64742-46-7 Reg.nr.: 01-2119827000-58	Hydrocarbons, C15-C20 n-alkanes, isoalkanes, cycloalkanes, <0.03% aromatics � Asp. Tox. 1, H304	5-10%
CAS: 74-98-6 Reg.nr.: 01-2119486944-21	propane 🚸 Flam. Gas 1, H220; Press. Gas, H280	2.5-7.5%
Reg.nr.: 01-2119453414-43	Hydrocarbons, C12-C15, n-alkanes, isoalkanes, cycloalkanes, <2% aromatics � Asp. Tox. 1, H304	2.5-7.5%
Reg.nr.: 01-2119826592-36	Hydrocarbons, C13-C16, n-alkanes, isoalkanes, cycloalkanes, <12:03% aromatics � Asp. Tox. 1, H304	2.5-7.5%

#### 4 First-aid measures

· Description of first aid measures

- General information: Immediately remove any clothing soiled by the product.
- After inhalation:
- In case of unconsciousness place patient stably in side position for transportation. • After skin contact:
- Remove residues with soap and water.
- Immediately wash with water and soap and rinse thoroughly.
- · After eye contact: Rinse opened eye for several minutes under running water.
- After swallowing: If symptoms persist consult doctor.
- · Information for doctor:
- *Most important symptoms and effects, both acute and delayed* No further relevant information available.
- *Indication of any immediate medical attention and special treatment needed* No further relevant information available.

(Contd. on page 4)

US

#### Safety Data Sheet acc. to OSHA HCS

Printing date 03/22/2016

Reviewed on 03/22/2016

#### Trade name: CHAINLUBE RACING SPRAY

(Contd. of page 3)

#### 5 Fire-fighting measures

- · Extinguishing media
- Suitable extinguishing agents:
- CO2, extinguishing powder or water spray. Fight larger fires with water spray or alcohol resistant foam.
- · Special hazards arising from the substance or mixture No further relevant information available.
- · Advice for firefighters
- · Protective equipment: No special measures required.

#### 6 Accidental release measures

- · Personal precautions, protective equipment and emergency procedures Wear protective equipment. Keep unprotected persons away.
- · Environmental precautions: Do not allow product to reach sewage system or any water course. Inform respective authorities in case of seepage into water course or sewage system. Do not allow to enter sewers/ surface or ground water.
- · Methods and material for containment and cleaning up: Dispose contaminated material as waste according to item 13. Ensure adequate ventilation.
- · Reference to other sections See Section 7 for information on safe handling. See Section 8 for information on personal protection equipment. See Section 13 for disposal information.

#### 7 Handling and storage

#### · Handling:

- · Precautions for safe handling Ensure good ventilation/exhaustion at the workplace.
- · Information about protection against explosions and fires: Keep ignition sources away - Do not smoke.

Pressurized container: protect from sunlight and do not expose to temperatures exceeding 50 °C, i.e. electric lights. Do not pierce or burn, even after use. Do not spray on a naked flame or any incandescent material.

- Conditions for safe storage, including any incompatibilities
- · Storage:
- Requirements to be met by storerooms and receptacles: Observe official regulations on storing packagings with pressurized containers.
- Information about storage in one common storage facility: Not required.
- · Further information about storage conditions: Keep receptacle tightly sealed. Storage class: 2 B
- Specific end use(s) No further relevant information available.

#### 8 Exposure controls/personal protection

· Additional information about design of technical systems: No further data; see item 7. (Contd. on page 5)

#### Safety Data Sheet acc. to OSHA HCS

Printing date 03/22/2016

#### Reviewed on 03/22/2016

#### Trade name: CHAINLUBE RACING SPRAY

(Contd. of page 4)

· Control µ	parameters
-------------	------------

· Components with limit values that require monitoring at the workplace:

#### 106-97-8 butane

REL Long-term value: 1900 mg/m<sup>3</sup>, 800 ppm

TLV Short-term value: 2370 mg/m<sup>3</sup>, 1000 ppm

#### 74-98-6 propane

PEL Long-term value: 1800 mg/m<sup>3</sup>, 1000 ppm

REL Long-term value: 1800 mg/m<sup>3</sup>, 1000 ppm

TLV refer to Appendix F inTLVs and BEIs book

· Additional information: The lists that were valid during the creation were used as basis.

#### · Exposure controls

#### · Personal protective equipment:

 General protective and hygienic measures: Keep away from foodstuffs, beverages and feed. Immediately remove all soiled and contaminated clothing. Wash hands before breaks and at the end of work. Avoid contact with the skin. Avoid contact with the eyes and skin.

#### · Breathing equipment:

In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use respiratory protective device that is independent of circulating air.

#### · Protection of hands:



Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

• Material of gloves

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

#### · Penetration time of glove material

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

• Eye protection: Not required.

#### 9 Physical and chemical properties

· Information on basic physical and chemical properties

- General Information
- · Appearance:

Form:

Color: Odor: Liquefied gas Beige Solvent-like

(Contd. on page 6)

# Safety Data Sheet acc. to OSHA HCS

Printing date 03/22/2016

Reviewed on 03/22/2016

#### Trade name: CHAINLUBE RACING SPRAY

	(Contd. of page 5
· Odor threshold:	Not determined.
· pH-value:	Not determined.
<ul> <li>Change in condition Melting point/Melting range: Boiling point/Boiling range:</li> </ul>	Undetermined. Not applicable, as aerosol.
· Flash point:	< -20 °C (< -4 °F)
· Flammability (solid, gaseous):	Not applicable.
· Ignition temperature:	> 230 °C (> 446 °F) (DIN 51794)
· Decomposition temperature:	Not determined.
· Auto igniting:	Product is not selfigniting.
· Danger of explosion:	Product is not explosive. However, formation of explosive air/vapor mixtures are possible.
· Explosion limits: Lower: Upper:	0.9 Vol % 8.5 Vol %
· Vapor pressure at 20 °C (68 °F):	2100 hPa (1575 mm Hg)
<ul> <li>Density at 20 °C (68 °F):</li> <li>Relative density</li> <li>Vapor density</li> <li>Evaporation rate</li> </ul>	0.756 g/cm³ (6.309 lbs/gal) (ASTM D 4052) Not determined. Not determined. Not applicable.
<ul> <li>Solubility in / Miscibility with Water:</li> </ul>	Not miscible or difficult to mix.
· Partition coefficient (n-octanol/wat	er): Not determined.
<ul> <li>Viscosity:</li> <li>Dynamic:</li> <li>Kinematic:</li> <li>VOC content:</li> </ul>	Not determined. < 50 mm²/s @40 °C (DIN 51562-1) 50.0 % 378.0 g/l / 3.15 lb/gl
· Other information	No further relevant information available.

## 10 Stability and reactivity

- · Reactivity No further relevant information available.
- · Chemical stability
- · Thermal decomposition / conditions to be avoided:
- No decomposition if used according to specifications.
- · Possibility of hazardous reactions No dangerous reactions known.
- · Conditions to avoid No further relevant information available.
- · Incompatible materials: No further relevant information available.
- · Hazardous decomposition products: No dangerous decomposition products known.

(Contd. on page 7)

us

## Safety Data Sheet

acc. to OSHA HCS

Printing date 03/22/2016

Reviewed on 03/22/2016

#### Trade name: CHAINLUBE RACING SPRAY

(Contd. of page 6)

3

## 11 Toxicological information

- · Information on toxicological effects
- Acute toxicity:

· LD/LC50 values that are relevant for classification:

64742-46-7 Hydrocarbons, C15-C20 n-alkanes, isoalkanes, cycloalkanes, <0.03% aromatics

Oral LD50 2000 mg/kg (rat)

Dermal LD50 2000 mg/kg (rabbit)

#### · Primary irritant effect:

- on the skin: Irritant to skin and mucous membranes.
- · on the eye: No irritating effect.
- · Sensitization: No sensitizing effects known.

· Additional toxicological information:

The product shows the following dangers according to internally approved calculation methods for preparations: *Irritant* 

· Carcinogenic categories

· IARC (International Agency for Research on Cancer)

9002-84-0 Polytetrafluoroethylene

· NTP (National Toxicology Program)

None of the ingredients is listed.

· OSHA-Ca (Occupational Safety & Health Administration)

None of the ingredients is listed.

### 12 Ecological information

- · Toxicity
- · Aquatic toxicity: No further relevant information available.
- · Persistence and degradability No further relevant information available.
- · Behavior in environmental systems:
- · Bioaccumulative potential No further relevant information available.
- · Mobility in soil No further relevant information available.
- Ecotoxical effects:
- · Remark: Harmful to fish
- · Additional ecological information:
- · General notes:

Water hazard class 2 (Self-classification according VwVwS, 17.05.1999): hazardous for water

Do not allow product to reach ground water, water course or sewage system. Danger to drinking water if even small guantities leak into the ground.

- Harmful to aquatic organisms
- · Results of PBT and vPvB assessment
- · PBT: Not applicable.
- · vPvB: Not applicable.
- Other adverse effects No further relevant information available.

(Contd. on page 8)

# Safety Data Sheet acc. to OSHA HCS

Printing date 03/22/2016

Reviewed on 03/22/2016

#### Trade name: CHAINLUBE RACING SPRAY

(Contd. of page 7)

## 13 Disposal considerations

- · Waste treatment methods
- **Recommendation:** Must not be disposed of together with household garbage. Do not allow product to reach sewage system.
- · Uncleaned packagings:
- · Recommendation:
- Disposal must be made according to official regulations.
- Discharged containers can contain flammable or explosive vapours.

UN-Number DOT, ADR,ADN, IMDG, IATA	UN1950	
UN proper shipping name	011930	
DOT, IATA	Aerosols, flammable	
ADR/ADN	1950 Aerosols	
IMDG	AEROSOLS	
Transport hazard class(es)		
DOT		
Class	2.1	
Label	2.1	
ADR/ADN		
	0.550	
Class Label	2 5F Gases 2.1	
	2.1	
IMDG, IATA		
Class	2.1	
Label	2.1	
Packing group		
DOT, ADR,ADN, IMDG, IATA	Void	
Environmental hazards:		
Marine pollutant:	No	
Special precautions for user	Warning: Gases	
Danger code (Kemler):		

Printing date 03/22/2016

Reviewed on 03/22/2016

Trade name: CHAINLUBE RACING SPRAY

	(Contd. of page 8
EMS Number: Stowage Code Segregation Code	F-D,S-U SW1 Protected from sources of heat. SW22 For AEROSOLS with a maximum capacity of 1 litre: Category A. Fo AEROSOLS with a capacity above 1 litre Category B. For WASTE AEROSOLS Category C, Clear of living quarters. SG69 For AEROSOLS with a maximum capacity of 1 litre: Segregation as for class 9 Stow "separated from" class 1 except fo division 1.4. For AEROSOLS with a capacity above 1 litre: Segregation as for the appropriate subdivision of class 2. Fo WASTE AEROSOLS: Segregation as for the appropriate subdivision of class 2.
Transport in bulk according to Annex I MARPOL73/78 and the IBC Code	ll of Not applicable.
• Transport/Additional information:	
ADR/ADN Excepted quantities (EQ)	Code: E0 Not permitted as Excepted Quantity
· IMDG · Limited quantities (LQ) · Excepted quantities (EQ)	1L Code: E0 Not permitted as Excepted Quantity
· UN "Model Regulation":	UN 1950 AEROSOLS, 2.1

## 15 Regulatory information

 Safety, health and environmental regulations/legislation specific for the substance or mixture
 Sara

· Section 355 (extremely hazardous substances): None of the ingredients is listed. · Section 313 (Specific toxic chemical listings): None of the ingredients is listed. · TSCA (Toxic Substances Control Act): 106-97-8 butane 9044-17-1 Butene, polymer with 2-methyl-1-propene 64745-49-0 Hydrocarbons, C7-C9, n-alkanes, isoalkanes, cyclics 64742-46-7 Hydrocarbons, C15-C20 n-alkanes, isoalkanes, cycloalkanes, <0.03% aromatics 9002-84-0 Polytetrafluoroethylene 74-98-6 propane 75-28-5 isobutane 78-78-4 isopentane 95-38-5 2-(2-heptadec-8-enyl-2-imidazolin-1-yl)ethanol (Contd. on page 10)

(Contd. of page 9)

#### Safety Data Sheet acc. to OSHA HCS

Printing date 03/22/2016

#### Reviewed on 03/22/2016

#### Trade name: CHAINLUBE RACING SPRAY

110-25-8 N-Oleoyl-sarcosid

Proposition 65

· Chemicals known to cause cancer:

None of the ingredients is listed.

· Chemicals known to cause reproductive toxicity for females:

None of the ingredients is listed.

· Chemicals known to cause reproductive toxicity for males:

None of the ingredients is listed.

· Chemicals known to cause developmental toxicity:

None of the ingredients is listed.

#### · Carcinogenic categories

· EPA (Environmental Protection Agency)

None of the ingredients is listed.

· TLV (Threshold Limit Value established by ACGIH)

None of the ingredients is listed.

· NIOSH-Ca (National Institute for Occupational Safety and Health)

None of the ingredients is listed.

· Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

#### 16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

· Department issuing SDS: Abteilung Produktsicherheit

· Date of preparation / last revision 03/22/2016 / -

 Abbreviations and acronyms: Flam. Gas 1: Flammable gases, Hazard Category 1 Flam. Aerosol 1: Flammable aerosols, Hazard Category 1 Press. Gas: Gases under pressure: Compressed gas

- Flam. Liq. 2: Flammable liquids, Hazard Category 2
- Skin Irrit. 2: Skin corrosion/irritation, Hazard Category 2 STOT SE 3: Specific target organ toxicity - Single exposure, Hazard Category 3
- Asp. Tox. 1: Aspiration hazard, Hazard Category 1

Aquatic Acute 2: Hazardous to the aquatic environment - AcuteHazard, Category 2

Aquatic Acute 3: Hazardous to the aquatic environment - AcuteHazard, Category 3

Aquatic Chronic 2: Hazardous to the aquatic environment - Chronic Hazard, Category 2 Aquatic Chronic 3: Hazardous to the aquatic environment - Chronic Hazard, Category 3