COPPER ANTI-SEIZE Spray (US

Version)



Date of issue / Reference Replaces version of 20.04.2003 uh

Date of printing 24.04.2003 **Sheet No. 1504** Page 1 of 5

Company BUCHER AG LANGENTHAL, MOTOREX-Schmiertechnik, CH-4901

Langenthal

1 Commercial product name and supplier

1.1 Commercial product name /

**COPPER ANTI-SEIZE Spray (US Version)** 

Designation

1.2 Application / Use Lubrication, anticorrosive

1.3 Producer BUCHER AG LANGENTHAL, MOTOREX-Schmiertechnik, CH-4901

Langenthal

Telefon +41 (0)62 919 75 75, Fax +41 (0)62 919 75 95

1.4 Supplier BUCHER AG MOTOREX, Inc., dba: MOTOREX USA, 1932 Eastman

Avenue, Suite 107, Ventura, CA 93003-5766

Tel. 805-658-0900 Fax: 805-658-0910

1.5 TOX emergency number Europe: +41 (0)1 251 51 51 (Center of Toxicology Information, CH-8028

Zurich)

North America:

1.6 Product No.

2 Composition

2.1 Chemical characterization Copper

Petrol fraction (aromatics <0,5%) Mineral oil, paraffinic (CAS# 8042-47-5)

Lithium soap

Propane/butane (propellant)

2.2 Hazardous components Dangerous substances according to the criteria of the EC (Council

Directive 88/379/EEC):

CAS No. 64742-49-0 45-55 % Naphtha, hydrogenated, light: benzene <0.1%

Xn: Harmful. F: Highly flammable. N: Dangerous for the environment. R11: Highly flammable. R65: Harmful: may cause lung damage if swallowed. R51/53: Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic

environment.

CAS No. 74-98-6 Propane

F+: Extremely flammable. R12: Extremely flammable.

CAS No. 106-97-8 Butane

F+: Extremely flammable. R12: Extremely flammable.

2.3 Further information

3 Hazards identification Extremely flammable.

Can is under pressure. Protect from direct sunlight and temperatures

above 50°C (122°F). Do not pierce or burn can after use. Do not spray

towards flame or incandescent object.

Keep away from sources of ignition - No smoking. Keep out of the

reach of children.

## COPPER ANTI-SEIZE Spray (US

Version)



Date of issue / Reference Replaces version of

20.04.2003 uh

Date of printing 24.04.2003 Sheet No. 1504 Page 2 of 5

	1 0			
4	1 First aid measures No adverse effects anticipated by this route of exposure inciproper industrial handling.			
4.1	Eye contact	Flush eyes with plenty of water.		
4.2	Skin contact	Remove residues with soap and water.		
4.3	Ingestion			
4.4	Inhalation	Take into fresh air.		
4.5	Further information			
5	Fire-fighting measures			
5.1	Suitable extinguishing media	Carbon dioxide, dry chemical and protein based foam.		
5.2	Extinguishing media to avoid	Water spray.		
5.3	Further information	None.		
6	Accidental release measures	Spills should be contained by, and covered with suitable absorbent material and removed for disposal.		
7	Handling and storage			
7.1	Handling	Do not spray towards flame or incandescent object. Keep away from sources of ignition - No smoking.		
7.2	Industrial hygiene	Avoid breathing mists.		
7.3	Storage	Protect from direct sunlight and temperatures above 50°C (122°F). Keep out of the reach of children.		
7.4	Place of storage			
7.5	Fire- and explosion-protection	Use only if ventilation is good.		
8	Exposure controls / Personal protect	tion		
8.1	Technical measures	Good general ventilation should be sufficient for most processing operations.		
8.2	Control of threshold limits	None established for the mixture.		
8.3	Personal protective equipment			
8.3.1	Respiratory protection	None required.		
8.3.2	Hand protection	None required.		
8.3.3	Eye protection	None required.		
8.3.4	Other			

COPPER ANTI-SEIZE Spray (US

Sheet No. 1504

Version)



Date of issue / Reference Replaces version of

9.13 Further information

Date of printing

20.04.2003 uh

24.04.2003

Page 3 of 5

9	Dharical and shamical mean sation						
9.1	Physical and chemical properties  Appearance	liquified g	ac				
9.2	Colour	gold	as				
9.3	Odour	solvent					
9.4	Change of physical state	551,6110			Test method:		
···	onange of physical state				1000 11101110		
9.5	Density						
		0.572 g/cn	$n^3 (20^{\circ}C)$	ISO 3675			
9.6	Vapour pressure						
7.0	vapour pressure	3200 mbar	·(20°C)				
			( )				
9.7	Viscosity						
7.1	, is costly						
			.1.1.				
9.8	Colubility	not applic	able				
9.0	in water	olubility					
	iii watei	insoluble					
9.9	pH						
	•						
		not applic	able				
9.10	Flash point	<0 °C					
9.11	Ignition temperature	500 °C					
	C						
9.12	Explosion limits	Lower:	2,1 Vol%	((1013 mbar))			
		Upper:	9,5 Vol%	((//			

COPPER ANTI-SEIZE Spray (US

Version)



Date of issue / Reference Replaces version of

20.04.2003 uh

Date of printing		24.04.2003	Sheet No.	. 1504	Page 4 of 5	
10	Stability and reactivity					
10.1	Thermal decomposition	Stable under recommended storage conditions.				
10.2	Hazardous decomposition products	None under normal conditions of storage and use.				
10.3	Hazardous reactions	No hazards known.				
10.4	Further information					
11	Toxicological information					
11.1	Acute toxicity	No relevant information found.				
11.2	Subacute / Chronic toxicity					
11.3	Further information					
12	Ecological information	German 'Wassergefaehrdungs Klasse (WGK)': 2				
13	Disposal considerations	Comply with local and national regulations.				
13.1	EU waste key	16 01 99 Waste o.n.s				
14	Transport information		_			
14.1	Transport at land	ADR	2	RID 2		
		UN Number	1950	Kemler Number		
		Packing Group Proper shipping name Aerosols, flammable,		Aerosols, flammable, n.o.s.		
142	Tananantatan		5 marrie			
14.2	Transport at sea	ADNR		IMDG		
		UN Number	1950			
		EMS Packing Group	2-13	MFAG 6	20	
		Proper shipping		Aerosols, flammable, n.o.s.		
14.3	Air transport	ICAO / IATA-I	OGR	2.1		
14.5	711 dansport	UN Number	JOR	1950		
		Packing Group				
		Proper shipping name		Aerosols, flammable, n.o.s.		
	Passenger airplane	Packing Instru	ctions	Y203		
		max.		30 kg G		
	Cargo Airplane	Packing Instru	ctions	203		

max.

75 kg

COPPER ANTI-SEIZE Spray (US Version)



Date of issue / Reference Replaces version of Date of printing 20.04.2003 uh

24.04.2003 **Sheet No. 1504** 

Page 5 of 5

15 Regulatory information

Further information

This product requires classification according to the criteria of the

EC and the "Gefahrstoffverordnung".

The product is classified for transportation.

15.1 UN number

14.4

1950

15.2 National regulations

15.3 EU number

15.4 Hazard symbols



15.5 Hazard designation

F+: Extremely flammable. Contains Propane, Butane, Naphtha,

hydrogenated, light: benzene <0.1%.

15.6 Risk phrases

R: 12

12

Extremely flammable.

15.7 Safety phrases

15.8 MAK value

15.9 BVD classification (CH)

15.10 VbF (D)

15.11 Further information

16 Other information

No other information.

The above mentioned data correspond to our present state of knowledge and experience. The safety data sheet serves as description of the products in regard to necessary safety measures. The indications do not have the meaning of guarantees on properties.

This safety data sheet has been generated with the safety database 'ChemManager',

© ASSiST Applied Software Solutions in Science and Technology AG, Weiherweg 3, CH-4104 Oberwil, Switzerland

91/155/EEC