

1. Product and Company Identification

Material name	Bel-Ray 6 in 1
Product Code	99020
MSDS Number	6429
Version #	1.0
Revision date	06-18-2010
Product use	Lubricant
Manufacturer information	Bel-Ray Company, Inc. P.O. Box 526 Farmingdale, NJ 07727 United States of America +1 732 938 2421 CHEMTREC: +1 703-527-3887 (outside USA) CHEMTREC: 800-424-9300 (USA)

2. Hazards Identification

Emergency overview	DANGER	
	Combustible liquid and vapor. CONTENTS UNDER PRESSURE. Aerosol. Pressurized container may explode when exposed to heat or flame. Vapors may cause a flash fire or ignite explosively.	
	Cancer hazard. Irritating to skin. Irritating to eyes. This is a consumer care product that is safe for consumers when used according to the label directions. Like many consumer products, a small number of individuals may experience reactions such as redness, rash and / or swelling upon prolonged or repeated skin contact or eye contact.	
OSHA regulatory status	This product is considered hazardous under 29 CFR 1910.1200 (Hazard Communication).	
Potential health effects		
Routes of exposure	Inhalation. Ingestion. Skin contact. Eye contact.	
Eyes	Causes eye irritation. Avoid contact with eyes.	
Skin	Irritating to skin. May be harmful if absorbed through skin. Frequent or prolonged contact may defat and dry the skin, leading to discomfort and dermatitis. Do not get this material in contact with skin.	
Inhalation	Intentional misuse by concentrating and inhaling the product can be harmful or fatal. May be irritating. May cause cancer by inhalation. Prolonged inhalation may be harmful. Avoid breathing dust/fume/gas/mist/vapors/spray.	
Ingestion	Exposure by ingestion of an aerosol is unlikely. Components of the product may be absorbed into the body by ingestion. Do not ingest. Small amounts of this product, if aspirated into the lungs, may cause mild to severe pulmonary injury.	
Target organs	Blood. Liver. Skin. Upper respiratory tract.	
	2-Butoxy ethanol may be absorbed through the skin in toxic amounts if contact is repeated and prolonged and may cause blood damage. These effects have not been observed in humans.	
	Kidneys. Central nervous system.	
Chronic effects	Unconsciousness. Edema. Jaundice. Cyanosis (blue tissue condition, nails, lips, and/or skin). May be harmful if absorbed through skin. Liver injury may occur. Kidney injury may occur. May cause central nervous system disorder (e.g., narcosis involving a loss of coordination, weakness, fatigue, mental confusion and blurred vision) and/or damage. Frequent or prolonged contact may defat and dry the skin, leading to discomfort and dermatitis.	
Signs and symptoms	Unconsciousness. Narcosis. Cyanosis (blue tissue condition, nails, lips, and/or skin). Decrease in motor functions. Behavioral changes. Edema. Liver enlargement. Jaundice. Proteinuria. Irritation of nose and throat. Irritation of eyes and mucous membranes. Defatting of the skin. Skin irritation. Rash.	

Components of this product are hazardous to aquatic life. May cause long-term adverse effects in the environment.

3. Composition / Information on Ingredients

Hazardous components	CAS #	Percent
STODDARD SOLVENT	8052-41-3	20 - 40
CARBON DIOXIDE	124-38-9	2.5 - 10
1,2,4-TRIMETHYLBENZENE	95-63-6	1 - 2.5
2-BUTOXYETHANOL	111-76-2	1 - 2.5
METHYL ETHYL BENZENE, ALL ISOMERS	25550-14-5	1 - 2.5
TRIMETHYLBENZENE AND ALL ISOMERS, EXCLUDING 1,2,4-TRIMETHYLBENZENE [CAS RN 95-63-6]	25551-13-7	1 - 2.5
XYLENE (MIXED ISOMERS)	1330-20-7	1 - 2.5
ETHYLBENZENE	100-41-4	0.1 - 1
Non-hazardous components	CAS #	Percent
Interchangeable base oils, one or more: 64741-88-4, 64742-54-7, 64742-65-0		20 - 40

4. First Aid Measures

First aid procedures		
Eye contact	Immediately flush eyes with plenty of water for at least 15 minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Get medical attention if irritation develops and persists.	
Skin contact	Take off immediately all contaminated clothing. Wash off with warm water and soap. Get medica attention if irritation develops and persists. For minor skin contact, avoid spreading material on unaffected skin.	
Inhalation	Move to fresh air. Oxygen or artificial respiration if needed. Do not use mouth-to-mouth method if victim inhaled the substance. Induce artificial respiration with the aid of a pocket mask equipped with a one-way valve or other proper respiratory medical device. Call a physician if symptoms develop or persist.	
Ingestion	Rinse mouth thoroughly. Do not induce vomiting. If vomiting occurs, keep head low so that stomach content doesn't get into the lungs. Do not use mouth-to-mouth method if victim ingested the substance. Induce artificial respiration with the aid of a pocket mask equipped with a one-way valve or other proper respiratory medical device. In the unlikely event of swallowing contact a physician or poison control center.	
Notes to physician	In case of shortness of breath, give oxygen. Keep victim warm. Keep victim under observation. Symptoms may be delayed.	
General advice	IF exposed or concerned: Get medical advice/attention. In case of shortness of breath, give oxygen. Keep victim warm. Keep victim under observation. Ensure that medical personnel are aware of the material(s) involved, and take precautions to protect themselves.	
5. Fire Fighting Measures		
Flammable properties	Combustible by OSHA criteria. Heat may cause the containers to explode. Vapors may travel considerable distance to a source of ignition and flash back. Runoff to sewer may cause fire or explosion hazard.	
Extinguishing media		
Suitable extinguishing media	Water. Water spray. Foam. Dry powder. Carbon dioxide (CO2).	
Unsuitable extinguishing media	Do not use a solid water stream as it may scatter and spread fire.	
Protection of firefighters		
Specific hazards arising from the chemical	Fire may produce irritating, corrosive and/or toxic gases.	
Fire fighting equipment/instructions	Not available.	

Specific methods	In the event of fire and/or explosion do not breathe fumes. Cool containers exposed to flames with water until well after the fire is out.	
Hazardous combustion products	May include oxides of nitrogen. Carbon monoxide and carbon dioxide.	
6. Accidental Release Me	asures	
Personal precautions	Keep unnecessary personnel away. Keep upwind. Keep out of low areas. Keep people away from and upwind of spill/leak. Ventilate closed spaces before entering them. Do not touch damaged containers or spilled material unless wearing appropriate protective clothing. In case of spills, beware of slippery floors and surfaces.	
Environmental precautions	Prevent further leakage or spillage if safe to do so. Do not contaminate water.	
Methods for containment	ELIMINATE all ignition sources (no smoking, flares, sparks or flames in immediate area). Stop leak if you can do so without risk. Move the cylinder to a safe and open area if the leak is irreparable. Use water spray to reduce vapors or divert vapor cloud drift.	
Methods for cleaning up	Should not be released into the environment. Use a non-combustible material like vermiculite, sand or earth to soak up the product and place into a container for later disposal.	
	Small Spills: Wipe up with absorbent material (e.g. cloth, fleece). Clean surface thoroughly to remove residual contamination. Following product recovery, flush area with water.	
7. Handling and Storage		
Handling Storage	Pressurized container: Do not pierce or burn, even after use. Do not spray on a naked flame or any other incandescent material. Do not smoke while using or until sprayed surface is thoroughly dry. DO NOT handle, store or open near an open flame, sources of heat or sources of ignition. Protect material from direct sunlight. Do not cut, weld, solder, drill, grind, or expose containers to heat, flame, sparks, or other sources of ignition. All equipment used when handling the product must be grounded. Ground and bond containers when transferring material. Do not use if spray button is missing or defective. Do not re-use empty containers. Do not get this material in contact with skin. Avoid breathing dust/fume/gas/mist/vapors/spray. Avoid contact with eyes. Use only in area provided with appropriate exhaust ventilation. Avoid prolonged exposure. Wash thoroughly after handling. Avoid release to the environment. Level 1 Aerosol.	
	Contents under pressure. The pressure in sealed containers can increase under the influence of heat. Do not expose to heat or store at temperatures above 120°F/49°C as can may burst. Do not puncture, incinerate or crush. Do not handle or store near an open flame, heat or other sources of ignition. This material can accumulate static charge which may cause spark and become an ignition source. Avoid exposure to long periods of sunlight. Refrigeration recommended. Store in a well-ventilated place. Keep away from food, drink and animal feedingstuffs. Keep out of the reach of children. Use care in handling/storage.	

8. Exposure Controls / Personal Protection

Occupational exposure limits

ACGIH Components Туре Value Form TWA 1,2,4-TRIMETHYLBENZENE (95-63-6) 25.0000 ppm 2-BUTOXYETHANOL (111-76-2) TWA 20.0000 ppm STEL CARBON DIOXIDE (124-38-9) 30000.0000 ppm TWA 5000.0000 ppm STEL ETHYLBENZENE (100-41-4) 125.0000 ppm TWA 100.0000 ppm Interchangeable base oils, one or more: 64741-88-4, STEL 10.0000 mg/m3 Mist. 64742-54-7, 64742-65-0 TWA 5.0000 mg/m3 Mist. STODDARD SOLVENT (8052-41-3) TWA 100.0000 ppm TRIMETHYLBENZENE AND ALL ISOMERS, EXCLUDING TWA 25.0000 ppm 1,2,4-TRIMETHYLBENZENE [CAS RN 95-63-6] (25551-13-7)STEL XYLENE (MIXED ISOMERS) (1330-20-7) 150.0000 ppm TWA 100.0000 ppm

Components		Туре	Value	Form
1,2,4-TRIMETHYLBENZENE (9	5-63-6)	TWA	25.0000 ppm	
			125.0000 mg/m3	
2-BUTOXYETHANOL (111-76-2)		PEL	240.0000 mg/m3	
			50.0000 ppm	
		TWA	120.0000 mg/m3	
			25.0000 ppm	
CARBON DIOXIDE (124-38-9)		PEL	9000.0000	
			mg/m3	
			5000.0000 ppm	
		STEL	30000.0000 ppm	
			54000.0000	
		T \A/A	mg/m3	
		IVVA	18000.0000	
			mg/m3	
ETUNI DENIZENIE (100-41-4)		חבו	100.0000 ppm	
ETHYLBENZENE (100-41-4)		PEL	100.0000 ppm	
		CTEI	435.0000 mg/m3	
		STEL	125.0000 ppm	
		Τ\Λ/Λ	545.0000 mg/m3	
		IVVA	100.0000 ppm	
Interchangeable base oils on	or more, 61711 00 1	DEI	435.0000 mg/m3	Mict
64742-54-7 64742-65-0	e of more. 04741-00-4,	T L L	5.0000 mg/m3	IVIISL.
04742 34 7, 04742 03 0			2000 0000	
			ma/m3	
			500.0000 ppm	
		TWA	5.0000 mg/m3	Mist.
			400.000 ppm	
			1600.0000	
			mg/m3	
STODDARD SOLVENT (8052-4	1-3)	PEL	2900.0000	
			mg/m3	
			500.0000 ppm	
		TWA	100.0000 ppm	
			525.0000 mg/m3	
TRIMETHYLBENZENE AND AL	L ISOMERS, EXCLUDING	TWA	25.0000 ppm	
1,2,4-TRIMETHYLBENZENE [C	AS RN 95-63-6]			
(25551-13-7)				
		DEI	125.0000 mg/m3	
XYLENE (MIXED ISOMERS) (1	330-20-7)	PEL	100.0000 ppm	
		CTE!	435.0000 mg/m3	
		STEL	150.0000 ppm	
		T\A/A	655.0000 mg/m3	
		IVVA	100.0000 ppm	
			435.0000 mg/m3	
ineering controls	Good general ventilation	(typically 10 air o	changes per hour) should be	used. Ventilation rates
	should be matched to conditions. If applicable, use process enclosures, local exhaust ventilation, or			
other engineering cont		hoop ostablished	borne levels below recommer	anded exposure limits. If
	exposure infinits have not	Deen established		an acceptable level.
sonal protective equipmen	t			
Eye / face protection	Avoid contact with eyes. Chemical goggles are recommended.			
Skin protection	Avoid contact with the skin. Wear appropriate chemical resistant clothing. Chemical resistant gloves.		ng. Chemical resistant	
Respiratory protection	Wear positive pressure self-contained breathing apparatus (SCBA). If permissible levels are exceeded use NIOSH mechanical filter / organic vapor cartridge or an air-supplied respirator.		permissible levels are air-supplied respirator.	
General hygiene considerations	When using do not smoke. Avoid contact with eyes. Avoid contact with skin. Keep away from food and drink. Handle in accordance with good industrial hygiene and safety practice.			

9. Physical & Chemical Properties

۸n	noara	nco	
Ар	peara	nce	

Aerosol.

Color	Blue green	
Odor	Hydrocarbon-like.	
Odor threshold	Not available.	
Physical state	Liquid	
Form	Aerosol.	
рН	Not available.	
Melting point/Freezing point	-94 °F (-70 °C) estimated / -94 °F (-70 °C) estimated	
Boiling point	-110.2 °F (-78.5 °C) estimated	
Flash point	109.4 °F (43 °C) Pensky-Martens Closed Cup	
Evaporation rate	Not available.	
Flammability limits in air, upper, % by volume	Not available.	
Flammability limits in air, lower, % by volume	Not available.	
Vapor pressure	3475.08 hPa estimated	
Density	820 kg/m³	
Vapor density	Not available.	
Specific gravity	0.82	
Relative density	0.8708 g/cm3 estimated	
Solubility (water)	Not available.	
Solubility (other)	Not available.	
Partition coefficient (n-octanol/water)	Not available.	
Auto-ignition temperature	446 °F (230 °C) estimated	
Decomposition temperature	Not available.	
voc	48.5 %	
Viscosity	3 cSt @ 104 °F (40 °C)	
Percent volatile	3.68191 % estimated	

10. Chemical Stability & Reactivity Information

Chemical stability	Risk of ignition. Material is stable under normal conditions.	
Conditions to avoid	Heat, flames and sparks.	
Incompatible materials	Strong oxidizing agents.	
Hazardous decomposition products	Irritants. Sulfuric acid. Nitrogen oxides (NOx). At thermal decomposition temperatures, carbon monoxide and carbon dioxide.	
Possibility of hazardous reactions	Hazardous polymerization does not occur.	

11. Toxicological Information

Toxicological data	
Product	Test Results
Bel-Ray 6 in 1 (Mixture)	Acute Dermal LD50 Rabbit: 3927 mg/kg estimated
	Acute Inhalation LC50 Mouse: 36082 ppm estimated
	Acute Inhalation LC50 Mouse: 7586 mg/l estimated
	Acute Inhalation LC50 Rat: 10487 mg/l estimated
	Acute Oral LD50 Guinea pig: 30697 mg/kg estimated
	Acute Oral LD50 Mouse: 23004 mg/kg estimated
	Acute Oral LD50 Rabbit: 8247 mg/kg estimated
	Acute Oral LD50 Rat: 5254 mg/kg estimated
	Acute Other LD50 Mouse: 29116 mg/kg estimated
	Acute Other LD50 Rabbit: 7216 mg/kg estimated

Components		Test Results
2-BUTOXYETHANOL (111-76-2)		Acute Dermal LD50 Rabbit: 400 mg/kg
		Acute Inhalation LC50 Mouse: 700 mg/l 7.00 Hours
		Acute Inhalation LC50 Rat: 450 mg/l 4.00 Hours
		Acute Oral LD50 Guinea pig: 1200 mg/kg
		Acute Oral LD50 Mouse: 1200 mg/kg
		Acute Oral LD50 Rabbit: 320 mg/kg
		Acute Oral LD50 Rat: 1480 mg/kg
		Acute Other LD50 Mouse: 1130 mg/kg
		Acute Other LD50 Rabbit: 280 mg/kg
		Acute Other LD50 Rat: 340 mg/kg
XYLENE (MIXED ISOMERS) (1330-2	20-7)	Acute Dermal LD50 Rabbit: 12100 mg/kg
		Acute Inhalation LC50 Mouse: 4600 mg/l 6.00 Hours
		Acute Inhalation LC50 Rat: 6350 mg/l 4.00 Hours
		Acute Inhalation LCL0 Rat: 8000 mg/l 4.00 Hours
		Acute Oral LD50 Mouse: 1590 mg/kg
		Acute Oral LD50 Rat: 4300 mg/kg
TRIMETHYLBENZENE AND ALL ISC	MERS, EXCLUDING	Acute Oral LD50 Rat: 8970 mg/kg
1,2,4-TRIMETHYLBENZENE [CAS R	N 95-63-6] (25551-13-7)	
1,2,4-TRIMETHYLBENZENE (95-63-	-6)	Acute Dermal LD50 Rabbit: > 3160 mg/kg
		Acute Inhalation LC50 Rat: > 2000 mg/l 48.00 Hours
		Acute Oral LD50 Rat: 8970 mg/kg
* Estimates for product may b	e based on additional componer	nt data not shown.
Local effects	Components of the product ma occur after ingestion. Ingestion diarrhea, Liver toxicity, Irritatir	ay be absorbed into the body through the skin. Blood disorder may n may cause gastrointestinal irritation, nausea, vomiting and ng to eves. Irritating to skin
Chronic effects	Hazardous by OSHA criteria. Pr through skin.	rolonged inhalation may be harmful. May be harmful if absorbed
	2-Butoxy ethanol may be abso prolonged. These effects have	rbed through the skin in toxic amounts if contact is repeated and e not been observed in humans.
	Repeated absorption may cause Prolonged exposure may cause	e disorder of central nervous system, liver, kidneys and blood.
Subchronic effects	Blood disorder may occur after prolonged inhalation. Blood disorder may occur after ingestion. Blood disorder may occur after prolonged skin contact. Kidney injury may occur.	
Carcinogenicity	Hazardous by OSHA criteria. R	isk of cancer cannot be excluded with prolonged exposure.
ACGIH Carcinogens		
2-BUTOXYETHANOL (CAS	111-76-2)	A3 Confirmed animal carcinogen with unknown relevance to humans.
ETHYLBENZENE (CAS 100-41-4)		A3 Confirmed animal carcinogen with unknown relevance to humans.
IARC Monographs Overall	b) (CAS 1330-20-7) Evaluation of Carcinogenicit	A4 Not classifiable as a numan carcinogen.
2-BUTOXYETHANOL (CAS	111-76-2)	3 Not classifiable as to carcinogenicity to humans.
ETHYLBENZENE (CAS 100	-41-4)	2B Possibly carcinogenic to humans.
STODDARD SOLVENT (CA	S 8052-41-3)	3 Not classifiable as to carcinogenicity to humans.
XYLENE (MIXED ISOMERS	b) (CAS 1330-20-7)	3 Not classifiable as to carcinogenicity to humans.
Epidemiology	Hazardous by OSHA criteria.	

Neurological effects	Hazardous by OSHA criteria.
5	5

Reproductive effects	Components in this product have been shown to cause birth defects and reproductive disorders in laboratory animals.
Teratogenicity	Components in this product have been shown to cause birth defects and reproductive disorders in laboratory animals.
Further information	Symptoms may be delayed.

12. Ecological Information

Ecotoxicological data Product		Test Results
Rel-Ray 6 in 1 (Mixture)		EC50 Daphnia: 368 mg/l 48.00 hours estimated
		LC50 Fish: 154 mg/l 96.00 hours estimated
Components		Test Results
2-BUTOXYETHANOL (111-76-2)		LC50 Inland silverside (Menidia beryllina): 1250 mg/l 96.00 hours
XYLENE (MIXED ISOMERS) (1330-	20-7)	LC50 Rainbow trout,donaldson trout (Oncorhynchus mykiss): 5.59 - 11.6 mg/l 96.00 hours
1,2,4-TRIMETHYLBENZENE (95-63	-6)	LC50 Fathead minnow (Pimephales promelas): 7.19 - 8.28 mg/l 96.00 hours
* Estimates for product may b	e based on additional compone	nt data not shown.
Ecotoxicity	Components of this product are hazardous to aquatic life.	
Environmental effects	Harmful to aquatic organisms	
Persistence and degradability	Not available.	
13. Disposal Consideration	ons	
Waste codes	D001: Waste Flammable mate D018: Waste Benzene	erial with a flash point <140 F
US RCRA Hazardous Waste	e U List: Reference	
XYLENE (MIXED ISOMERS	S) (CAS 1330-20-7)	U239
Disposal instructions	Contents under pressure. Do not puncture, incinerate or crush. Incinerate the material under controlled conditions in an approved incinerator. Do not allow this material to drain into sewers/water supplies. If discarded, this product is considered a RCRA ignitable waste, D001. Dispose in accordance with all applicable regulations.	
Contaminated packaging	Do not re-use empty containe	rs.
14. Transport Informatio	n	
DOT		
Basic shipping requiremen	ts:	

UN1950
Aerosols, flammable
2.1
9
153, N82
ts:
2.1
306
None
None
126
ts:
1950
Aerosols, flammable
2.1

IMDG



15. Regulatory Information

US federal regulations

This product is a "Hazardous Chemical" as defined by the OSHA Hazard Communication Standard, 29 CFR 1910.1200.

All components are on the U.S. EPA TSCA Inventory List.

US EPCRA (SARA Title III) Section 313 - Toxic Chemical: De minimis concentration

FDODA (CADA THIS III) Costion 212	Tavia Chaminal, Listad auk
ETHYLBENZENE (CAS 100-41-4)	0.1 %
2-BUTOXYETHANOL (CAS 111-76-2)	1.0 % N230
1,2,4-TRIMETHYLBENZENE (CAS 95-63-6	6) 1.0 %

US EPCRA (SARA Title III) Section 313 - Toxic Chemical: Listed substance

1,2,4-TRIMETHYLBENZENE (CAS 95-63-6)	
2-BUTOXYETHANOL (CAS 111-76-2)	
ETHYLBENZENE (CAS 100-41-4)	

US TSCA Section 12(b) Export Notification: Export Notification requirement/De minimis concentration

Listed. Listed. N230 Listed.

XYLENE (MIXED ISOMERS) (CAS 1330-20-7)

1.0 % One-Time Export Notification only.

Listed: February 27, 1987 Carcinogenic.

CERCLA (Superfund) reportable quantity

XYLENE (MIXED ISOMERS): 1000.0000 ETHYLBENZENE: 100.0000

Superfund Amendments and Reauthorization Act of 1986 (SARA)

Hazard categories	Immediate Hazard - Yes	
· · · · · · · · · · · · · · · · · · ·	Delayed Hazard - Yes	
	Fire Hazard - Yes	
	Pressure Hazard - No	
	Reactivity Hazard - No	
Section 302 extremely hazardous substance	No	
Section 311 hazardous chemical	No	
Inventory status		
Country(s) or region	Inventory name	On inventory (yes/no)*
Australia	Australian Inventory of Chemical Substances (AICS)	Yes
Canada	Non-Domestic Substances List (NDSL)	Yes
Europe	European Inventory of Existing Commercial Chemical Substances (EINECS)	Yes
Korea	Existing Chemicals List (ECL)	Yes
United States & Puerto Rico	Toxic Substances Control Act (TSCA) Inventory	Yes
*A "Yes" indicates that all compon	ents of this product comply with the inventory requirements administered by t	he governing country(s)
State regulations	WARNING: This product contains a chemical known to the State of C birth defects or other reproductive harm.	alifornia to cause cancer and
US - California Proposition	65 - CRT: Listed date/Carcinogenic substance	

Material name: Bel-Ray 6 in 1 99020 Version #: 1.0 Revision date: 06-18-2010 Print date: 06-18-2010

BENZENE (CAS 71-43-2)

ETHYLBENZENE (CAS 100-41-4)	Listed: June 11, 2004 Carcinogenic.	
NAPHTHALENE (CAS 91-20-3)	Listed: April 19, 2002 Carcinogenic.	
US - California Proposition 65 - CRT: Listed date/Develo	opmental toxin	
BENZENE (CAS 71-43-2)	Listed: December 26, 1997 Developmental toxin.	
TOLUENE (CAS 108-88-3)	Listed: January 1, 1991 Developmental toxin.	
US - California Proposition 65 - CRT: Listed date/Femal	e reproductive toxin	
TOLUENE (CAS 108-88-3)	Listed: August 7, 2009 Female reproductive toxin.	
US - California Proposition 65 - CRT: Listed date/Male r	eproductive toxin	
BENZENE (CAS 71-43-2)	Listed: December 26, 1997 Male reproductive toxin.	
US - New Jersey Community RTK (EHS Survey): Report	able threshold	
1,2,4-TRIMETHYLBENZENE (CAS 95-63-6)	500 LBS	
2-BUTOXYETHANOL (CAS 111-76-2)	500 LBS	
ETHYLBENZENE (CAS 100-41-4)	500 LBS	
US - Pennsylvania RTK - Hazardous Substances: Listed	substance	
1,2,4-TRIMETHYLBENZENE (CAS 95-63-6)	Listed.	
2-BUTOXYETHANOL (CAS 111-76-2)	Listed.	
CARBON DIOXIDE (CAS 124-38-9)	Listed.	
ETHYLBENZENE (CAS 100-41-4)	Listed.	
STODDARD SOLVENT (CAS 8052-41-3)	Listed.	
TRIMETHYLBENZENE AND ALL ISOMERS, EXCLUDING	Listed.	
1,2,4-TRIMETHYLBENZENE [CAS RN 95-63-6] (CAS		
25551-13-7)		
XYLENE (MIXED ISOMERS) (CAS 1330-20-7)	Listed.	
16. Other Information		

Further information	HMIS® is a registered trade and service mark of the NPCA.
HMIS [®] ratings	Health: 2* Flammability: 2 Physical hazard: 0
NFPA ratings	Health: 2 Flammability: 2 Instability: 0
Disclaimer	Bel-Ray Company cannot anticipate all conditions under which this information and its product, or the products of other manufacturers in combination with its product, may be used. It is the user's responsibility to ensure safe conditions for handling, storage and disposal of the product, and to assume liability for loss, injury, damage or expense due to improper use. The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.
Issue date	06-18-2010