Revision: 24.08.2015



Safety data sheet according to 1907/2006/EC, Article 31

Printing date 24.08.2015

Version number 1

SECTION 1: Identification of the substance/mixture and of the company/undertaking

- · 1.1 Product identifier
- · Trade name: OEM TWIN AIR BIO LIQUID POWER
- 1.2 Relevant identified uses of the substance or mixture and uses advised against No further relevant information available.
- · Application of the substance / the mixture

Air filter oil

Only for proper handling.

- · 1.3 Details of the supplier of the safety data sheet
- · Manufacturer/Supplier:

BUCHER AG LANGENTHAL MOTOREX-Schmiertechnik Bern-Zürich-Strasse 31 CH-4901 Langenthal Telefon +41 (0)62 919 75 75

- · Further information obtainable from: msds@motorex.com
- · 1.4 Emergency telephone number:

Toxicological Information Centre, CH-8028 Zurich, info@toxi.ch.

T. +41 (0) 44 251 51 51

SECTION 2: Hazards identification

- · 2.1 Classification of the substance or mixture
- · Classification according to Regulation (EC) No 1272/2008



GHS02 flame

Flam. Liq. 2

H225 Highly flammable liquid and vapour.



GHS08 health hazard

Asp. Tox. 1

H304 May be fatal if swallowed and enters airways.



GHS09 environment

Aquatic Chronic 2 H411 Toxic to aquatic life with long lasting effects.



GHS07

Skin Irrit. 2

H315 Causes skin irritation.

STOT SE 3

H336 May cause drowsiness or dizziness.

- · 2.2 Label elements
- Labelling according to Regulation (EC) No 1272/2008

The product is classified and labelled according to the CLP regulation.

(Contd. on page 2)

(Contd. of page 1)

Safety data sheet according to 1907/2006/EC, Article 31

Printing date 24.08.2015 Version number 1 Revision: 24.08.2015

Trade name: OEM TWIN AIR BIO LIQUID POWER

Hazard pictograms





· Signal word Danger

· Hazard-determining components of labelling:

Hydrocarbons C6-C7, n-alkanes, iso-alkanes, cyclenes, <5% n-hexane

· Hazard statements

H225 Highly flammable liquid and vapour.

H315 Causes skin irritation.

H336 May cause drowsiness or dizziness.

H304 May be fatal if swallowed and enters airways.

H411 Toxic to aquatic life with long lasting effects.

Precautionary statements

P210 Keep away from heat, hot surfaces, sparks, open flames and other

ignition sources. No smoking.

P241 Use explosion-proof electrical/ventilating/lighting/equipment.

P261 Avoid breathing dust/fume/gas/mist/vapours/spray.

P280 Wear protective gloves/protective clothing/eye protection/face protection.

P240 Ground/bond container and receiving equipment.

P301+P310 IF SWALLOWED: Immediately call a POISON CENTER/ doctor.

P303+P361+P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing.

Rinse skin with water/shower.

P321 Specific treatment (see on this label).

P405 Store locked up.

P501 Dispose of contents/container in accordance with local/regional/national/

international regulations.

· 2.3 Other hazards

· Results of PBT and vPvB assessment

PBT: Not applicable.vPvB: Not applicable.

SECTION 3: Composition/information on ingredients

- · 3.2 Chemical characterisation: Mixtures
- · Description: Mixture of substances listed below with nonhazardous additions.

•	Dangerous	components:
---	-----------	-------------

EC number: 921-024-6
Reg.nr.: 01-2119475514-35-xxxx

Hydrocarbons C6-C7, n-alkanes, iso-alkanes, cyclenes, <5% n-hexane

↑ Flam. Liq. 2, H225; ↑ Asp. Tox. 1, H304; Aquatic Chronic 2, H411; ↑ Skin Irrit. 2, H315; STOT SE 3, H336

· Additional information: For the wording of the listed risk phrases refer to section 16.

SECTION 4: First aid measures

- · 4.1 Description of first aid measures
- · After inhalation:

In case of unconsciousness place patient stably in side position for transportation.

(Contd. on page 3)

Printing date 24.08.2015 Version number 1 Revision: 24.08.2015

Trade name: OEM TWIN AIR BIO LIQUID POWER

(Contd. of page 2)

· After skin contact:

Remove contaminated clothing immediately.

Immediately wash with water and soap and rinse thoroughly.

· After eye contact:

Rinse opened eye for several minutes under running water.

Consult a physician if irritation develops.

· After swallowing:

Do not induce vomitting. Do not take in resorption stimulating agents.

Consult a physician who will decide on need and method of emptying the stomach.

· 4.2 Most important symptoms and effects, both acute and delayed No further relevant information available.

• 4.3 Indication of any immediate medical attention and special treatment needed No further relevant information available.

SECTION 5: Firefighting measures

- · 5.1 Extinguishing media
- · Suitable extinguishing agents: CO2, sand, extinguishing powder. Do not use water.
- · For safety reasons unsuitable extinguishing agents: Water with full jet
- 5.2 Special hazards arising from the substance or mixture

No further relevant information available.

- · 5.3 Advice for firefighters
- · Protective equipment: No special measures required.
- · Additional information

Use water spray to cool fire exposed containers and fire affected zone until fire is out and danger of reignition has passed.

SECTION 6: Accidental release measures

- 6.1 Personal precautions, protective equipment and emergency procedures Wear protective equipment. Keep unprotected persons away.
- 6.2 Environmental precautions:

Inform respective authorities in case of seepage into water course or sewage system. Do not allow to enter sewers/ surface or ground water.

6.3 Methods and material for containment and cleaning up:

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).

Ensure adequate ventilation.

Do not flush with water or aqueous cleansing agents

6.4 Reference to other sections

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

SECTION 7: Handling and storage

· 7.1 Precautions for safe handling

Ensure good ventilation/exhaustion at the workplace.

Prevent formation of aerosols.

· Information about fire - and explosion protection:

Keep ignition sources away - Do not smoke.

Protect against electrostatic charges.

(Contd. on page 4)

Printing date 24.08.2015 Version number 1 Revision: 24.08.2015

Trade name: OEM TWIN AIR BIO LIQUID POWER

(Contd. of page 3)

- · 7.2 Conditions for safe storage, including any incompatibilities
- Storage:
- · Requirements to be met by storerooms and receptacles: Store in a cool location.
- · Information about storage in one common storage facility: Not required.
- · Further information about storage conditions:

Keep container tightly sealed.

Store in cool, dry conditions in well sealed receptacles.

- · Storage class: 3
- · 7.3 Specific end use(s) No further relevant information available.

SECTION 8: Exposure controls/personal protection

- · Additional information about design of technical facilities: No further data; see item 7.
- · 8.1 Control parameters
- · Ingredients with limit values that require monitoring at the workplace:

The product does not contain any relevant quantities of materials with critical values that have to be monitored at the workplace.

- · Additional information: The lists valid during the making were used as basis.
- · 8.2 Exposure controls
- · Personal protective equipment:
- General protective and hygienic measures:

Keep away from foodstuffs, beverages and feed.

Immediately remove all soiled and contaminated clothing

Wash hands before breaks and at the end of work.

Avoid contact with the skin.

Avoid contact with the eyes and skin.

· Respiratory protection:

In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use self-contained respiratory protective device.

· Protection of hands:



Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

· Material of gloves

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

Penetration time of glove material

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

(Contd. on page 5)

Printing date 24.08.2015 Version number 1 Revision: 24.08.2015

Trade name: OEM TWIN AIR BIO LIQUID POWER

· Eye protection:



Tightly sealed goggles

(Contd. of page 4)

Od Information on basis above is a	and shamical proportion
9.1 Information on basic physical a General Information	and cnemical properties
Appearance:	
Form:	Fluid
Colour:	Dark green
Odour:	Solvent-like
Odour threshold:	Not determined.
pH-value:	Not determined.
Change in condition	
Melting point/Melting range:	Undetermined.
Boiling point/Boiling range:	65 °C (DIN EN ISO 3405)
Flash point:	< -20 °C
Flammability (solid, gaseous):	Not applicable.
Ignition temperature:	250 °C (DIN 51794)
Decomposition temperature:	Not determined.
Self-igniting:	Product is not selfigniting.
Danger of explosion:	Product is not explosive. However, formation explosive air/vapour mixtures are possible.
Explosion limits:	
Lower:	1.0 Vol %
Upper:	7.3 Vol %
Vapour pressure at 20 °C:	1.9 hPa
Density at 20 °C:	0.781 g/cm³ (ASTM D 4052)
Density at 15 °C:	0.785 g/cm³
Relative density	Not determined.
Vapour density	Not determined.
Evaporation rate	Not determined.
Solubility in / Miscibility with	
water:	Not miscible or difficult to mix.
Partition coefficient (n-octanol/wat	ter): Not determined.
Viscosity:	
Dynamic:	Not determined.
Kinematic:	7,1 mm²/s @ 40 °C (DIN 51562-1)
VOC (EC)	59.98 %
9.2 Other information	No further relevant information available.

Printing date 24.08.2015 Version number 1 Revision: 24.08.2015

Trade name: OEM TWIN AIR BIO LIQUID POWER

(Contd. of page 5)

SECTION 10: Stability and reactivity

- · 10.1 Reactivity No further relevant information available.
- · 10.2 Chemical stability
- · Thermal decomposition / conditions to be avoided:

Can be distilled without decomposing at normal pressure.

- · 10.3 Possibility of hazardous reactions No dangerous reactions known.
- · 10.4 Conditions to avoid With strong oxidisers.
- · 10.5 Incompatible materials: No further relevant information available.
- · 10.6 Hazardous decomposition products: No dangerous decomposition products known.
- · Additional information: The product is highly flammable.

SECTION 11: Toxicological information

- · 11.1 Information on toxicological effects
- · Acute toxicity
- · Primary irritant effect:
- · Skin corrosion/irritation

Causes skin irritation.

· Serious eye damage/irritation

Based on available data, the classification criteria are not met.

· Respiratory or skin sensitisation

Based on available data, the classification criteria are not met.

- · CMR effects (carcinogenity, mutagenicity and toxicity for reproduction)
- · Germ cell mutagenicity Based on available data, the classification criteria are not met.
- · Carcinogenicity Based on available data, the classification criteria are not met.
- · Reproductive toxicity Based on available data, the classification criteria are not met.
- STOT-single exposure

May cause drowsiness or dizziness.

- · STOT-repeated exposure Based on available data, the classification criteria are not met.
- · Aspiration hazard

May be fatal if swallowed and enters airways.

SECTION 12: Ecological information

- · 12.1 Toxicity
- · Aquatic toxicity: No further relevant information available.
- 12.2 Persistence and degradability

Biodegradability according to OECD 301 B: >60 % in 28 days

- · 12.3 Bioaccumulative potential No further relevant information available.
- · 12.4 Mobility in soil No further relevant information available.
- Ecotoxical effects:
- · Remark: Toxic for fish
- · Additional ecological information:
- · General notes:

Water hazard class 2 (German Regulation) (Self-classification according VwVwS, 17.05.1999): hazardous for water

Do not allow product to reach ground water, water course or sewage system.

Danger to drinking water if even small quantities leak into the ground.

Also poisonous for fish and plankton in water bodies.

Toxic for aquatic organisms

- 12.5 Results of PBT and vPvB assessment
- · PBT: Not applicable.

(Contd. on page 7)

Printing date 24.08.2015 Version number 1 Revision: 24.08.2015

Trade name: OEM TWIN AIR BIO LIQUID POWER

(Contd. of page 6)

· vPvB: Not applicable.

• 12.6 Other adverse effects No further relevant information available.

SECTION 13: Disposal considerations

- · 13.1 Waste treatment methods
- Recommendation

Must not be disposed together with household garbage. Do not allow product to reach sewage system.

· European waste catalogue

12 01 19* readily biodegradable machining oil

- · Uncleaned packaging:
- · Recommendation:

Disposal must be made according to official regulations.

Discharged containers can contain flammable or explosive vapours.

14.1 UN-Number ADR,ADN, IMDG, IATA	UN3295
14.2 UN proper shipping name ADR/ADN	3295 HYDROCARBONS, LIQUID, N.O ENVIRONMENTALLY HAZARDOUS
IMDG, IATA	HYDROCARBONS, LIQUID, N.O.S.
14.3 Transport hazard class(es)	
ADR/ADN	
Class Label	3 (F1) Flammable liquids. 3
	3
IMDG, IATA Class	3 Flammable liquids.
Label	3
14.4 Packing group ADR,ADN, IMDG, IATA	II .
14.5 Environmental hazards:	
Marine pollutant: Special marking (ADR/ADN):	No Symbol (fish and tree)
14.6 Special precautions for user Danger code (Kemler):	Warning: Flammable liquids. 33

- GB

Revision: 24.08.2015

Safety data sheet according to 1907/2006/EC, Article 31

Printing date 24.08.2015

Version number 1

Trade name: OEM TWIN AIR BIO LIQUID POWER

	(Contd. of page 7
· EMS Number:	F-E,S-D
14.7 Transport in bulk according to	Annex
II of Marpol and the IBC Code	Not applicable.
Transport/Additional information:	
ADR/ADN	
· Limited quantities (LQ)	1L
Excepted quantities (EQ)	Code: E2
	Maximum net quantity per inner packaging
	30 ml
	Maximum net quantity per outer packaging
	500 ml
· Transport category	2
Tunnel restriction code	D/E
· IMDG	
Limited quantities (LQ)	1L
Excepted quantities (ÉQ)	Code: E2
, ,	Maximum net quantity per inner packaging
	30 ml
	Maximum net quantity per outer packaging
	500 ml
UN "Model Regulation":	UN3295, HYDROCARBONS, LIQUID
G	N.O.S., ENVIRONMENTALLY
	HAZARDOUS, 3, II

SECTION 15: Regulatory information

- · 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture
- · Directive 2012/18/EU
- · Named dangerous substances ANNEX I None of the ingredients is listed.
- · Seveso category

E2 Hazardous to the Aquatic Environment

P5c FLAMMABLE LIQUIDS

- · Qualifying quantity (tonnes) for the application of lower-tier requirements 200 t
- Qualifying quantity (tonnes) for the application of upper-tier requirements 500 t
- · National chemical directories

Components listed or exempted from listing:

TSCA (USA) DSL/NDSL (CDN)

ENCS/METI (J)

AICS (Aus)

IECSC (CN)

EINECS/ELINCS/NLP (EU)

ECL/KECI (KOR)

· 15.2 Chemical safety assessment:

A Chemical Safety Assessment has not been carried out.

Printing date 24.08.2015 Versio

Version number 1

(Contd. of page 8)

Revision: 24.08.2015

Trade name: OEM TWIN AIR BIO LIQUID POWER

SECTION 16: Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

· Relevant phrases

H225 Highly flammable liquid and vapour.

H304 May be fatal if swallowed and enters airways.

H315 Causes skin irritation.

H336 May cause drowsiness or dizziness.

H411 Toxic to aquatic life with long lasting effects.

- · Department issuing MSDS: Abteilung Produktsicherheit
- · Abbreviations and acronyms:

Flam. Liq. 2: Flammable liquids, Hazard Category 2

Skin Irrit. 2: Skin corrosion/irritation, Hazard Category 2

STOT SE 3: Specific target organ toxicity - Single exposure, Hazard Category 3 Asp. Tox. 1: Aspiration hazard, Hazard Category 1

Aquatic Chronic 2: Hazardous to the aquatic environment - Chronic Hazard, Category 2

GB -