



邦查工業股份有限公司

BANZA STAMPING INDUSTRY, CORP.

中華民國宜蘭縣27049蘇澳鎮頂平路2號 #2, Dingping Road, Su'ao Township

E msds@banza.com.tw

Yilan, Taiwan 27049, R.O.C

T +886 3 990 7650 F +886 3 990 7198



Product Safety Data Sheet (PSDS)

The gas cylinder products referenced in this PSDS document are consumer products. Gas cylinders under 50ml capacity are considered "articles" under the Global Harmonized System and are exempted from the GHS labeling and SDS classification criteria. This PSDS document is provided as service in response to requests for information on gas cylinder use, safety and regulatory compliance.

SECTION 1 — PRODUCT IDENTIFICATION

Product Name DISPOSABLE CARBON DIOXIDE CARTRIDGES

Product Identification Gas Cylinders; Receptacles Small, Containing Gas; Disposable Carbon Dioxide Cartridges

Product Use Propellent source for Non-powdered projectile gun

PSDS Date of Preparation 2015/09/09, Revised 2021/02/01

Document ID BZ_PSDS_CO2_50ML

Company Identification BANZA STAMPING INDUSTRY CORP

#2 DINGPING ROAD, SU'AO TOWNSHIP

YILAN COUNTY 27049, TAIWAN

REPUBLIC OF CHINA

SECTION 2 — HAZARD IDENTIFICATION

TPED status In accordance to Articles 2 of Directive 2010/35/EU; Annexes to the Directive 2008/68/EC;

and Special Provision 584 of ADR 2019, this material is exempt from TPED requirements.

OSHA/HCS statusThis material is considered "articles" by the OSHA Hazard Communication Standard (29 CFR

1910.1200) and is exempted from the OSHA/HCS labeling criteria.

DOT statusThis material is a container for carbon dioxide with no more than 4 fluid ounces of capacity

and is considered "ORM-D" or "Consumer Commodity" by the Department of Transportation (49 CFR 172.101 and 173.306). This material is exempted from the DOT labeling criteria,

except when offered for transportation or transported by air.

GHS statusThis material is considered "articles" by the Global Harmonized System and is exempted

from the GHS labeling and SDS classification criteria.

Precautionary statements

General Read and follow all Product Safety Data Sheets (PSDS'S) before use. Read label before

use. Keep out of reach of children. If medical advice is needed, have product container or label at hand. Use equipment rated for cylinder pressure. Do not puncture until connected to equipment prepared for use. Do not remove until contents is empty. Do not throw into fire.

Use only equipment of compatible materials of construction.

Prevention Use and store outdoors or in a well ventilated place.

Response IF INHALED: Remove person to fresh air and keep comfortable for breathing. Call a

POISON CENTER or doctor/physician if you feel unwell.

Storage Protect from sunlight. Protect from sunlight when ambient temperature exceeds 52°C/125°F.

Store in a well-ventilated place.

Disposal Dispose in accordance with all applicable regulations. Do not incinerate unless content is

empty.

Hazards not otherwise classified In addition to any other important health or physical hazards, this product may displace

oxygen and cause rapid suffocation.

May cause frostbite.

SECTION 3 — COMPOSITION AND INGREDIENTS

Substance / Mixture Substance

Chemical Name Carbon Dioxide

Synonyms Carbonic, Carbon Dioxide, Carbon Anhydride, CO₂

CAS Number 124-38-9

Content (vo%) 99.8 % or more

There are no additional ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified as hazardous to health or the environment and hence require reporting in this section.

Occupational exposure limits, if available, are listed in Section 8.

SECTION 4 — FIRST AID INFORMATION

Descriptions of necessary first aid measures

Inhalation Remove exposed person to fresh air and keep at rest in a position comfortable for breathing.

If not breathing, if breathing is irregular, or if respiratory arrest occurs, provide artificial respiration or oxygen by trained personnel. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. Get medical attention if adverse health effects persist or are severe. If unconscious, place in recovery position and get medical attention immediately. Maintain an open airway. Loosen tight clothing such as a collar, tie, belt or

waistband.

Skin Contact Carbon dioxide is harmless at atmospheric pressure. Flush contaminated skin with plenty of

water. Remove contaminated clothing and shoes. Get medical attention if symptoms occur.

Wash clothing before reuse. Clean shoes thoroughly before reuse.

Eye Contact Carbon dioxide is harmless at atmospheric pressure. Immediately flush eyes with plenty of

water, occasionally lifting the upper and lower eyelids. Check for and remove any contact lenses. Continue to rinse for at least 10 minutes. Get medical attention if irritation occurs.

Ingestion Refer to the inhalation section.

Most important symptoms/effects, acute and delayed

Potential acute health effects

InhalationNo known significant effects or critical hazards.Skin ContactNo known significant effects or critical hazards.Eye ContactNo known significant effects or critical hazards.

Frostbite Try to warm up the frozen tissues and seek medical attention.

Ingestion Refer to the inhalation section.

Over-exposure signs/symptoms

Inhalation No specific data.

Skin ContactNo specific data.Eye ContactNo specific data.IngestionNo specific data.

Indication of immediate medical attention and special treatment needed, if necessary

Notes to physician Treat symptomatically. Contact poison treatment specialist immediately if large quantities

have been ingested or inhaled.

Specific treatments No specific treatment.

Protection of first-aiders No action shall be taken involving any personal risk or without suitable training. It may be

dangerous to the person providing aid to give mouth-to-mouth resuscitation.

SECTION 5 — FIRE FIGHTING INFORMATION

Extinguishing media

Unsuitable extinguishing media No specific treatment.

Specific hazards arising from the

chemical

Contains gas under pressure. In a fire or if heated, a pressure increase will occur and

the container may burst or explode.

Hazardous thermal Decomposition products may include the following materials:

decomposition products

Carbon dioxide

Carbon monoxide

Special protective actions

for fire-fighters

Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire. No action shall be taken involving any personal risk or without suitable training. Contact supplier immediately for specialist advice. Move containers from fire area if this can be done without risk. Use water spray to keep fire-exposed containers

cool

Special protective

equipment for fire-fighters

Fire-fighters should wear appropriate equipment and self-contained breathing apparatus (SCBA) with a full face-piece operated in positive pressure mode.

SECTION 6 — ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency procedures

For non-emergency personnel No action shall be taken involving any personal risk or without suitable training.

Evacuate surrounding areas. Keep unnecessary and unprotected personnel from entering. Avoid breathing gas. Provide adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Put on appropriate personal protective

equipment.

in Section 8 on suitable and unsuitable materials. See also the information in "For

non-emergency personnel".

Environmental precautions Ensure emergency procedures to deal with accidental gas releases are in place to

avoid contamination of the environment. Inform the relevant authorities if the product

has caused environmental pollution (sewers, waterways, soil or air).

Methods and materials for containment and cleaning up

Small spill This material contains no more than 40grams of carbon dioxide, in case of spill, allow carbon

dioxide to vent naturally. Do not handle the cylinder without protective gloves as it may cause

frostbite.

Large spill This material contains no more than 40grams of carbon dioxide, in case of spill, allow carbon

dioxide to vent naturally. Do not handle the cylinder without protective gloves as it may cause

frostbite.

SECTION 7 — HANDLING AND STORAGE

Precaution for safe handling

Put on appropriate personal protective equipment (see Section 8). Contains gas Protective measures

under pressure. Avoid contact with eyes, skin and clothing. Avoid breathing gas. Empty containers retain product residue and can be hazardous. Do not puncture or incinerate container. Use equipment rated for cylinder pressure. Close valve after each use and when empty. Protect cylinders from physical damage; do not drag, roll, slide, or drop. Use a suitable hand truck for cylinder movement.

Advice on general occupational hvaiene

Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed. Workers should wash hands and face before eating, drinking and smoking. Remove contaminated clothing and protective equipment before entering eating areas. See also Section 8 for additional information on hygiene measures.

Conditions for safe storage, including any incompatibility Store in accordance with local regulations. Store in a segregated and approved area. Store away from direct sunlight in a dry, cool and well-ventilated area, away from incompatible materials (see Section 10). Keep container tightly closed and sealed until ready for use. Cylinders should be stored upright, with valve protection cap in place, and firmly secured to prevent falling or being knocked over. Cylinder temperatures should not exceed 52°C (125°F).

SECTION 8 — EXPOSURE CONTROLS / PERSONAL PROTECTION

This material contains no more than 40 grams of Carbon Dioxide. Although unlikely to result in serious exposures, the following Control parameters Occupational exposure limits are provided for regulatory purpose.

Control parameters Occupational exposure limits

Ingredient name	Exposure Limits		
Carbon Dioxide	ACGIH TLV (United States, 3/2012). Oxygen Depletion [Asphyxiant]. STEL: 54000 mg/m3 15 minutes. STEL: 30000 ppm 15 minutes. TWA: 9000 mg/m3 8 hours TWA: 5000 ppm 8 hours. NIOSH REL (United States, 1/2013). STEL: 54000 mg/m3 15 minutes. STEL: 30000 ppm 15 minutes. TWA: 9000 mg/m3 8 hours TWA: 5000 ppm 8 hours. OSHA PEL (United States, 6/2010). TWA: 9000 mg/m3 8 hours TWA: 5000 ppm 8 hours. OSHA PEL 1989 (United States, 3/1989). STEL: 54000 mg/m3 15 minutes. STEL: 30000 ppm 15 minutes. TWA: 9000 mg/m3 8 hours TWA: 9000 mg/m3 8 hours TWA: 9000 mg/m3 8 hours		
Appropriate engineering controls	Good general ventilation should be sufficient to control worker exposure to		

airborne contaminants.

Environmental exposure controls Emissions from ventilation or work process equipment should be checked to ensure they

comply with the requirements of environmental protection legislation. In some cases, fume scrubbers, filters or engineering modifications to the process equipment will be necessary

to reduce emissions to acceptable levels.

Precautions for safe handling

Protective measures Put on appropriate personal protective equipment (see Section 8). Contains gas

under pressure. Avoid contact with eyes, skin and clothing. Avoid breathing gas.

Empty containers retain product residue and can be hazardous.

Individual protection measure

Hygiene measure Wash hands, forearms and face thoroughly after handling chemical products, before eating,

smoking, using the lavatory and at the end of your shift.

Appropriate techniques should be used to remove potentially contaminated clothing. Wash contaminated clothing before reusing. Ensure that eyewash stations and safety showers are

close to the workstation location.

Eye/Face protection Safety eyewear complying with an approved standard should be used when a risk

assessment indicates this is necessary to avoid exposure to liquid splashes, mists, gases or dusts. If contact is possible, the following protection should be worn, unless the assessment

indicates a higher degree of protection: safety glasses with side-shields.

Skin protection Chemical-resistant, impervious gloves complying with an approved standard should be worn Hand protection at all times when handling chemical products if a risk assessment indicates this is necessary.

at all times when handling chemical products if a risk assessment indicates this is necessary. Considering the parameters specified by the glove manufacturer, check during use that the gloves are still retaining their protective properties. It should be noted that the time to breakthrough for any glove material may be different for different glove manufacturers. In the case of mixtures, consisting of several substances, the protection time of the gloves cannot

be accurately estimated.

Body protection Personal protective equipment for the body should be selected based on the task being

performed and the risks involved and should be approved by a specialist before handling this

product.

Other skin protection Appropriate footwear and any additional skin protection measures should be selected based

on the task being performed and the risks involved and should be approved by a specialist

before handling this product.

Respiratory protection Use a properly fitted, air-purifying or air-fed respirator complying with an approved standard

if a risk assessment indicates this is necessary. Respirator selection must be based on known or anticipated exposure levels, the hazards of the product and the safe working limits

of the selected respirator.

SECTION 9 — PHYSICAL AND CHEMICAL PROPERTIES

Appearance

Physical state Gas at normal temperature and pressure

Color Colorless

Molecular weiight 44.01g/mol

Molecular fomula C-O₂

Melting/freezing point Sublimation temperature: -79°C (-110.2ªF)

Critical temperature 30.85°C (87.5°F)

Odor Odorless
Odor threshold Not available

pH Not available

Flash point [Product does not sustain combustion]

Burning time Not available
Burning rate Not available
Evaporation rate Not available
Flammability (solid, gas) Not available

Lower and upper explosive

(flammable) limits

Not available

Vapor pressure 830 psig

Vapor density 1.53 (Air = 1), Liquid Density@BP: Solid Density = 97.5 lb/ft3 (1562 kg/m3)

8.7719 ft3/lb (m3/g) Specific volume

0.114 lb/ft3 (178.6 g/m3) Gas density

Relative density Not available Solubility Not available Solubility in Water Not available

Partition coefficient 0.83

n-octano / water Not available Auto-ignition temperature Not available Not available Decomposition temperature SADT Not available Viscosity Not available

SECTION 10 — STABILITY AND REACTIVITY

Reactivity No specific test data related to reactivity is available for this product or its ingredients.

Chemical stability The product is stable

Possibility of hazardous reaction Under normal conditions of storage and use, hazardous reactions will not occur.

Conditions to avoid No specific data.

Hazardous decomposition Under normal conditions of storage and use, hazardous decomposition products should not

be produced.

Hazardous polymerization Under normal conditions of storage and use, hazardous polymerization will not occur.

SECTION 11 — TOXICOLOGICAL INFORMATION

Information on toxicological effects

Acute toxicity Not Available Irritation / Corrosion Not available Sensitization Not available Mutagenicity Not available Carcinogenicity Not available Reproductive toxicity Not available Teratogenicity Not available Specific target organ toxicity Not available

(single exposure)

Specific target organ toxicity

Potential acute health effects

(repeated exposure)

Not available

Aspiration hazard Not available Information on the likely route of

exposure

Not available

BANZA STAMPING INDUSTRY CORP. BZ PSDS CO2 50ML Page 6 of 10 Eye contact

No known significant effects or critical hazards.

Inhalation

No known significant effects or critical hazards.

Skin contact No known significant effects or critical hazards.

Ingestion Since this product is a gas, refer to the inhalation section.

Symptoms related to the physical, chemical, and toxicological characteristics

Eye contactNo specific data.InhalationNo specific data.Skin contactNo specific data.IngestionNo specific data.

Delayed and immediate effects and also chronic effects from short and long term exposure

Short term exposure

Potential immediate effects Not available

Potential delayed effects Not available

Long term exposure

Potential immediate effects Not available

Potential delayed effects Not available

Potential chronic health effects — Not available

GeneralNo known significant effects or critical hazards.CarcinogenicityNo known significant effects or critical hazards.MutagenicityNo known significant effects or critical hazards.TeratogenicityNo known significant effects or critical hazards.Developmental effectsNo known significant effects or critical hazards.Fertility effectsNo known significant effects or critical hazards.

Numerical measures of toxicity

Acute toxicity estimate Not available

SECTION 12 — ECOLOGICAL INFORMATION

Toxicity Not available

Persistence and degradability Not available

Bioaccumulative potential

Product / Ingredient name	Log Pow	BCF	Potential
Carbon Dioxide	0.83	-	low

Mobility in soil

Soil/Water partition Not available coefficient (Koc)

Other adverse effects Not available

SECTION 13 — DISPOSAL CONSIDERATIONS

Discharge of Carbon Dioxide

Gradually release in open air.

Disposal of Cylinders

If gas remains in cylinders, release gas with proper equipment and recycle cylinders as recyclable steel.

Verify for puncture hole.

Do not dispose or recycle without first checking that all gas has been released and there is a puncture hole on the cylinder.



SECTION 14 — TRANSPORT INFORMATION

IMO IMDG 39-18

This product conforms to **Special Provision 191 of IMDG 39-18**: Receptacles with a _{Capacity} not exceeding 50 mL containing only non-toxic constituents are **not subject to the provisions of this Code**.

IATA DGR 62th (2021)

This product conforms to **Special Provision A98 of IATA DGR 62th:** Aerosols, gas cartridges and receptacles, small, containing gas with a capacity not exceeding 50 mL, containing no constituents subject to these Regulations other than a Division 2.2 gas, **are not subject to these Regulations when carried as cargo** unless their release could cause extreme annoyance or discomfort to crew members so as to prevent the correct performance of duties.

The words "Not Restricted" and the Special Provision number must be included in the description of the substance on the Air Waybill as required by 8.2.6, when an Air Waybill is issued.

ADR (2019)

This product conforms to Special Provision 584 of ADR 2019:

This gas is not subject to the requirements of ADR when:

- it contains not more than 5% air in the gaseous state;
- it is contained in metal capsules (sodors, sparklets) free from defects which may impair their strength;
- the leakproofness of the closure of the capsule is ensured;
- a capsule contains no more than 25 g of this gas;
- a capsule contains not more than $0.75~\mbox{g}$ of this gas per cm 3 of capacity.

SECTION 15 — REGULATORY INFORMATION

The following selected regulatory requirements may apply to this product. Not all such requirements are identified. Users of this product are solely responsible for compliance with all applicable international and domestic (including but not limited to federal, state, and local) regulations.

U.S. Federal Regulations

None of this products components are listed under SARA Sections 302/304 (40 CFR 355 Appendix A), SARA Section 313 (40 CFR 372.65), CERCLA (40 CFR 372.65)

302.4), TSCA 12(b), or require an OSHA process safety plan.

This material is considered "articles" by the OSHA Hazard Communication Standard (29 CFR 1910.1200) and is exempted from the OSHA/HCS labeling

criteria.

This material is a container for carbon dioxide with no more than 4 fluid ounces of capacity and is considered "ORM-D" or "Consumer Commodity" by the Department of Transportation (49 CFR 173.101 and 173.306). This material is exempted from the DOT labeling criteria, except when offered for transportation

or transported by air.

SARA 311/312 Hazardous Categories

Fire hazard NO

Sudden release of pressure YES

Reactive

Immediate (acute) health hazard NO

Delayed (chronic) health hazard NO

State Regulations Massachusetts This material is listed

New Jersey This material is listed

Pennsylvania This material is listed

California This material is listed

Not regulated under CA Proposition 65.

SECTION 16 — OTHER INFORMATION

Hazard Rating Systems NFPA Ratings HMIS Ratings

Health = 2 Health = 1

Flammability = 0 Flammability = 0

Reactivity = 0 Physical Hazard = 3

Special = SA

Key to abbreviations

ACGIH American Conference of Governmental Industrial Hygienists

BCF Bioconcentration Factor

CAS Chemical Abstract Services

CERCLA Comprehensive Environmental Response, Compensation, and Liability Act

CFR United States Code of Federal Regulations

DOT Department of Transportation

GHS Globally Harmonized System of Classification and Labeling of Chemicals

IATA International Air Transport Association

IMDG International Maritime Dangerous Goods

Log Pow Logarithm of the octanol/water partition coefficient

NIOSH National Institute for Occupational Safety and Health

OSHA Occupational Safety and Healthy Organizaton

STEL Short-term Exposure Limit

BANZA STAMPING INDUSTRY CORP. BZ_PSDS_CO2_50ML Page 9 of 10

SARA Superfund Amendments and Reauthorization Act

TLV Threshold Limit Value

TSCA Toxic Substances Control Act

TWA Time Weighted Average

DISCLAIMER: This PSDS is intended to provide a brief summary of our knowledge and guidance regarding the use of this material. The information contained here has been compiled from sources considered by the BANZA Stamping Industry Corp. and its affiliates to be dependable and is accurate to the best of the Company's knowledge. It is not meant to be an all-inclusive document on worldwide hazard communication regulations.

This information is offered in good faith. Each user of this material needs to evaluate the conditions of use and design the appropriate protective mechanisms to prevent employee exposures, property damage or release to the environment. The BANZA Stamping Industry Corp. and its affiliates assume no responsibility for injury to the recipient or third persons, or for any damage to any property resulting from misuse of the product.

Final determination of suitability of any material is the sole responsibility of the user. All materials may present unknown hazards and should be used with caution. Although certain hazards are described herein, we cannot guarantee they are the only hazards that exist.