



Safety Data Sheet

acc. to OSHA HCS

Printing date 12/18/2017

Reviewed on 12/18/2017

1 Identification

- **Product identifier**
- **Trade name:** Muc-Off Motorcycle Dry Chain Lube
- **Article number:** 649, 649US, 604, 604US
- **Details of the supplier of the safety data sheet**
- **Manufacturer/Supplier:**
Muc-Off Ltd. 1st Floor, Unit 1, Concept Office
Park, Innovation Close, Poole, Dorset
BH12 4QT, UK
Tel: +44 (0)1202 307790
Fax: +44 (0)1202 746853
- **Information department:** Research & Development/E-mail: info@muc-off.com
- **Emergency telephone number:** CHEMTREC: 1-800-424-9300 24HR

2 Hazard(s) identification

- **Classification of the substance or mixture**



GHS02 Flame

Flam. Aerosol 1 H222-H229 Extremely flammable aerosol. Pressurized container: May burst if heated.



GHS08 Health hazard

Asp. Tox. 1 H304 May be fatal if swallowed and enters airways.



GHS07

Skin Irrit. 2 H315 Causes skin irritation.

STOT SE 3 H336 May cause drowsiness or dizziness.

- **Label elements**

- **GHS label elements**

The product is classified and labeled according to the Globally Harmonized System (GHS).

- **Hazard pictograms**



GHS02



GHS07



GHS08

- **Signal word** Danger

- **Hazard-determining components of labeling:**

Hydrocarbons, C7, n-alkanes, isoalkanes, cyclic

- **Hazard statements**

H222-H229 Extremely flammable aerosol. Pressurized container: May burst if heated.

H315 Causes skin irritation.

H336 May cause drowsiness or dizziness.

H304 May be fatal if swallowed and enters airways.

- **Precautionary statements**

P210 Keep away from heat/sparks/open flames/hot surfaces. - No smoking.

(Contd. on page 2)

Safety Data Sheet

acc. to OSHA HCS

Printing date 12/18/2017

Reviewed on 12/18/2017

Trade name: Muc-Off Motorcycle Dry Chain Lube

(Contd. of page 1)

- P211 Do not spray on an open flame or other ignition source.
 P251 Pressurized container: Do not pierce or burn, even after use.
 P260 Do not breathe spray.
 P271 Use only outdoors or in a well-ventilated area.
 P273 Avoid release to the environment.
 P280 Wear protective gloves / eye protection.
 P301+P310 If swallowed: Immediately call a doctor.
 P302+P352 If on skin: Wash with plenty of soap and water.
 P304+P340 IF INHALED: Remove person to fresh air and keep comfortable for breathing.
 P331 Do NOT induce vomiting.
 P403 Store in a well-ventilated place.
 P410+P412 Protect from sunlight. Do not expose to temperatures exceeding 50°C/122°F.
 P501 Dispose of contents/container in accordance with local/regional/national/international regulations.

· **Classification system:**

· **NFPA ratings (scale 0 - 4)**



· **WHMIS-ratings (scale 0 - 4)**



· **Other hazards**

· **Results of PBT and vPvB assessment**

· **PBT:** Not applicable.

· **vPvB:** Not applicable.

3 Composition/information on ingredients

· **Chemical characterization: Mixtures**

· **Description:** Active substance with propellant

· **Dangerous components:**

Reg.nr.: 01-2119475515-33	Hydrocarbons, C7, n-alkanes, isoalkanes, cyclic	50-<75%
CAS: 106-97-8 Reg.nr.: 01-2119474691-32	butane (containing < 0.1% butadiene (203-450-8))	25-<50%
CAS: 74-98-6 Reg.nr.: 01-2119486944-21	propane	2.5-<10%
	Thixocal 7000	1-<2.5%

4 First-aid measures

· **Description of first aid measures**

· **After inhalation:** In case of unconsciousness place patient stably in side position for transportation.

· **After skin contact:** Immediately wash with water and soap and rinse thoroughly.

· **After eye contact:** Rinse opened eye for several minutes under running water.

· **After swallowing:** Do not induce vomiting; immediately call for medical help.

· **Information for doctor:**

· **Most important symptoms and effects, both acute and delayed** No further relevant information available.

(Contd. on page 3)

Safety Data Sheet

acc. to OSHA HCS

Printing date 12/18/2017

Reviewed on 12/18/2017

Trade name: Muc-Off Motorcycle Dry Chain Lube

(Contd. of page 2)

- **Indication of any immediate medical attention and special treatment needed**
No further relevant information available.

5 Fire-fighting measures

- **Extinguishing media**
- **Suitable extinguishing agents:**
Water haze
Fire-extinguishing powder
Carbon dioxide
Alcohol resistant foam
- **For safety reasons unsuitable extinguishing agents:** Water with full jet
- **Special hazards arising from the substance or mixture** No further relevant information available.
- **Advice for firefighters**
- **Protective equipment:** Mount respiratory protective device.

6 Accidental release measures

- **Personal precautions, protective equipment and emergency procedures**
Wear protective equipment. Keep unprotected persons away.
- **Environmental precautions:**
Do not allow product to reach sewage system or any water course.
Inform respective authorities in case of seepage into water course or sewage system.
Do not allow to enter sewers/ surface or ground water.
- **Methods and material for containment and cleaning up:**
Ensure adequate ventilation.
Do not flush with water or aqueous cleansing agents
- **Reference to other sections**
See Section 7 for information on safe handling.
See Section 8 for information on personal protection equipment.
See Section 13 for disposal information.
- **Protective Action Criteria for Chemicals**

· PAC-1:

106-97-8	butane (containing < 0.1% butadiene (203-450-8))	5500* ppm
74-98-6	propane	5500* ppm
	calciumdihydroxide	15 mg/m ³
9002-84-0	Polytetrafluorethylene (PTFE)	12 mg/m ³
14808-60-7	Quartz (SiO ₂)	0.075 mg/m ³
5989-27-5	(R)-p-mentha-1,8-diene	15 ppm

· PAC-2:

106-97-8	butane (containing < 0.1% butadiene (203-450-8))	17000** ppm
74-98-6	propane	17000** ppm
	calciumdihydroxide	240 mg/m ³
9002-84-0	Polytetrafluorethylene (PTFE)	130 mg/m ³
14808-60-7	Quartz (SiO ₂)	33 mg/m ³
5989-27-5	(R)-p-mentha-1,8-diene	67 ppm

· PAC-3:

106-97-8	butane (containing < 0.1% butadiene (203-450-8))	53000*** ppm
74-98-6	propane	33000*** ppm
	calciumdihydroxide	1,500 mg/m ³

(Contd. on page 4)

Safety Data Sheet

acc. to OSHA HCS

Printing date 12/18/2017

Reviewed on 12/18/2017

Trade name: Muc-Off Motorcycle Dry Chain Lube

(Contd. of page 3)

9002-84-0	Polytetrafluorethylene (PTFE)	790 mg/m ³
14808-60-7	Quartz (SiO ₂)	200 mg/m ³
5989-27-5	(R)-p-mentha-1,8-diene	170 ppm

7 Handling and storage

- **Handling:**
- **Precautions for safe handling**
Ensure good ventilation/exhaustion at the workplace.
Open and handle receptacle with care.
- **Information about protection against explosions and fires:**
Do not spray on a naked flame or any incandescent material.
Keep ignition sources away - Do not smoke.
Protect against electrostatic charges.
Pressurized container: protect from sunlight and do not expose to temperatures exceeding 50°C, i.e. electric lights. Do not pierce or burn, even after use.
- **Conditions for safe storage, including any incompatibilities**
- **Storage:**
- **Requirements to be met by storerooms and receptacles:**
Store in a cool location.
Observe official regulations on storing packagings with pressurized containers.
- **Information about storage in one common storage facility:**
Observe official regulations on storing packagings with pressurized containers.
- **Further information about storage conditions:**
Keep receptacle tightly sealed.
Do not gas tight seal receptacle.
Store in cool, dry conditions in well sealed receptacles.
Protect from heat and direct sunlight.
- **Specific end use(s)** No further relevant information available.

8 Exposure controls/personal protection

- **Additional information about design of technical systems:** No further data; see item 7.
- **Control parameters**
- **Components with limit values that require monitoring at the workplace:**
The following constituents are the only constituents of the product which have a PEL, TLV or other recommended exposure limit.
At this time, the other constituents have no known exposure limits.

106-97-8 butane (containing < 0.1% butadiene (203-450-8))

REL	Long-term value: 1900 mg/m ³ , 800 ppm
TLV (EX)	Short-term value: 2370 mg/m ³ , 1000 ppm

74-98-6 propane

PEL	Long-term value: 1800 mg/m ³ , 1000 ppm
REL	Long-term value: 1800 mg/m ³ , 1000 ppm
TLV	refer to Appendix F in TLVs&BEIs book; D, EX

- **Additional information:** The lists that were valid during the creation were used as basis.

(Contd. on page 5)

US

Safety Data Sheet

acc. to OSHA HCS

Printing date 12/18/2017

Reviewed on 12/18/2017

Trade name: Muc-Off Motorcycle Dry Chain Lube

(Contd. of page 4)

- **Exposure controls**

- **Personal protective equipment:**

- **General protective and hygienic measures:**

Keep away from foodstuffs, beverages and feed.

Immediately remove all soiled and contaminated clothing.

Wash hands before breaks and at the end of work.

Do not inhale gases / fumes / aerosols.

Avoid contact with the skin.

Avoid contact with the eyes and skin.

- **Breathing equipment:**

In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use respiratory protective device that is independent of circulating air.

Filter AX/P2

Use suitable respiratory protective device in case of insufficient ventilation.

Filter A/P2

- **Protection of hands:**

Wear gloves for the protection against chemicals according to EN 374



Protective gloves

Solvent resistant gloves

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

- **Material of gloves**

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

Nitrile rubber, NBR

Recommended thickness of the material: ≥ 0.5 mm

- **Penetration time of glove material**

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

- **Eye protection:**

Safety glasses



Tightly sealed goggles

- **Body protection:** Use protective suit.

9 Physical and chemical properties

- **Information on basic physical and chemical properties**

- **General Information**

- **Appearance:**

Form: Aerosol

Color: Whitish

· **Odor:** Odorless

· **Odor threshold:** Not determined.

· **pH-value:** Not determined.

(Contd. on page 6)

Safety Data Sheet

acc. to OSHA HCS

Printing date 12/18/2017

Reviewed on 12/18/2017

Trade name: Muc-Off Motorcycle Dry Chain Lube

(Contd. of page 5)

· Change in condition	
Melting point/Melting range:	Undetermined.
Boiling point/Boiling range:	83-105 °C (181.4-221 °F)
· Flash point:	-97 °C (-142.6 °F)
· Flammability (solid, gaseous):	Not applicable.
· Ignition temperature:	365 °C (689 °F)
· Decomposition temperature:	Not determined.
· Auto igniting:	Product is not selfigniting.
· Danger of explosion:	Product is not explosive. However, formation of explosive air/vapor mixtures are possible.
· Explosion limits:	
Lower:	0.6 Vol %
Upper:	10.9 Vol %
· Vapor pressure at 20 °C (68 °F):	2,100 hPa (1.5 mm Hg)
· Density at 20 °C (68 °F):	0.69 g/cm ³ (5.76 lbs/gal)
· Relative density	Not determined.
· Vapor density	Not determined.
· Evaporation rate	Not applicable.
· Solubility in / Miscibility with Water:	Not miscible or difficult to mix.
· Partition coefficient (n-octanol/water):	Not determined.
· Viscosity:	
Dynamic:	Not determined.
Kinematic:	Not determined.
· Solvent content:	
Organic solvents:	83.8 %
Solids content:	11.8 %
· Other information	No further relevant information available.

10 Stability and reactivity

- **Reactivity** No further relevant information available.
- **Chemical stability**
- **Thermal decomposition / conditions to be avoided:** No decomposition if used according to specifications.
- **Possibility of hazardous reactions** No dangerous reactions known.
- **Conditions to avoid** No further relevant information available.
- **Incompatible materials:** No further relevant information available.
- **Hazardous decomposition products:** No dangerous decomposition products known.

US

(Contd. on page 7)

Safety Data Sheet

acc. to OSHA HCS

Printing date 12/18/2017

Reviewed on 12/18/2017

Trade name: Muc-Off Motorcycle Dry Chain Lube

(Contd. of page 6)

11 Toxicological information

- Information on toxicological effects
- Acute toxicity:

- LD/LC50 values that are relevant for classification:

Hydrocarbons, C7, n-alkanes, isoalkanes, cyclic

Oral	LD50	>5,840 mg/kg (rat)
Dermal	LD50	>2,920 mg/kg (rat)
Inhalative	LC50/4 h	23.3 mg/l (rat)

- Primary irritant effect:
- on the skin: Irritant to skin and mucous membranes.
- on the eye: No irritating effect.
- Sensitization: No sensitizing effects known.
- Additional toxicological information:
The product shows the following dangers according to internally approved calculation methods for preparations:
Irritant

- Carcinogenic categories

- IARC (International Agency for Research on Cancer)

9002-84-0	Polytetrafluorethylene (PTFE)	3
14808-60-7	Quartz (SiO ₂)	1
5989-27-5	(R)-p-mentha-1,8-diene	3

- NTP (National Toxicology Program)

14808-60-7	Quartz (SiO ₂)	K
93-08-3	Cetone d	R

- OSHA-Ca (Occupational Safety & Health Administration)

None of the ingredients is listed.

12 Ecological information

- Toxicity

- Aquatic toxicity:

Hydrocarbons, C7, n-alkanes, isoalkanes, cyclic

EL50 (72h)	10-30 mg/l (algae)
LC50/96h	>13.4 mg/l (Fish)
EC50/48h	3 mg/l (Daphnia magna)

- Persistence and degradability No further relevant information available.
- Behavior in environmental systems:
- Bioaccumulative potential No further relevant information available.
- Mobility in soil No further relevant information available.
- Ecotoxic effects:
- Remark: Toxic for fish
- Additional ecological information:
- General notes:
Water hazard class 2 (Self-assessment): hazardous for water
Do not allow product to reach ground water, water course or sewage system.
Danger to drinking water if even small quantities leak into the ground.
Also poisonous for fish and plankton in water bodies.
Toxic for aquatic organisms

(Contd. on page 8)

Safety Data Sheet

acc. to OSHA HCS

Printing date 12/18/2017

Reviewed on 12/18/2017

Trade name: Muc-Off Motorcycle Dry Chain Lube






(Contd. of page 7)

- **Results of PBT and vPvB assessment**
- **PBT:** Not applicable.
- **vPvB:** Not applicable.
- **Other adverse effects** No further relevant information available.

13 Disposal considerations

- **Waste treatment methods**
- **Recommendation:**
Must not be disposed of together with household garbage. Do not allow product to reach sewage system.
- **Uncleaned packagings:**
- **Recommendation:** Disposal must be made according to official regulations.

14 Transport information

- | | |
|---|---|
| · UN-Number | UN1950 |
| · DOT, ADR, ADN, IMDG, IATA | UN1950 |
| · UN proper shipping name | Aerosols, flammable |
| · DOT | UN1950 Aerosols, ENVIRONMENTALLY HAZARDOUS |
| · ADR, ADN | AEROSOLS (Hydrocarbons, C7, n-alkanes, isoalkanes, cyclic), |
| · IMDG | MARINE POLLUTANT |
| · IATA | AEROSOLS, flammable |
| · Transport hazard class(es) | |
| · DOT | |
|  | |
| · Class | 2.1 |
| · Label | 2.1 |
| · ADR | |
|   | |
| · Class | 2 5F Gases |
| · Label | 2.1 |
| · ADN | |
| · ADN/R Class: | 2 5F |
| · IMDG | |
|   | |
| · Class | 2.1 |

(Contd. on page 9)

Safety Data Sheet

acc. to OSHA HCS

Printing date 12/18/2017

Reviewed on 12/18/2017

Trade name: Muc-Off Motorcycle Dry Chain Lube

(Contd. of page 8)

· Label 2.1

· IATA



· Class 2.1

· Label 2.1

· Packing group

· DOT, ADR, IMDG, IATA Void

· Environmental hazards: Product contains environmentally hazardous substances: p-mentha-1,8(9)-diene, Hydrocarbons, C7, n-alkanes, isoalkanes, cyclic

· Marine pollutant: Yes

Symbol (fish and tree)

· Special marking (ADR): Symbol (fish and tree)

· Special precautions for user Warning: Gases

· Danger code (Kemler): -

· EMS Number: F-D, S-U

· Stowage Code SW1 Protected from sources of heat.

SW22 For AEROSOLS with a maximum capacity of 1 litre:

Category A. For AEROSOLS with a capacity above 1 litre:

Category B. For WASTE AEROSOLS: Category C, Clear of living quarters.

· Segregation Code SG69 For AEROSOLS with a maximum capacity of 1 litre:

Segregation as for class 9. Stow "separated from" class 1

except for division 1.4. For AEROSOLS with a capacity above

1 litre: Segregation as for the appropriate subdivision of class

2. For WASTE AEROSOLS: Segregation as for the

appropriate subdivision of class 2.

· Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code Not applicable.

· Transport/Additional information:

· ADR

· Excepted quantities (EQ) Code: E0

Not permitted as Excepted Quantity

· IMDG

· Limited quantities (LQ) 1L

· Excepted quantities (EQ) Code: E0

Not permitted as Excepted Quantity

· UN "Model Regulation": UN 1950 AEROSOLS, 2.1, ENVIRONMENTALLY HAZARDOUS

*

15 Regulatory information

· Safety, health and environmental regulations/legislation specific for the substance or mixture

· Sara

· Section 355 (extremely hazardous substances):

None of the ingredient is listed.

(Contd. on page 10)

US

Safety Data Sheet

acc. to OSHA HCS

Printing date 12/18/2017

Reviewed on 12/18/2017

Trade name: Muc-Off Motorcycle Dry Chain Lube

(Contd. of page 9)

· Section 313 (Specific toxic chemical listings):

None of the ingredients is listed.

· TSCA (Toxic Substances Control Act):

106-97-8 butane (containing < 0.1% butadiene (203-450-8))

74-98-6 propane

8042-47-5 Mineral Oil

calciumdihydroxide

9002-84-0 Polytetrafluorethylene (PTFE)

· TSCA new (21st Century Act) (Substances not listed)

Hydrocarbons, C7, n-alkanes, isoalkanes, cyclic

Thixocal 7000

· Proposition 65
· Chemicals known to cause cancer:

None of the ingredients is listed.

· Chemicals known to cause reproductive toxicity for females:

None of the ingredients is listed.

· Chemicals known to cause reproductive toxicity for males:

None of the ingredients is listed.

· Chemicals known to cause developmental toxicity:

None of the ingredients is listed.

· Cancerogenity categories
· EPA (Environmental Protection Agency)

None of the ingredients is listed.

· TLV (Threshold Limit Value established by ACGIH)
14808-60-7 Quartz (SiO₂)

A2

· MAK (German Maximum Workplace Concentration)
14808-60-7 Quartz (SiO₂)

1

· NIOSH-Ca (National Institute for Occupational Safety and Health)
14808-60-7 Quartz (SiO₂)
· National regulations:

Class	Share in %
NK	75-<100

· Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

· Department issuing SDS: Research & Development

· Date of preparation / last revision 12/18/2017 / 2

· Abbreviations and acronyms:

ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

DOT: US Department of Transportation

IATA: International Air Transport Association

ACGIH: American Conference of Governmental Industrial Hygienists

(Contd. on page 11)

Safety Data Sheet

acc. to OSHA HCS

Printing date 12/18/2017

Reviewed on 12/18/2017

Trade name: Muc-Off Motorcycle Dry Chain Lube

(Contd. of page 10)

EINECS: European Inventory of Existing Commercial Chemical Substances
ELINCS: European List of Notified Chemical Substances
CAS: Chemical Abstracts Service (division of the American Chemical Society)
NFPA: National Fire Protection Association (USA)
HMIS: Hazardous Materials Identification System (USA)
LC50: Lethal concentration, 50 percent
LD50: Lethal dose, 50 percent
PBT: Persistent, Bioaccumulative and Toxic
vPvB: very Persistent and very Bioaccumulative
NIOSH: National Institute for Occupational Safety
OSHA: Occupational Safety & Health
TLV: Threshold Limit Value
PEL: Permissible Exposure Limit
REL: Recommended Exposure Limit
Flam. Aerosol 1: Aerosols – Category 1
Skin Irrit. 2: Skin corrosion/irritation – Category 2
STOT SE 3: Specific target organ toxicity (single exposure) – Category 3
Asp. Tox. 1: Aspiration hazard – Category 1

US