SAFETY DATA SHEET

SECTION 1) CHEMICAL PRODUCT AND MANUFACTURER'S IDENTIFICATION

Product ID: MOOSE RACING ULTRA GLOW SILICONE SPRAY

Product Name: MOOSE RACING ULTRA GLOW SILICONE SPRAY

 Revision Date:
 May 01, 2023
 Date Printed:
 May 08, 2024

 Version:
 5.0
 Supersedes Date:
 Dec 14, 2022

Distributor's Name: MOOSE RACING

Address: 3501 Kennedy Road Janesville, WI 53545

Emergency Phone: 1-800-535-5053 Information Phone Number: (608) 758-1111

Fax:

Product/Recommended Uses: Vinyl/Plastic Coating

SECTION 2) HAZARDS IDENTIFICATION

Classification

Aerosols - Category 1

Gases Under Pressure - Liquefied Gas

Aspiration Hazard - Category 1

Skin Irritation - Category 2

Reproductive Toxicity - Category 2

Specific Target Organ Toxicity - Repeated Exposure - Category 2

Specific Target Organ Toxicity - Single Exposure (Narcotic Effects) - Category 3

Pictograms









Signal Word

Danger

Hazardous Statements - Physical

H222 - Extremely flammable aerosol

H280 - Contains gas under pressure; may explode if heated

Hazardous Statements - Health

H304 - May be fatal if swallowed and enters airways

H361f - Suspected of damaging fertility

H315 - Causes skin irritation

H373 - May cause damage to organs through prolonged or repeated exposure.

H336 - May cause drowsiness or dizziness

Precautionary Statements - General

- P101 If medical advice is needed, have product container or label at hand.
- P102 Keep out of reach of children.
- P103 Read label before use.

Precautionary Statements - Prevention

- P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
- P211 Do not spray on an open flame or other ignition source.
- P251 Do not pierce or burn, even after use.
- P201 Obtain special instructions before use.
- P202 Do not handle until all safety precautions have been read and understood.
- P280 Wear protective gloves, protective clothing, eye protection, and face protection.
- P264 Wash hands thoroughly after handling.
- P260 Do not breathe mist, vapor, or spray.
- P271 Use only outdoors or in a well-ventilated area.

Precautionary Statements - Response

- P314 Get medical attention if you feel unwell.
- P308 + P313 IF exposed or concerned: Get medical attention.
- P301 + P310 IF SWALLOWED: Immediately call a POISON CENTER or doctor.
- P331 Do NOT induce vomiting.
- P302 + P352 IF ON SKIN: Wash with plenty of soap and water.
- P332 + P313 If skin irritation occurs: Get medical advice/attention.
- P362 + P364 Take off contaminated clothing and wash it before reuse.
- P304 + P340 IF INHALED: Remove person to fresh air and keep comfortable for breathing.
- P312 Call a POISON CENTER or doctor if you feel unwell.

Precautionary Statements - Storage

- P410 + P412 Protect from sunlight. Do not expose to temperatures exceeding 50°C / 122°F.
- P403 + P405 Store in a well-ventilated place. Store locked up.

Precautionary Statements - Disposal

P501 - Dispose of contents and container in accordance with local, regional, national and international regulations.

SECTION 3) COMPOSITION/INFORMATION ON INGREDIENTS

CAS	Chemical Name	% By Weight
110-54-3	Hexane	25% - 50%
68476-86-8	Petroleum gases, liquefied, sweetened	25% - 50%
63148-62-9	Silicone	15% - 25%

Specific chemical identity and/or exact percentage (concentration) of the composition has been withheld to protect confidentiality.

SECTION 4) FIRST-AID MEASURES

Inhalation

Remove source of exposure or move person to fresh air and keep comfortable for breathing. If breathing is difficult, trained personnel should administer emergency oxygen if advised to do so by the POISON CENTER/doctor. If breathing has stopped, trained personnel should begin rescue breathing or, if the heart has stopped, immediately start cardiopulmonary resuscitation (CPR) or automated external defibrillation (AED). If you feel unwell/lf concerned: Get medical advice/attention.

Eye Contact

Rinse eyes cautiously with lukewarm, gently flowing water for 15 minutes, while holding the eyelids open. Remove contact lenses, if present and easy to do. Take care not to rinse contaminated water into the unaffected eye or onto the face. If eye irritation persists: Get medical advice/attention.

Skin Contact

Wipe off with a towel. Wash with soap and water. Get medical attention if irritation persists.

Ingestion

Ingestion is not a likely route of exposure. Get medical attention if you feel unwell.

Most Important Symptoms/Effects, Acute and Delayed

No data available.

Indication of Immediate Medical Attention and Special Treatment Needed

No data available.

SECTION 5) FIRE-FIGHTING MEASURES

Suitable Extinguishing Media

Foam, alcohol foam, carbon dioxide, dry chemical, water fog.

Unsuitable Extinguishing Media

Water may be ineffective but can be used to cool containers exposed to heat or flame.

Specific Hazards in Case of Fire

Closed containers may explode from internal pressure build-up when exposed to extreme heat and discharge contents. Liquid content of container will support combustion. Overexposure to decomposition products may cause a health hazard. Symptoms may not be readily apparent. Obtain medical attention. Hazardous decomposition products include carbon dioxide, carbon monoxide, and other toxic fumes.

Fire-fighting Procedures

Water may be used to cool containers to prevent pressure build-up and explosion when exposed to extreme heat.

Special Protective Actions

Wear goggles and use a self-contained breathing apparatus. If water is used, fog nozzles are preferred.

SECTION 6) ACCIDENTAL RELEASE MEASURES

Emergency Procedure

Avoid breathing vapors. Ventilate area. Remove all sources of ignition.

Recommended Equipment

Wear safety glasses with side shields. Use of gloves approved from relevant standards that meet or are equivalent to OSHA 29 CFR 1910.132.

Personal Precautions

Avoid breathing vapors. Ventilate area.

Environmental Precautions

Stop spill/release if it can be done safely.

Methods and Materials for Containment and Cleaning up

Contain and collect spillage with non-combustible, absorbent material e.g. sand, earth, vermiculite or diatomaceous earth and place in container for disposal according to local regulations.

SECTION 7) HANDLING AND STORAGE

General

Do not puncture or incinerate (burn) cans. Do not stick pins, nails, or any other sharp objects into opening on top of can. Do not spray in eyes. Do not take internally.

Ventilation Requirements

Use in a well-ventilated place.

Storage Room Requirements

Store and use in a cool, dry, well-ventilated area. Do not store above 120°F. See product label for additional information.

SECTION 8) EXPOSURE CONTROLS/PERSONAL PROTECTION

Eye protection

Wear safety glasses with side shields. Eyewash stations and showers should be available in areas where this material is used and stored.

Skin Protection

Use solvent-resistant protective gloves for prolonged or repeated contact.

Respiratory protection

Avoid breathing vapors. In restricted areas, use approved chemical/mechanical filters designed to remove a combination of particles and vapor. In confined areas, use an approved air line respirator or hood. A self-contained breathing apparatus is required for vapor concentrations above PEL/TLV limits.

Appropriate Engineering Controls

Ventilation should be sufficient to prevent inhalation of any vapors.

Chemical Name	OSHA TWA (mg/m3)	OSHA TWA (ppm)	OSHA STEL (mg/m3)	OSHA Carcinogen	OSHA Skin designation	OSHA Tables (Z1, Z2, Z3)	ACGIH TWA (mg/m3)	ACGIH TWA (ppm)
Petroleum gases, liquefied, sweetened	2000	500				1		
Hexane	1800	500				1		50

Chemical Name	NIOSH STEL (ppm)	ACGIH STEL (mg/m3)	ACGIH STEL (ppm)	ACGIH Carcinogen	ACGIH TLV Basis	ACGIH Notations	NIOSH TWA (mg/m3)	NIOSH TWA (ppm)
Petroleum gases, liquefied, sweetened								
Hexane					CNS imp; peripheral neuropathy; eye irr	Skin; BEI	180	50

Chemical Name	NIOSH STEL (mg/m3)	OSHA STEL (ppm)	NIOSH Carcinogen
Petroleum gases, liquefied, sweetened			
Hexane			

BEI - Substances for which there is a Biological Exposure Index or Indices, CNS - Central nervous system, imp - Impairment, irr - Irritation

SECTION 9) PHYSICAL AND CHEMICAL PROPERTIES

Physical and Chemical Properties

Density	5.62 lb/gal
Density VOC	4.77 lb/gal
% VOC	85.0%

Appearance Clear, colorless liquid

Odor Threshold N.A.

Odor Description Petroleum spirit

pH N.A. Water Solubility Insoluble

Flammability Flash point below 73°F / 23°C

Vapor Pressure N/A
Flash Point <73.0°F
Kinematic Viscosity <20 cSt (40°C)

Lower Explosion Level N.A.

Upper Explosion Level	N.A.
Melting Point	N.A.
Vapor Density	N.A.
Freezing Point	N.A.
Low Boiling Point	N.A.
High Boiling Point	N.A.
Decomposition Pt	N.A.
Auto Ignition Temp	N.A.
Evaporation Rate	N.A.

SECTION 10) STABILITY AND REACTIVITY

Stability

The product is stable under normal storage conditions.

Conditions To Avoid

High temperatures.

Incompatible Materials

No data available.

Hazardous Reactions/Polymerization

None known.

Hazardous Decomposition Products

Hazardous decomposition products may include carbon dioxide, carbon monoxide, and other toxic fumes.

SECTION 11) TOXICOLOGICAL INFORMATION

Likely Route of Exposure

Inhalation, ingestion, skin absorption.

Skin Corrosion/Irritation

Causes skin irritation

Serious Eye Damage/Irritation

Based on available data, the classification criteria are not met.

Carcinogenicity

Based on available data, the classification criteria are not met.

Germ Cell Mutagenicity

Based on available data, the classification criteria are not met.

Reproductive Toxicity

Suspected of damaging fertility

Respiratory/Skin Sensitization

Based on available data, the classification criteria are not met.

Specific Target Organ Toxicity - Single Exposure

May cause drowsiness or dizziness

Specific Target Organ Toxicity - Repeated Exposure

May cause damage to organs through prolonged or repeated exposure.

Aspiration Hazard

May be fatal if swallowed and enters airways

Acute Toxicity

Based on available data, the classification criteria are not met.

SECTION 12) ECOLOGICAL INFORMATION

Toxicity

Based on available data, the classification criteria are not met.

Persistence and Degradability

Expected to be readily biodegradable

Bioaccumulative Potential

Has the potential to bioaccumulate.

Mobility in Soil

If it enters soil, it will adsorb to soil particles and will not be mobile

Other Adverse Effects

No data available.

Results of the PBT and vPvB assessment

The substance is not PBT / vPvB.

SECTION 13) DISPOSAL CONSIDERATIONS

Waste Disposal

Under RCRA, it is the responsibility of the user of the product, to determine at the time of disposal whether the product meets RCRA criteria for hazardous waste. Waste management should be in full compliance with federal, state, and local laws.

Empty containers retain product residue which may exhibit hazards of material, therefore do not pressurize, cut, glaze, weld or use for any other purposes. Return drums to reclamation centers for proper cleaning and reuse.

SECTION 14) TRANSPORT INFORMATION

	U.S. DOT Information	IMDG Information	IATA Information
UN number:	UN1950	UN1950	UN1950
Proper shipping name:	Aerosols	Aerosols	Aerosols, flammable
Hazard class:	2.1	2.1	2.1
Packaging group:	N.A.	N.A.	N.A.
Hazardous substance (RQ):	No Data Available		
Marine Pollutant:	No Data Available	No Data Available	
Note / Special Provision:	Limited Quantity	Limited Quantity	Limited Quantity
Toxic-Inhalation Hazard:	No Data Available		


SECTION 15) REGULATORY INFORMATION

CAS	Chemical Name	% By Weight	Regulation List
110-54-3	Hexane	25% - 50%	SARA313, CERCLA, HAPS, SARA312, VOC, TSCA, ACGIH, California Proposition 65, OSHA
68476-86-8	Petroleum gases, liquefied, sweetened	25% - 50%	SARA312, TSCA, OSHA
63148-62-9	Silicone	15% - 25%	SARA312, TSCA

SECTION 16) OTHER INFORMATION

Glossary

ACGIH- American Conference of Governmental Industrial Hygienists; ANSI- American National Standards Institute; Canadian TDG-Canadian Transportation of Dangerous Goods; CAS- Chemical Abstract Service; Chemtrec- Chemical Transportation Emergency Center (US); CHIP- Chemical Hazard Information and Packaging; DSL- Domestic Substances List; EC- Equivalent Concentration; EH40 (UK)-HSE Guidance Note EH40 Occupational Exposure Limits; EPCRA- Emergency Planning and Community Right-To-Know Act; ESL- Effects screening levels; HMIS- Hazardous Material Information Service; LC- Lethal Concentration; LD- Lethal Dose; NFPA- National Fire Protection Association; OEL- Occupational Exposure Limits; OSHA- Occupational Safety and Health Administration, US Department of Labor; PEL- Permissible Exposure Limit; SARA (Title III)- Superfund Amendments and Reauthorization Act; SARA 313- Superfund Amendments and Reauthorization Act, Section 313; SCBA- Self-Contained Breathing Apparatus; STEL- Short Term Exposure Limit; TCEQ- Texas Commission on Environmental Quality; TLV- Threshold Limit Value; TSCA- Toxic Substances Control Act Public Law 94-469; TWA- Time Weighted Value; US DOT- US Department of Transportation; WHMIS- Workplace Hazardous Materials Information System.



(*) - Chronic effects

Caution: HMIS® ratings are based on a 0-4 rating scale, with 0 representing minimal hazards or risks, and 4 representing significant hazards or risks

Version 5.0:

Revision Date: May 01, 2023

DISCLAIMER

To the best of our knowledge, the information contained herein is accurate. However, neither the above named supplier nor any of its subsidiaries assumes any liability whatsoever for the accuracy or completeness of the information contained herein. Final determination of suitability of any material is the sole responsibility of the user. All materials may present unknown hazards and should be used with caution. Although certain hazards are described herein, we cannot guarantee that these are the only hazards that exist. The above information pertains to this product as currently formulated, and is based on the information available at this time. Addition of reducers or other additives to this product may substantially alter the composition and hazards of the product. Since conditions of use are outside our control, we make no warranties, express or implied, and assume no liability in connection with any use of this information.