

20186 MOTORBIKE 4T SYNTH 10W-60 OFFROAD RACE 1L

Liqui Moly GmbH

Chemwatch: 64-3514

Version No: 2.1.1.1

Safety Data Sheet according to OSHA HazCom Standard (2012) requirements

Chemwatch Hazard Alert Code: 1

Issue Date: 15/07/2016

Print Date: 12/12/2016

S.GHS.USA.EN

SECTION 1 IDENTIFICATION

Product Identifier

Product name	20186 MOTORBIKE 4T SYNTH 10W-60 OFFROAD RACE 1L
Synonyms	Item No: 20186
Other means of identification	Not Available

Recommended use of the chemical and restrictions on use

Relevant identified uses	Motor oil.
--------------------------	------------

Name, address, and telephone number of the chemical manufacturer, importer, or other responsible party

Registered company name	Liqui Moly GmbH
Address	Jerg-Wieland-Strasse 4 Ulm D-89081 Germany
Telephone	+49 731 1420 0
Fax	+49 731 1420 82
Website	Not Available
Email	Not Available

Emergency phone number

Association / Organisation	INFOTRAC
Emergency telephone numbers	+1800 535 5053 (US & Canada)
Other emergency telephone numbers	+1 352 323 3500 (International)

SECTION 2 HAZARD(S) IDENTIFICATION


Classification of the substance or mixture

CHEMWATCH HAZARD RATINGS

	Min	Max
Flammability	1	
Toxicity	0	
Body Contact	1	
Reactivity	1	
Chronic	0	

0 = Minimum
1 = Low
2 = Moderate
3 = High
4 = Extreme

NFPA 704 diamond



Note: The hazard category numbers found in GHS classification in section 2 of this SDSs are NOT to be used to fill in the NFPA 704 diamond. Blue = Health Red = Fire Yellow = Reactivity White = Special (Oxidizer or water reactive substances)

Classification	Eye Irritation Category 2B
----------------	----------------------------

Label elements

GHS label elements	Not Applicable
--------------------	----------------

SIGNAL WORD	WARNING
-------------	----------------

Hazard statement(s)

H320	Causes eye irritation
------	-----------------------

Hazard(s) not otherwise specified

Not Applicable

Precautionary statement(s) Prevention

P264	Wash all exposed external body areas thoroughly after handling.
------	---

Precautionary statement(s) Response

P305+P351+P338	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P337+P313	If eye irritation persists: Get medical advice/attention.

Precautionary statement(s) Storage

Not Applicable

Precautionary statement(s) Disposal

Not Applicable

SECTION 3 COMPOSITION / INFORMATION ON INGREDIENTS**Substances**

See section below for composition of Mixtures

Mixtures

CAS No	%[weight]	Name
Not avail.	1-5	<u>mineral oil</u>
		contains one or more of the following;
64742-54-7.		<u>paraffinic distillate, heavy, hydrotreated (severe)</u>
64742-65-0.		<u>paraffinic distillate, heavy, solvent-dewaxed (severe)</u>
64742-55-8.		<u>paraffinic distillate, light, hydrotreated (severe)</u>
64742-56-9.		<u>paraffinic distillate, light, solvent-dewaxed (severe)</u>

The specific chemical identity and/or exact percentage (concentration) of composition has been withheld as a trade secret.

SECTION 4 FIRST-AID MEASURES**Description of first aid measures**

Eye Contact	If this product comes in contact with the eyes: - Wash out immediately with fresh running water. - Ensure complete irrigation of the eye by keeping eyelids apart and away from eye and moving the eyelids by occasionally lifting the upper and lower lids. - Seek medical attention without delay; if pain persists or recurs seek medical attention. - Removal of contact lenses after an eye injury should only be undertaken by skilled personnel.
Skin Contact	If skin contact occurs: - Immediately remove all contaminated clothing, including footwear. - Flush skin and hair with running water (and soap if available). - Seek medical attention in event of irritation.
Inhalation	- If fumes, aerosols or combustion products are inhaled remove from contaminated area. - Other measures are usually unnecessary.
Ingestion	- Immediately give a glass of water. - First aid is not generally required. If in doubt, contact a Poisons Information Centre or a doctor.

Most important symptoms and effects, both acute and delayed

See Section 11

Indication of any immediate medical attention and special treatment needed

Treat symptomatically.

SECTION 5 FIRE-FIGHTING MEASURES**Extinguishing media**

- Foam.
- Dry chemical powder.
- BCF (where regulations permit).
- Carbon dioxide.

Special hazards arising from the substrate or mixture

Fire Incompatibility	Avoid contamination with oxidising agents i.e. nitrates, oxidising acids, chlorine bleaches, pool chlorine etc. as ignition may result
-----------------------------	--

Special protective equipment and precautions for fire-fighters

Fire Fighting	- Alert Fire Brigade and tell them location and nature of hazard. - Wear full body protective clothing with breathing apparatus. - Prevent, by any means available, spillage from entering drains or water course. - Use water delivered as a fine spray to control fire and cool adjacent area.
Fire/Explosion Hazard	'' - Combustible. - Slight fire hazard when exposed to heat or flame. - Heating may cause expansion or decomposition leading to violent rupture of containers. - On combustion, may emit toxic fumes of carbon monoxide (CO). Combustion products include:

Continued...

20186 MOTORBIKE 4T SYNTH 10W-60 OFFROAD RACE 1L

carbon dioxide (CO₂)
 other pyrolysis products typical of burning organic material.
 May emit poisonous fumes.
 May emit corrosive fumes.

SECTION 6 ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency procedures

See section 8

Environmental precautions

See section 12

Methods and material for containment and cleaning up

Minor Spills	- Remove all ignition sources. - Clean up all spills immediately. - Avoid breathing vapours and contact with skin and eyes. - Control personal contact with the substance, by using protective equipment.
Major Spills	Moderate hazard. - Clear area of personnel and move upwind. - Alert Fire Brigade and tell them location and nature of hazard. - Wear breathing apparatus plus protective gloves.

Personal Protective Equipment advice is contained in Section 8 of the SDS.

SECTION 7 HANDLING AND STORAGE

Precautions for safe handling

Safe handling	- Avoid all personal contact, including inhalation. - Wear protective clothing when risk of exposure occurs. - Use in a well-ventilated area. - Prevent concentration in hollows and sumps. DO NOT allow clothing wet with material to stay in contact with skin
Other information	- Store in original containers. - Keep containers securely sealed. - No smoking, naked lights or ignition sources. - Store in a cool, dry, well-ventilated area.

Conditions for safe storage, including any incompatibilities

Suitable container	- Metal can or drum - Packaging as recommended by manufacturer. - Check all containers are clearly labelled and free from leaks.
Storage incompatibility	Avoid reaction with oxidising agents

SECTION 8 EXPOSURE CONTROLS / PERSONAL PROTECTION

Control parameters

OCCUPATIONAL EXPOSURE LIMITS (OEL)

INGREDIENT DATA

Source	Ingredient	Material name	TWA	STEL	Peak	Notes
US OSHA Permissible Exposure Levels (PELs) - Table Z1	mineral oil	Oil mist, mineral	5 mg/m ³	Not Available	Not Available	Not Available
US ACGIH Threshold Limit Values (TLV)	mineral oil	Mineral oil, excluding metal working fluids - Pure, highly and severely refined / Mineral oil, excluding metal working fluids - Poorly and mildly refined	5 mg/m ³	Not Available	Not Available	TLV® Basis: URT irr
US NIOSH Recommended Exposure Limits (RELs)	mineral oil	Heavy mineral oil mist, Paraffin oil mist, White mineral oil mist	5 mg/m ³	10 mg/m ³	Not Available	Not Available
US OSHA Permissible Exposure Levels (PELs) - Table Z1	paraffinic distillate, heavy, hydrotreated (severe)	Oil mist, mineral	5 mg/m ³	Not Available	Not Available	Not Available
US ACGIH Threshold Limit Values (TLV)	paraffinic distillate, heavy, hydrotreated (severe)	Mineral oil, excluding metal working fluids - Pure, highly and severely refined / Mineral oil, excluding metal working fluids - Poorly and mildly refined	5 mg/m ³	Not Available	Not Available	TLV® Basis: URT irr
US NIOSH Recommended Exposure Limits (RELs)	paraffinic distillate, heavy, hydrotreated (severe)	Heavy mineral oil mist, Paraffin oil mist, White mineral oil mist	5 mg/m ³	10 mg/m ³	Not Available	Not Available
US OSHA Permissible Exposure Levels (PELs) - Table Z1	paraffinic distillate, heavy, solvent-dewaxed (severe)	Oil mist, mineral	5 mg/m ³	Not Available	Not Available	Not Available
US ACGIH Threshold Limit Values (TLV)	paraffinic distillate, heavy, solvent-dewaxed (severe)	Mineral oil, excluding metal working fluids - Pure, highly and severely refined / Mineral oil, excluding metal working fluids - Poorly and mildly refined	5 mg/m ³	Not Available	Not Available	TLV® Basis: URT irr

Continued...

20186 MOTORBIKE 4T SYNTH 10W-60 OFFROAD RACE 1L

US NIOSH Recommended Exposure Limits (RELs)	paraffinic distillate, heavy, solvent-dewaxed (severe)	Heavy mineral oil mist, Paraffin oil mist, White mineral oil mist	5 mg/m ³	10 mg/m ³	Not Available	Not Available
US OSHA Permissible Exposure Levels (PELs) - Table Z1	paraffinic distillate, light, hydrotreated (severe)	Oil mist, mineral	5 mg/m ³	Not Available	Not Available	Not Available
US ACGIH Threshold Limit Values (TLV)	paraffinic distillate, light, hydrotreated (severe)	Mineral oil, excluding metal working fluids - Pure, highly and severely refined / Mineral oil, excluding metal working fluids - Poorly and mildly refined	5 mg/m ³	Not Available	Not Available	TLV® Basis: URT irr
US NIOSH Recommended Exposure Limits (RELs)	paraffinic distillate, light, hydrotreated (severe)	Heavy mineral oil mist, Paraffin oil mist, White mineral oil mist	5 mg/m ³	10 mg/m ³	Not Available	Not Available
US OSHA Permissible Exposure Levels (PELs) - Table Z1	paraffinic distillate, light, solvent-dewaxed (severe)	Oil mist, mineral	5 mg/m ³	Not Available	Not Available	Not Available
US ACGIH Threshold Limit Values (TLV)	paraffinic distillate, light, solvent-dewaxed (severe)	Mineral oil, excluding metal working fluids - Pure, highly and severely refined / Mineral oil, excluding metal working fluids - Poorly and mildly refined	5 mg/m ³	Not Available	Not Available	TLV® Basis: URT irr
US NIOSH Recommended Exposure Limits (RELs)	paraffinic distillate, light, solvent-dewaxed (severe)	Heavy mineral oil mist, Paraffin oil mist, White mineral oil mist	5 mg/m ³	10 mg/m ³	Not Available	Not Available

EMERGENCY LIMITS

Ingredient	Material name	TEEL-1	TEEL-2	TEEL-3
paraffinic distillate, heavy, solvent-dewaxed (severe)	Pump oil; (petroleum distillates, solvent de-waxed heavy paraffinic)	140 mg/m ³	1,500 mg/m ³	8,900 mg/m ³

Ingredient	Original IDLH	Revised IDLH
mineral oil	Not Available	Not Available
paraffinic distillate, heavy, hydrotreated (severe)	Not Available	Not Available
paraffinic distillate, heavy, solvent-dewaxed (severe)	Not Available	Not Available
paraffinic distillate, light, hydrotreated (severe)	Not Available	Not Available
paraffinic distillate, light, solvent-dewaxed (severe)	Not Available	Not Available

Exposure controls

Appropriate engineering controls	Engineering controls are used to remove a hazard or place a barrier between the worker and the hazard. Well-designed engineering controls can be highly effective in protecting workers and will typically be independent of worker interactions to provide this high level of protection. The basic types of engineering controls are: Process controls which involve changing the way a job activity or process is done to reduce the risk. Enclosure and/or isolation of emission source which keeps a selected hazard "physically" away from the worker and ventilation that strategically "adds" and "removes" air in the work environment.
Personal protection	
Eye and face protection	▶ Safety glasses with side shields. ▶ Chemical goggles. ▶ Contact lenses may pose a special hazard; soft contact lenses may absorb and concentrate irritants. A written policy document, describing the wearing of lenses or restrictions on use, should be created for each workplace or task.
Skin protection	See Hand protection below
Hands/feet protection	▶ Wear chemical protective gloves, e.g. PVC. ▶ Wear safety footwear or safety gumboots, e.g. Rubber The selection of suitable gloves does not only depend on the material, but also on further marks of quality which vary from manufacturer to manufacturer. Where the chemical is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application. The exact break through time for substances has to be obtained from the manufacturer of the protective gloves and has to be observed when making a final choice. Personal hygiene is a key element of effective hand care.
Body protection	See Other protection below
Other protection	▶ Overalls. ▶ P.V.C. apron. ▶ Barrier cream.
Thermal hazards	Not Available

Respiratory protection

Type A-P Filter of sufficient capacity. (AS/NZS 1716 & 1715, EN 143:2000 & 149:2001, ANSI Z88 or national equivalent)

Where the concentration of gas/particulates in the breathing zone, approaches or exceeds the "Exposure Standard" (or ES), respiratory protection is required.

Degree of protection varies with both face-piece and Class of filter; the nature of protection varies with Type of filter.

Required Minimum Protection Factor	Half-Face Respirator	Full-Face Respirator	Powered Air Respirator
up to 10 x ES	A-AUS P2	-	A-PAPR-AUS / Class 1 P2

20186 MOTORBIKE 4T SYNTH 10W-60 OFFROAD RACE 1L

up to 50 x ES	-	A-AUS / Class 1 P2	-
up to 100 x ES	-	A-2 P2	A-PAPR-2 P2 ^

^ - Full-face

A(All classes) = Organic vapours, B AUS or B1 = Acid gasses, B2 = Acid gas or hydrogen cyanide(HCN), B3 = Acid gas or hydrogen cyanide(HCN), E = Sulfur dioxide(SO2), G = Agricultural chemicals, K = Ammonia(NH3), Hg = Mercury, NO = Oxides of nitrogen, MB = Methyl bromide, AX = Low boiling point organic compounds(below 65 degC)

Cartridge respirators should never be used for emergency ingress or in areas of unknown vapour concentrations or oxygen content. The wearer must be warned to leave the contaminated area immediately on detecting any odours through the respirator. The odour may indicate that the mask is not functioning properly, that the vapour concentration is too high, or that the mask is not properly fitted. Because of these limitations, only restricted use of cartridge respirators is considered appropriate.

SECTION 9 PHYSICAL AND CHEMICAL PROPERTIES

Information on basic physical and chemical properties

Appearance	Brown colour liquid with characteristic odour; not miscible with water.		
Physical state	Liquid	Relative density (Water = 1)	0.85
Odour	Not Available	Partition coefficient n-octanol / water	Not Available
Odour threshold	Not Available	Auto-ignition temperature (°C)	Not Available
pH (as supplied)	Not Applicable	Decomposition temperature	Not Available
Melting point / freezing point (°C)	Not Available	Viscosity (cSt)	164
Initial boiling point and boiling range (°C)	Not Available	Molecular weight (g/mol)	Not Applicable
Flash point (°C)	236	Taste	Not Available
Evaporation rate	Not Available	Explosive properties	Not Available
Flammability	Not Applicable	Oxidising properties	Not Available
Upper Explosive Limit (%)	Not Available	Surface Tension (dyn/cm or mN/m)	Not Available
Lower Explosive Limit (%)	Not Available	Volatile Component (%vol)	Not Available
Vapour pressure (kPa)	Not Available	Gas group	Not Available
Solubility in water (g/L)	Immiscible	pH as a solution (1%)	Not Available
Vapour density (Air = 1)	Not Available	VOC g/L	Not Available

SECTION 10 STABILITY AND REACTIVITY

Reactivity	See section 7
Chemical stability	▶ Unstable in the presence of incompatible materials. ▶ Product is considered stable. ▶ Hazardous polymerisation will not occur.
Possibility of hazardous reactions	See section 7
Conditions to avoid	See section 7
Incompatible materials	See section 7
Hazardous decomposition products	See section 5

SECTION 11 TOXICOLOGICAL INFORMATION

Information on toxicological effects

Inhaled	The material is not thought to produce adverse health effects or irritation of the respiratory tract (as classified by EC Directives using animal models). Nevertheless, good hygiene practice requires that exposure be kept to a minimum and that suitable control measures be used in an occupational setting.
Ingestion	The material has NOT been classified by EC Directives or other classification systems as "harmful by ingestion". This is because of the lack of corroborating animal or human evidence.
Skin Contact	There is some evidence to suggest that this material can cause inflammation of the skin on contact in some persons. Open cuts, abraded or irritated skin should not be exposed to this material Entry into the blood-stream, through, for example, cuts, abrasions or lesions, may produce systemic injury with harmful effects. Examine the skin prior to the use of the material and ensure that any external damage is suitably protected.
Eye	There is some evidence to suggest that this material can cause eye irritation and damage in some persons.
Chronic	Substance accumulation, in the human body, may occur and may cause some concern following repeated or long-term occupational exposure.

20186 MOTORBIKE 4T SYNTH 10W-60 OFFROAD RACE 1L	TOXICITY	IRRITATION
	Not Available	Not Available
mineral oil	TOXICITY	IRRITATION
	Not Available	Not Available

20186 MOTORBIKE 4T SYNTH 10W-60 OFFROAD RACE 1L

paraffinic distillate, heavy, hydrotreated (severe)	TOXICITY	IRRITATION
	Dermal (rabbit) LD50: >2000 mg/kg ^[1]	Not Available
	Inhalation (rat) LC50: >3.9 mg/l/4hr ^[1]	
	Inhalation (rat) LC50: >4.7 mg/l/4hr ^[1]	
	Inhalation (rat) LC50: >5 mg/l/4hr ^[1]	
	Inhalation (rat) LC50: >5.2 mg/l/4hr ^[1]	
	Inhalation (rat) LC50: >5.3 mg/l/4hr ^[1]	
	Inhalation (rat) LC50: 10.5 mg/l/4hr ^[1]	
	Inhalation (rat) LC50: 5.7 mg/l/4hr ^[1]	
	Inhalation (rat) LC50: 9.6 mg/l/4hr ^[1]	
	Oral (rat) LD50: >2000 mg/kg ^[1]	
paraffinic distillate, heavy, solvent-dewaxed (severe)	TOXICITY	IRRITATION
	Dermal (rabbit) LD50: >2000 mg/kg ^[1]	Not Available
	Inhalation (rat) LC50: >3.9 mg/l/4hr ^[1]	
	Inhalation (rat) LC50: >4.7 mg/l/4hr ^[1]	
	Inhalation (rat) LC50: >5.2 mg/l/4hr ^[1]	
	Inhalation (rat) LC50: >5.3 mg/l/4hr ^[1]	
	Inhalation (rat) LC50: 10.5 mg/l/4hr ^[1]	
	Inhalation (rat) LC50: 5.7 mg/l/4hr ^[1]	
	Inhalation (rat) LC50: 9.6 mg/l/4hr ^[1]	
	Oral (rat) LD50: >2000 mg/kg ^[1]	
paraffinic distillate, light, hydrotreated (severe)	TOXICITY	IRRITATION
	Dermal (rabbit) LD50: >2000 mg/kg ^[1]	Not Available
	Inhalation (rat) LC50: 3.9 mg/L/4hr ^[2]	
	Oral (rat) LD50: >2000 mg/kg ^[1]	
paraffinic distillate, light, solvent-dewaxed (severe)	TOXICITY	IRRITATION
	Dermal (rabbit) LD50: >2000 mg/kg ^[1]	Not Available
	Inhalation (rat) LC50: >3.9 mg/l/4hr ^[1]	
	Inhalation (rat) LC50: >4.7 mg/l/4hr ^[1]	
	Inhalation (rat) LC50: >5 mg/l/4hr ^[1]	
	Inhalation (rat) LC50: >5.2 mg/l/4hr ^[1]	
	Inhalation (rat) LC50: >5.3 mg/l/4hr ^[1]	
	Inhalation (rat) LC50: 10.5 mg/l/4hr ^[1]	
	Inhalation (rat) LC50: 5.7 mg/l/4hr ^[1]	
	Inhalation (rat) LC50: 9.6 mg/l/4hr ^[1]	
	Oral (rat) LD50: >2000 mg/kg ^[1]	

Legend:

1. Value obtained from Europe ECHA Registered Substances - Acute toxicity 2.* Value obtained from manufacturer's SDS. Unless otherwise specified data extracted from RTECS - Register of Toxic Effect of chemical Substances

MINERAL OIL	Toxicity and Irritation data for petroleum-based mineral oils are related to chemical components and vary as does the composition and source of the original crude. A small but definite risk of occupational skin cancer occurs in workers exposed to persistent skin contamination by oils over a period of years. This risk has been attributed to the presence of certain polycyclic aromatic hydrocarbons (PAH) (typified by benz[a]pyrene). Petroleum oils which are solvent refined/extracted or severely hydrotreated, contain very low concentrations of both.
PARAFFINIC DISTILLATE, LIGHT, HYDROTREATED (SEVERE)	* Q8 MSDS
PARAFFINIC DISTILLATE, HEAVY, HYDROTREATED (SEVERE) & PARAFFINIC DISTILLATE, HEAVY, SOLVENT-DEWAXED (SEVERE) & PARAFFINIC DISTILLATE, LIGHT, HYDROTREATED	The materials included in the Lubricating Base Oils category are related from both process and physical-chemical perspectives; The potential toxicity of a specific distillate base oil is inversely related to the severity or extent of processing the oil has undergone, since: ▶ The adverse effects of these materials are associated with undesirable components, and ▶ The levels of the undesirable components are inversely related to the degree of processing; ▶ Distillate base oils receiving the same degree or extent of processing will have similar toxicities; ▶ The potential toxicity of <i>residual</i> base oils is independent of the degree of processing the oil receives. ▶ The reproductive and developmental toxicity of the distillate base oils is inversely related to the degree of processing. Unrefined & mildly refined distillate base oils contain the highest levels of undesirable components, have the largest variation of hydrocarbon molecules and

20186 MOTORBIKE 4T SYNTH 10W-60 OFFROAD RACE 1L

(SEVERE) & PARAFFINIC DISTILLATE, LIGHT, SOLVENT-DEWAXED (SEVERE)	have shown the highest potential carcinogenic and mutagenic activities. Highly and severely refined distillate base oils are produced from unrefined and mildly refined oils by removing or transforming undesirable components.
PARAFFINIC DISTILLATE, HEAVY, HYDROTREATED (SEVERE) & PARAFFINIC DISTILLATE, HEAVY, SOLVENT-DEWAXED (SEVERE) & PARAFFINIC DISTILLATE, LIGHT, HYDROTREATED (SEVERE) & PARAFFINIC DISTILLATE, LIGHT, SOLVENT-DEWAXED (SEVERE)	For highly and severely refined distillate base oils: In animal studies, the acute, oral, semilethal dose is >5g/kg body weight and the semilethal dose by skin contact is >2g/kg body weight. The semilethal concentration for inhalation is 2.18 to >4 mg/L. The materials have varied from "non-irritating" to "moderately irritating" when tested for skin and eye irritation. Testing for sensitisation has been negative.
PARAFFINIC DISTILLATE, HEAVY, HYDROTREATED (SEVERE) & PARAFFINIC DISTILLATE, HEAVY, SOLVENT-DEWAXED (SEVERE) & PARAFFINIC DISTILLATE, LIGHT, HYDROTREATED (SEVERE) & PARAFFINIC DISTILLATE, LIGHT, SOLVENT-DEWAXED (SEVERE)	The substance is classified by IARC as Group 3: NOT classifiable as to its carcinogenicity to humans. Evidence of carcinogenicity may be inadequate or limited in animal testing.
PARAFFINIC DISTILLATE, HEAVY, SOLVENT-DEWAXED (SEVERE) & PARAFFINIC DISTILLATE, LIGHT, HYDROTREATED (SEVERE) & PARAFFINIC DISTILLATE, LIGHT, SOLVENT-DEWAXED (SEVERE)	No significant acute toxicological data identified in literature search.

Acute Toxicity	☐	Carcinogenicity	☐
Skin Irritation/Corrosion	☐	Reproductivity	☐
Serious Eye Damage/Irritation	✓	STOT - Single Exposure	☐
Respiratory or Skin sensitisation	☐	STOT - Repeated Exposure	☐
Mutagenicity	☐	Aspiration Hazard	☐

Legend: ✗ – Data available but does not fill the criteria for classification
✓ – Data required to make classification available
☐ – Data Not Available to make classification

SECTION 12 ECOLOGICAL INFORMATION

Toxicity

Ingredient	Endpoint	Test Duration (hr)	Species	Value	Source
paraffinic distillate, heavy, hydrotreated (severe)	EC50	48	Crustacea	>1000mg/L	1
paraffinic distillate, heavy, hydrotreated (severe)	EC50	96	Algae or other aquatic plants	>1000mg/L	1
paraffinic distillate, heavy, hydrotreated (severe)	EC50	96	Algae or other aquatic plants	>1000mg/L	1
paraffinic distillate, heavy, hydrotreated (severe)	NOEC	504	Crustacea	>1mg/L	1
paraffinic distillate, heavy, solvent-dewaxed (severe)	EC50	48	Crustacea	>1000mg/L	1
paraffinic distillate, heavy, solvent-dewaxed (severe)	EC50	96	Algae or other aquatic plants	>1000mg/L	1
paraffinic distillate, heavy, solvent-dewaxed (severe)	EC50	96	Algae or other aquatic plants	>1000mg/L	1
paraffinic distillate, heavy, solvent-dewaxed (severe)	NOEC	504	Crustacea	>1mg/L	1
paraffinic distillate, light, hydrotreated (severe)	EC50	48	Crustacea	>1000mg/L	1
paraffinic distillate, light, hydrotreated (severe)	EC50	48	Crustacea	>10000mg/L	1
paraffinic distillate, light, hydrotreated (severe)	NOEC	504	Crustacea	>1mg/L	1

Continued...

20186 MOTORBIKE 4T SYNTH 10W-60 OFFROAD RACE 1L

paraffinic distillate, light, solvent-dewaxed (severe)	EC50	48	Crustacea	>1000mg/L	1
paraffinic distillate, light, solvent-dewaxed (severe)	EC50	48	Crustacea	>1000mg/L	1
paraffinic distillate, light, solvent-dewaxed (severe)	NOEC	504	Crustacea	>1mg/L	1
Legend:	Extracted from 1. IUCLID Toxicity Data 2. Europe ECHA Registered Substances - Ecotoxicological Information - Aquatic Toxicity 3. EPIWIN Suite V3.12 - Aquatic Toxicity Data (Estimated) 4. US EPA, Ecotox database - Aquatic Toxicity Data 5. ECETOC Aquatic Hazard Assessment Data 6. NITE (Japan) - Bioconcentration Data 7. METI (Japan) - Bioconcentration Data 8. Vendor Data				

DO NOT discharge into sewer or waterways.

Persistence and degradability

Ingredient	Persistence: Water/Soil	Persistence: Air
	No Data available for all ingredients	No Data available for all ingredients

Bioaccumulative potential

Ingredient	Bioaccumulation
	No Data available for all ingredients

Mobility in soil

Ingredient	Mobility
	No Data available for all ingredients

SECTION 13 DISPOSAL CONSIDERATIONS

Waste treatment methods

Product / Packaging disposal	- DO NOT allow wash water from cleaning or process equipment to enter drains. - It may be necessary to collect all wash water for treatment before disposal. - In all cases disposal to sewer may be subject to local laws and regulations and these should be considered first. - Where in doubt contact the responsible authority. - Recycle wherever possible or consult manufacturer for recycling options. - Consult State Land Waste Authority for disposal. - Bury or incinerate residue at an approved site. - Recycle containers if possible, or dispose of in an authorised landfill.
------------------------------	---

SECTION 14 TRANSPORT INFORMATION

Labels Required

Marine Pollutant	NO
------------------	----

Land transport (DOT): NOT REGULATED FOR TRANSPORT OF DANGEROUS GOODS

Air transport (ICAO-IATA / DGR): NOT REGULATED FOR TRANSPORT OF DANGEROUS GOODS

Sea transport (IMDG-Code / GGVSee): NOT REGULATED FOR TRANSPORT OF DANGEROUS GOODS

Transport in bulk according to Annex II of MARPOL and the IBC code

Not Applicable

SECTION 15 REGULATORY INFORMATION

Safety, health and environmental regulations / legislation specific for the substance or mixture

MINERAL OIL(NOT AVAIL.) IS FOUND ON THE FOLLOWING REGULATORY LISTS	
International Agency for Research on Cancer (IARC) - Agents Classified by the IARC Monographs	US - Vermont Permissible Exposure Limits Table Z-1-A Final Rule Limits for Air Contaminants
US - Alaska Limits for Air Contaminants	US - Vermont Permissible Exposure Limits Table Z-1-A Transitional Limits for Air Contaminants
US - California Permissible Exposure Limits for Chemical Contaminants	US - Washington Permissible exposure limits of air contaminants
US - California Proposition 65 - Carcinogens	US - Wyoming Toxic and Hazardous Substances Table Z1 Limits for Air Contaminants
US - Hawaii Air Contaminant Limits	US ACGIH Threshold Limit Values (TLV)
US - Idaho - Limits for Air Contaminants	US ACGIH Threshold Limit Values (TLV) - Carcinogens
US - Michigan Exposure Limits for Air Contaminants	US National Toxicology Program (NTP) 13th Report Part A Known to be Human Carcinogens
US - Minnesota Permissible Exposure Limits (PELs)	US NIOSH Recommended Exposure Limits (RELs)
US - Oregon Permissible Exposure Limits (Z-1)	US OSHA Permissible Exposure Levels (PELs) - Table Z1
US - Tennessee Occupational Exposure Limits - Limits For Air Contaminants	US Priority List for the Development of Proposition 65 Safe Harbor Levels - No Significant Risk Levels (NSRLs) for Carcinogens and Maximum Allowable Dose Levels (MADLs) for Chemicals Causing Reproductive Toxicity
PARAFFINIC DISTILLATE, HEAVY, HYDROTREATED (SEVERE)(64742-54-7.) IS FOUND ON THE FOLLOWING REGULATORY LISTS	

20186 MOTORBIKE 4T SYNTH 10W-60 OFFROAD RACE 1L

International Agency for Research on Cancer (IARC) - Agents Classified by the IARC Monographs	US - Vermont Permissible Exposure Limits Table Z-1-A Transitional Limits for Air Contaminants
US - Alaska Limits for Air Contaminants	US - Washington Permissible exposure limits of air contaminants
US - California Permissible Exposure Limits for Chemical Contaminants	US - Wyoming Toxic and Hazardous Substances Table Z1 Limits for Air Contaminants
US - California Proposition 65 - Carcinogens	US ACGIH Threshold Limit Values (TLV)
US - Hawaii Air Contaminant Limits	US ACGIH Threshold Limit Values (TLV) - Carcinogens
US - Idaho - Limits for Air Contaminants	US National Toxicology Program (NTP) 13th Report Part A Known to be Human Carcinogens
US - Michigan Exposure Limits for Air Contaminants	US NIOSH Recommended Exposure Limits (RELs)
US - Minnesota Permissible Exposure Limits (PELs)	US OSHA Permissible Exposure Levels (PELs) - Table Z1
US - Oregon Permissible Exposure Limits (Z-1)	US Priority List for the Development of Proposition 65 Safe Harbor Levels - No Significant Risk Levels (NSRLs) for Carcinogens and Maximum Allowable Dose Levels (MADLs) for Chemicals Causing Reproductive Toxicity
US - Tennessee Occupational Exposure Limits - Limits For Air Contaminants	US Toxic Substances Control Act (TSCA) - Chemical Substance Inventory
US - Vermont Permissible Exposure Limits Table Z-1-A Final Rule Limits for Air Contaminants	

PARAFFINIC DISTILLATE, HEAVY, SOLVENT-DEWAXED (SEVERE)(64742-65-0.) IS FOUND ON THE FOLLOWING REGULATORY LISTS

International Agency for Research on Cancer (IARC) - Agents Classified by the IARC Monographs	US - Vermont Permissible Exposure Limits Table Z-1-A Transitional Limits for Air Contaminants
US - Alaska Limits for Air Contaminants	US - Washington Permissible exposure limits of air contaminants
US - California Permissible Exposure Limits for Chemical Contaminants	US - Wyoming Toxic and Hazardous Substances Table Z1 Limits for Air Contaminants
US - California Proposition 65 - Carcinogens	US ACGIH Threshold Limit Values (TLV)
US - Hawaii Air Contaminant Limits	US ACGIH Threshold Limit Values (TLV) - Carcinogens
US - Idaho - Limits for Air Contaminants	US National Toxicology Program (NTP) 13th Report Part A Known to be Human Carcinogens
US - Michigan Exposure Limits for Air Contaminants	US NIOSH Recommended Exposure Limits (RELs)
US - Minnesota Permissible Exposure Limits (PELs)	US OSHA Permissible Exposure Levels (PELs) - Table Z1
US - Oregon Permissible Exposure Limits (Z-1)	US Priority List for the Development of Proposition 65 Safe Harbor Levels - No Significant Risk Levels (NSRLs) for Carcinogens and Maximum Allowable Dose Levels (MADLs) for Chemicals Causing Reproductive Toxicity
US - Tennessee Occupational Exposure Limits - Limits For Air Contaminants	US Toxic Substances Control Act (TSCA) - Chemical Substance Inventory
US - Vermont Permissible Exposure Limits Table Z-1-A Final Rule Limits for Air Contaminants	

PARAFFINIC DISTILLATE, LIGHT, HYDROTREATED (SEVERE)(64742-55-8.) IS FOUND ON THE FOLLOWING REGULATORY LISTS

International Agency for Research on Cancer (IARC) - Agents Classified by the IARC Monographs	US - Vermont Permissible Exposure Limits Table Z-1-A Transitional Limits for Air Contaminants
US - Alaska Limits for Air Contaminants	US - Washington Permissible exposure limits of air contaminants
US - California Permissible Exposure Limits for Chemical Contaminants	US - Wyoming Toxic and Hazardous Substances Table Z1 Limits for Air Contaminants
US - California Proposition 65 - Carcinogens	US ACGIH Threshold Limit Values (TLV)
US - Hawaii Air Contaminant Limits	US ACGIH Threshold Limit Values (TLV) - Carcinogens
US - Idaho - Limits for Air Contaminants	US National Toxicology Program (NTP) 13th Report Part A Known to be Human Carcinogens
US - Michigan Exposure Limits for Air Contaminants	US NIOSH Recommended Exposure Limits (RELs)
US - Minnesota Permissible Exposure Limits (PELs)	US OSHA Permissible Exposure Levels (PELs) - Table Z1
US - Oregon Permissible Exposure Limits (Z-1)	US Priority List for the Development of Proposition 65 Safe Harbor Levels - No Significant Risk Levels (NSRLs) for Carcinogens and Maximum Allowable Dose Levels (MADLs) for Chemicals Causing Reproductive Toxicity
US - Tennessee Occupational Exposure Limits - Limits For Air Contaminants	US Toxic Substances Control Act (TSCA) - Chemical Substance Inventory
US - Vermont Permissible Exposure Limits Table Z-1-A Final Rule Limits for Air Contaminants	

PARAFFINIC DISTILLATE, LIGHT, SOLVENT-DEWAXED (SEVERE)(64742-56-9.) IS FOUND ON THE FOLLOWING REGULATORY LISTS

International Agency for Research on Cancer (IARC) - Agents Classified by the IARC Monographs	US - Vermont Permissible Exposure Limits Table Z-1-A Transitional Limits for Air Contaminants
US - Alaska Limits for Air Contaminants	US - Washington Permissible exposure limits of air contaminants
US - California Permissible Exposure Limits for Chemical Contaminants	US - Wyoming Toxic and Hazardous Substances Table Z1 Limits for Air Contaminants
US - California Proposition 65 - Carcinogens	US ACGIH Threshold Limit Values (TLV)
US - Hawaii Air Contaminant Limits	US ACGIH Threshold Limit Values (TLV) - Carcinogens
US - Idaho - Limits for Air Contaminants	US National Toxicology Program (NTP) 13th Report Part A Known to be Human Carcinogens
US - Michigan Exposure Limits for Air Contaminants	US NIOSH Recommended Exposure Limits (RELs)
US - Minnesota Permissible Exposure Limits (PELs)	US OSHA Permissible Exposure Levels (PELs) - Table Z1
US - Oregon Permissible Exposure Limits (Z-1)	US Priority List for the Development of Proposition 65 Safe Harbor Levels - No Significant Risk Levels (NSRLs) for Carcinogens and Maximum Allowable Dose Levels (MADLs) for Chemicals Causing Reproductive Toxicity
US - Tennessee Occupational Exposure Limits - Limits For Air Contaminants	US Toxic Substances Control Act (TSCA) - Chemical Substance Inventory
US - Vermont Permissible Exposure Limits Table Z-1-A Final Rule Limits for Air Contaminants	

Federal Regulations**Superfund Amendments and Reauthorization Act of 1986 (SARA)****SECTION 311/312 HAZARD CATEGORIES**

Immediate (acute) health hazard	Yes
Delayed (chronic) health hazard	No
Fire hazard	No
Pressure hazard	No
Reactivity hazard	No

US. EPA CERCLA HAZARDOUS SUBSTANCES AND REPORTABLE QUANTITIES (40 CFR 302.4)

None Reported

State Regulations**US. CALIFORNIA PROPOSITION 65**

WARNING: This product contains a chemical known to the State of California to cause cancer and birth defects or other reproductive harm

Continued...

US - CALIFORNIA PREPOSITION 65 - CARCINOGENS & REPRODUCTIVE TOXICITY (CRT): LISTED SUBSTANCE

Soots, tars, and mineral oils (untreated and mildly treated oils and used engine oils) Listed

National Inventory	Status
Australia - AICS	N (mineral oil)
Canada - DSL	N (mineral oil)
Canada - NDSL	N (paraffinic distillate, heavy, hydrotreated (severe); paraffinic distillate, light, solvent-dewaxed (severe); paraffinic distillate, heavy, solvent-dewaxed (severe); mineral oil; paraffinic distillate, light, hydrotreated (severe))
China - IECSC	N (mineral oil)
Europe - EINEC / ELINCS / NLP	N (mineral oil)
Japan - ENCS	N (paraffinic distillate, light, solvent-dewaxed (severe); paraffinic distillate, heavy, solvent-dewaxed (severe); mineral oil)
Korea - KECI	N (mineral oil)
New Zealand - NZIoC	N (mineral oil)
Philippines - PICCS	N (mineral oil)
USA - TSCA	N (mineral oil)
Legend:	Y = All ingredients are on the inventory N = Not determined or one or more ingredients are not on the inventory and are not exempt from listing(see specific ingredients in brackets)

SECTION 16 OTHER INFORMATION**Other information**

Classification of the preparation and its individual components has drawn on official and authoritative sources as well as independent review by the Chemwatch Classification committee using available literature references.

A list of reference resources used to assist the committee may be found at:

www.chemwatch.net

The SDS is a Hazard Communication tool and should be used to assist in the Risk Assessment. Many factors determine whether the reported Hazards are Risks in the workplace or other settings. Risks may be determined by reference to Exposures Scenarios. Scale of use, frequency of use and current or available engineering controls must be considered.

Definitions and abbreviations

PC – TWA: Permissible Concentration-Time Weighted Average
 PC – STEL: Permissible Concentration-Short Term Exposure Limit
 IARC: International Agency for Research on Cancer
 ACGIH: American Conference of Governmental Industrial Hygienists
 STEL: Short Term Exposure Limit
 TEEL: Temporary Emergency Exposure Limit
 IDLH: Immediately Dangerous to Life or Health Concentrations
 OSF: Odour Safety Factor
 NOAEL :No Observed Adverse Effect Level
 LOAEL: Lowest Observed Adverse Effect Level
 TLV: Threshold Limit Value
 LOD: Limit Of Detection
 OTV: Odour Threshold Value
 BCF: BioConcentration Factors
 BEI: Biological Exposure Index

This document is copyright.

Apart from any fair dealing for the purposes of private study, research, review or criticism, as permitted under the Copyright Act, no part may be reproduced by any process without written permission from CHEMWATCH.

TEL (+61 3) 9572 4700.